



SPECIFICATIONS -MIDSOTA TILTS

MIDSOTA TBWB 17.6K

	102 x 24	102 x 26	102 x 28	102 x 30
Model #	N-TBWB24-176	N-TBWB26-176	N-TBWB28-176	N-TBWB30-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4760	5010	5160	5543
Payload	12840	12590	12440	12057
CHASSIS				
Coupler	2 5/16" Adjustable Channel Mount, Demco EZ Latch			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	8" x 3" Steel Tube			
Crossmembers	3" Steel Channel, 16" On-Center			
Axle	(2) 8000 lb. Slipper Spring Brake			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Tie Downs	Stake Pockets and Rub Rail			
Wiring	No Exposed Wiring			
Exterior Lights	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Hydraulic Components	Hydraulic Lock			
Coupler Height	11.5 - 19.5			
Deck Height	28			
Width Between Fender	82			
Load Angle	12			
DIMENSIONS				
Overall Length	346	370	394	418
Deck Height	28			
Coupler Height	11.5 - 19.5			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 22	102 x 24	102 x 26	102 x 30	102 x 32
Model #	N-TBWB22-220	N-TBWB24-220	N-TBWB26-220	N-TBWB30-220	N-TBWB32-220
CAPACITIES					
GVWR (lbs)	22000				
GAWR (lbs/axle)	10000				
Curb Weight	4875	4860	5110	5500	5560
Payload	17125	17140	16890	16500	16440
CHASSIS					
Coupler	2-5/16" 4-Bolt Flat Plate				
Tongue Jack	12K Drop Leg, Set-Back				
Frame	8" x 3" Steel Tube				
Crossmembers	3" Steel Channel, 16" On-Center				
Axle	(2) 10000 lb. Torsion Brake				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	ST235/75R17.15J 18-PLY				
Tie Downs	Stake Pockets and Rub Rail				
Wiring	No Exposed Wiring				
Exterior Lights	Full LED, DOT Compliant				
Decking	2" Pressure Treated Pine				
Hydraulic Components	Hydraulic Lock				
Coupler Height	0				
DIMENSIONS					
Coupler Height	0				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 22	102 x 24	102 x 26	102 x 28	102 x 32
Model #	N-TBWB22-184G	N-TBWB24-184G	N-TBWB26-184G	N-TBWB28-184G	N-TBWB32-184G
CAPACITIES					
GVWR (lbs)	18400				
GAWR (lbs/axle)	8000				
Curb Weight	5110	5360	5610	5760	6574
Payload	13290	13040	12790	12640	11826
CHASSIS					
Coupler	2-5/16" Adjustable Gooseneck				
Tongue Jack	Dual 12K, 2-Speed Landing Gear				
Frame	8" x 3" Steel Tube				
Crossmembers	3" Steel Channel, 16" On-Center				
Axle	(2) 8000 lb. Slipper Spring Brake				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	215/75R17.5J 18-PLY				
Tie Downs	Stake Pockets and Rub Rail				
Wiring	No Exposed Wiring				
Exterior Lights	Full LED, DOT Compliant				
Decking	2" Pressure Treated Pine				
Exterior Storage	Receiver Tube Winch Mount, Spare Tire Carrier				Spare Tire Carrier
Hydraulic Components	Hydraulic Lock				
Coupler Height	0				
DIMENSIONS					
Coupler Height	0				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA TILTS
MIDSOTA TBWB GN 23K

	102 x 22	102 x 26	102 x 28
Model #	N-TBWB22-230G	N-TBWB26-230G	N-TBWB28-230G
CAPACITIES			
GVWR (lbs)	23000		
GAWR (lbs/axle)	10000		
Curb Weight	5950	5710	5860
Payload	17050	17290	17140
CHASSIS			
Coupler	2-5/16" Adjustable Gooseneck		
Tongue Jack	Dual 12K, 2-Speed Landing Gear		
Frame	8" x 3" Steel Tube		
Crossmembers	3" Steel Channel, 16" On-Center		
Axle	(2) 10000 lb. Torsion Brake		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/75R17.15J 18-PLY		
Tie Downs	Stake Pockets and Rub Rail		
Wiring	No Exposed Wiring		
Exterior Lights	Full LED, DOT Compliant		
Decking	2" Pressure Treated Pine		
Exterior Storage	Receiver Tube Winch Mount, Spare Tire Carrier		
Hydraulic Components	Hydraulic Lock		
Coupler Height	0		
DIMENSIONS			
Coupler Height	0		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.