



| Model | Axle Description | Tire Size | GAWR | GVWR |
|-----------------------|------------------------|----------------------------|-------|-------|
| DERBY SR ANGLE | | | | |
| 8x60" DSA | 3500# Dexter | ST205/15 LRC Radial | 2990# | 2990# |
| 10x60" DSA | EZ Lube - 1/2 Cambered | | | |
| 12x60" DSA | | | | |
| 14x60" DSA | | | | |
| 10x77" DSA | | | | |
| 12x77" DSA | | | | |
| 14x77" DSA | | | | |
| 10x83" DSA | | | | |
| 12x83" DSA | | | | |
| 14x83" DSA | | | | |

Standard Equipment

- Coupler: 2" Stamped A-Frame
- Jack: 2000#
- Fenders: 9x32 Rolled
- Floor: 2" Treated Pine
- Stake Pockets
- LED Lights
- 48" Lay-N-Tailgate
- Colors: Refer to Chart

Frame Structure

- Frame: 3x2x3/16
- Toprail: 2x2x1/8
- Crossmembers: 3x2x3/16
- Tongue: 3" Channel Thru 10'
- Tongue: 4" Channel on 12'-14'
- Uprights: 2x2x1/8
- TG Uprights: 2" Sq Tube 14GA
- TG Horizontal Rungs: 3 Each Side 77-83 Only

Options

- Electric Brake SA w/Break Away & 7W Plug
- Flush Mount LED Lights
- 2" RAM Forged Coupler
- Fold Up Jack
- Set Back Jack
- Spare Rack
- Spare ST205/15 LRC on 5-Hole **Radial**
- Wrap Tongue
- Tilt Bed
- HD Diamond Plate Fender
- 66" Box in Place of 5 Box
- 72" Box in Place of 6.5
- Sidegate (SG) 48"x50"
- Spring Assist
- Make TG Upright
- Make TG 24" w/2' Dovetail

- Make TG 36" w/2' Dovetail
- Make TG Split
- Make TG or SG Bi-Fold
- Delete TG 60"
- Delete TG 77-83"
- SA-5200# Idler Axle w/ 225/15 Tire on 6H Wheel
- **Other Options Available**