



SPECIFICATIONS -STEEL DUMP UTILITY DUMP 10K

	76 x 10	76 x 12
Model #	H-UD7610-100	H-UD7612-100
CAPACITIES		
GVWR (lbs)	9990	
GAWR (lbs/axle)	5200	
Curb Weight	2310	2560
Payload	7680	7430
CHASSIS		
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue	5" Steel Channel, Fully Wrapped	
Tongue Jack	7K Drop Leg, Set-Back	
Frame	5" Steel Channel	
Crossmembers	3" Steel Channel	
Axle	(2) 5200 lb. Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST225/75R15D 8-PLY	
Wheels	15", 6-Lug Steel	
Tie Downs	D-Rings, Side Mounted	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 24" Tall	
Gate	NaN	
Decking	12-Gauge, One-Piece Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box	
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Power Down (Single Ram)	
Tarp	Integrated Tarp Mount and Shroud, Tarp Brackets	
Deck Height	24	
Height Overall	54.5	
Width Interior	76.25	
Width Ramp	14	
Length Ramp	60	
Width Tilting Deck	76.25	
DIMENSIONS		
Overall Length	182	206
Deck Width	76.25	
Deck Height	24	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL DUMP UTILITY DUMP 5K

62 x 8	
Model #	H-UD628-052
CAPACITIES	
GVWR (lbs)	5000
GAWR (lbs/axle)	5200
Curb Weight	1380
Payload	3620
CHASSIS	
Coupler	2-5/16" A-Frame, Posi-Lock
Tongue	4" Steel Channel
Tongue Jack	2K Coupler Mounted
Frame	4" Steel Channel
Crossmembers	3" Steel Channel
Axle	3500 lb. Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Tires	ST225/75R15D 8-PLY
Wheels	15", 6-Lug Steel
Tie Downs	D-Rings, Side Mounted
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Sides	12-Gauge, 15" Tall
Gate	NaN
Decking	12-Gauge, One-Piece Smooth Steel
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Power Down (Single Ram)
Tarp	Integrated Tarp Mount and Shroud, Tarp Brackets
Deck Height	24
Height Overall	45.5
Width Interior	62
Width Tilting Deck	62
DIMENSIONS	
Overall Length	158
Deck Width	62
Deck Height	24

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL DUMP UTILITY DUMP 7K

62 x 10	
Model #	H-UD6210-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
Curb Weight	1890
Payload	5110
CHASSIS	
Coupler	2-5/16" A-Frame, Posi-Lock
Tongue	4" Steel Channel
Tongue Jack	2K Coupler Mounted
Frame	4" Steel Channel
Crossmembers	3" Steel Channel
Axle	(2) 3500 lb. Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Tires	ST205/75R15C 6-PLY
Wheels	15", 5-Lug Steel
Tie Downs	D-Rings, Side Mounted
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Sides	12-Gauge, 15" Tall
Gate	NaN
Decking	12-Gauge, One-Piece Smooth Steel
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Power Down (Single Ram)
Tarp	Integrated Tarp Mount and Shroud, Tarp Brackets
Deck Height	24
Height Overall	45.5
Width Interior	62
Width Tilting Deck	62
DIMENSIONS	
Overall Length	182
Deck Width	62
Deck Height	24

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.