



MODEL	AXLE DESCRIPTION	TIRE SIZE	GAWR	GVWR
SKID STEER 10K				
12x81" SS10	2 - 5200# Dexter	ST225/75R/15 LRD	5080#	9990#
14x81" SS10	2 - Electric Brake Nev-R-Adjust			
16x81" SS10	E-Z Lube - 1/2 Cambered			
18x81" SS10				
20x81" SS10				
SKID STEER 14K				
12X81" SS14	2 - 7000# Dexter	ST235/80R/16 LRE	7000#	14000#
14x81" SS14	2 - Electric Brakes Nev-R-Adjust			
16x81" SS14	E-Z Lube - 1/2 Cambered			
18x81" SS14				
20x81" SS14				

Standard Equipment

- ST235/80R/16 LRE Tires on 8-Hole
- 2-7000# Dexter Electric Brakes

- 4" Drop Axles 1/2 Cambered w/EZ Lube Hubs
- 2 5/16" DEMCO Easy Latch Adjustable 5/Position Coupler
- 10000# Drop Leg Jack
- HD Diamond Plate Fender (Double Broke)
- Treated Pine Floor
- Break Away Unit w/Charger
- Slipper Spring
- Stake Pockets
- 4-5/8" D-Rings
- DOT Reflective Tape
- Flush Mount LED Lights
- Spare Rack
- Color: Stock

Frame Structure

- Frame: 6x4x5/16
- Front Bump Rail: 3" Square Tube
- Crossmembers: 3" Channel
- Tongue: 6" Channel Wrap

Options

- Spare ST235/80R/16 LRE on 8-Hole
- Additional Weld-on D-Rings 5/8"
- Rub Rail w/Stake Pockets (Per Linear FT)
- Pintle Eye Adjustable 35K
- Steel Tread Plate Floor
- 5' Slide-N Channel Ramps (Must Purchase Rear Stabilizer Jacks) (NA 12'-14')
- Rear Stabilizer Jack (5K Top Wind Pipe Mount)
- 5' Fold-up Channel Ramp w/Adjustable Knees & Spring Assist
- 5' XM Fold Up Channel Ramp w/Adjustable Knees & Spring Assist
- **Above Ramp is 24" Wide Covered w/Expanded Metal**
- **SS14 NA w/Gooseneck or 8K Axles**