



SPECIFICATIONS -ALUM TILTBED OPEN ALUMINUM SPEEDLOADER 7K

	82 x 18	82 x 20
Model #	H-EXA18-070	H-EXA20-070
CAPACITIES		
GVWR (lbs)	7000	
GAWR (lbs/axle)	3500	
Curb Weight	1670	1750
Payload	5330	5250
CHASSIS		
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue	6" Aluminum Channel, Fully Wrapped	
Tongue Jack	7K Drop Leg, Set-Back	
Frame	6" Aluminum Channel	
Crossmembers	3" Aluminum Channel	
Axle	(2) 3500 lb. Spring Brake	
Hubs	Easy Lube	
Tires	ST205/75R15C 6-PLY	
Wheels	15", 5-Lug Aluminum	
Tie Downs	Aluminum Rub Rails, Aluminum Stake Pockets	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Bulkhead	Aluminum Tube	
Dovetail	Reverse Taper Cut	
Decking	2" Pressure Treated Pine	
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box	
Hydraulic Components	12 Volt Hydraulic Pump	
Deck Height	24	
Height Overall	34	
Width Interior	82.25	
Width Between Fender	82.25	
Load Angle	14	12
Width Tilting Deck	82.25	
DIMENSIONS		
Overall Length	276	300
Deck Width	82.25	
Deck Height	24	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM TILTBED OPEN ALUMINUM SPEEDLOADER LP 7K

	82 x 18	82 x 20
Model #	H-EXLA18-070	H-EXLA20-070
CAPACITIES		
GVWR (lbs)	7000	
GAWR (lbs/axle)	3500	
Curb Weight	1650	1730
Payload	5350	5270
CHASSIS		
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue	6" Aluminum Channel, Fully Wrapped, Low Profile	
Tongue Jack	7K Drop Leg, Set-Back	
Frame	6" Aluminum Channel	
Crossmembers	3" Aluminum Channel	
Axle	(2) 3500 lb. Drop Spring Brake	
Hubs	Easy Lube	
Tires	ST205/75R15C 6-PLY	
Wheels	15", 5-Lug Aluminum	
Tie Downs	Aluminum Rub Rails, Aluminum Stake Pockets	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Bulkhead	Aluminum Tube	
Dovetail	Reverse Taper Cut	
Decking	2" Pressure Treated Pine	
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box	
Hydraulic Components	12 Volt Hydraulic Pump	
Deck Height	20.5	
Height Overall	32	
Width Interior	79.25	
Width Between Fender	79.25	
Load Angle	11	9
Width Tilting Deck	79.25	
DIMENSIONS		
Overall Length	276	300
Deck Width	79.25	
Deck Height	20.5	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM TILTBED OPEN ALUMINUM SPEEDLOADER 10K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-EXA18-100	H-EXA20-100	H-EXA22-100	H-EXA24-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5200			
Curb Weight	1950	2030	2250	2350
Payload	7950	7870	7650	7550
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	6" Aluminum Channel, Fully Wrapped			
Tongue Jack	7K Drop Leg, Set-Back			
Frame	8" Aluminum Channel			
Crossmembers	3" Aluminum Channel			
Axle	(2) 5200 lb. Spring Brake			
Hubs	Easy Lube			
Tires	ST225/75R15D 8-PLY			
Wheels	15", 6-Lug Aluminum			
Tie Downs	Aluminum Rub Rails, Aluminum Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	Aluminum Tube			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine			
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Hydraulic Components	12 Volt Hydraulic Pump			
Deck Height	24		26	24
Height Overall	34		36	
Width Interior	82.25			
Width Between Fender	82.25			
Load Angle	14	12	11	9
Width Tilting Deck	82.25			
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width	82.25			
Deck Height	24		26	24

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM TILTBED OPEN ALUMINUM SPEEDLOADER LP 10K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-EXLA18-100	H-EXLA20-100	H-EXLA22-100	H-EXLA24-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5200			
Curb Weight	1950	2030	2330	2430
Payload	7950	7870	7570	7470
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	6" Aluminum Channel, Fully Wrapped, Low Profile			
Tongue Jack	7K Drop Leg, Set-Back			
Frame	8" Aluminum Channel			
Crossmembers	3" Aluminum Channel			
Axle	(2) 5200 lb. Drop Spring Brake			
Hubs	Easy Lube			
Tires	ST225/75R15D 8-PLY			
Wheels	15", 6-Lug Aluminum			
Tie Downs	Aluminum Rub Rails, Aluminum Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	Aluminum Tube			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine			
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Hydraulic Components	12 Volt Hydraulic Pump			
Deck Height	20.5		22.5	
Height Overall	32		34	
Width Interior		79.25		
Width Between Fender		79.25		
Load Angle	11	9	8	6
Width Tilting Deck		79.25		
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width		79.25		
Deck Height	20.5		22.5	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM TILTBED OPEN ALUMINUM SPEEDLOADER 14K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-EXA18-140	H-EXA20-140	H-EXA22-140	H-EXA24-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	2170	2200	2400	2600
Payload	11830	11800	11600	11400
CHASSIS				
Coupler	2-5/16" Adjustable			
Tongue	6" Aluminum Channel, Fully Wrapped			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	8" Aluminum Channel			
Crossmembers	4" Aluminum Channel			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Aluminum			
Tie Downs	Aluminum Rub Rails, Aluminum Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	Aluminum Tube			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine			
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Hydraulic Components	12 Volt Hydraulic Pump			
Deck Height	24		26	24
Height Overall	34		36	
Width Interior	82.25			
Width Between Fender	82.25			
Load Angle	14	12	11	9
Width Tilting Deck	82.25			
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width	82.25			
Deck Height	24		26	24

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM TILTBED OPEN ALUMINUM SPEEDLOADER LP 14K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-EXLA18-140	H-EXLA20-140	H-EXLA22-140	H-EXLA24-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	2100	2180	2480	2580
Payload	11900	11820	11520	11420
CHASSIS				
Coupler	2-5/16" Adjustable			
Tongue	6" Aluminum Channel, Fully Wrapped, Low Profile			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	8" Aluminum Channel			
Crossmembers	4" Aluminum Channel			
Axle	(2) 7000 lb. Drop Spring Brake			
Hubs	Easy Lube			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Aluminum			
Tie Downs	Aluminum Rub Rails, Aluminum Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	Aluminum Tube			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine			
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Hydraulic Components	12 Volt Hydraulic Pump			
Deck Height	20.5		22.5	
Height Overall	32		34	
Width Interior		79.25		
Width Between Fender		79.25		
Load Angle	11	9	8	6
Width Tilting Deck		79.25		
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width		79.25		
Deck Height	20.5		22.5	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.