

HEAVY DUTY LOW PROFILE POWER TILT BUMPER PULL DECKOVER

- HD Tube Bulkhead
- Safety Chains
- Breakaway Switch with Battery
- EverLink™ Wiring Harness
- Diamond Plate Deck Over Wheels
- (6) 5/8" D-Rings (8 on units with stationary deck)
- Chain Spools
- 2" x 2" Tube Top Rail & Uprights
- Brakes on Both Axles
- Fold-Flat Ramp Gate
- Self-Retained Gate Pins
- Setback Jack
- Spare Tire Carrier



	8.5 x 22, 15K	8.5 x 22+4, 15K	8.5 x 22, 17.6K	8.5 x 22+4, 17.6K
Model #	ST-DOT10222-150	ST-DOT102224-150	ST-DOT10222-176	ST-DOT102224-176
GVWR (lbs)	15000		17600	
GAWR (lbs/axle)	7000		8000	
Curb Weight	4485	5170	4825	5370
Payload	10515	9830	12775	12230
Main Frame	W10 x 12#/ft., I-Beam			
Side Rails	6 x 2, 3/16 Wall Tube			
Cross Members	3" C-Channel (16" On-Center)			
Coupler	Adjustable Pintle Eye		Adjustable 4-Bolt Pintle Eye	
Jack	Setback HD 12K Drop Leg Jack			
Axles	Easy Lube Hubs with Brakes		Oil Bath Hubs with Brakes	
Suspension	Slipper Leaf Spring			
Tires	235/80R16 LRE		215/75R17.5 LRJ LRJ	
Wheels	16", 8 on 6.5, Radial		17.5", 8 on 6.5, Radial	
Decking	2 x 6 Pressure Treated Pine			
Lights	All LED Lights			
Electric Plug	7-Way RV-Style Molded Plug			
Finish	Industrial Grade Polymer Finish, High Gloss Black			
Overall Length	330"	378"	330"	378"
Deck Height	34"	34"	34"	34"
Coupler Height	Adjustable 21" - 29"			
Hydraulic Hoist	Dual Ram (Power Up / Power Down)			
Pump	3000 PSI Pump with Reservoir			
Battery	Group 24 Deep Cycle			
Load Angle	15 Degrees			

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.



Specifications are subject to change without notice, please reference dealership for final specifications.