



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC GN SPEEDLOADER 10K

	82 x 20	82 x 22	82 x 24
Model #	H-EX20-100G	H-EX22-100G	H-EX24-100G
CAPACITIES			
GVWR (lbs)	9900		
GAWR (lbs/axle)	5200		
Curb Weight	3500		4220
Payload	6400		5680
CHASSIS			
Coupler	2-5/16" Adjustable Gooseneck		
Tongue	10" Flange, 12 lb/ft I-Beam, Gooseneck		
Tongue Jack	Dual 12K Drop Leg		
Frame	6" Steel Channel		
Crossmembers	3" Steel Channel, 16" On-Center		
Axle	(2) 5200 lb. Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST225/75R15D 8-PLY		
Wheels	15", 6-Lug Steel		
Tie Downs	Banjo Tie-Downs, Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	HD Tube		
Dovetail	Reverse Taper Cut		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Integrated Gooseneck Tool and Pump Box, Spare Tire Carrier, Recessed In Neck		
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
DIMENSIONS			
Overall Length	340	364	388

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC GN SPEEDLOADER 14K

	82 x 18	82 x 20	82 x 24
Model #	H-EX18-140G	H-EX20-140G	H-EX24-140G
CAPACITIES			
GVWR (lbs)	14000		
GAWR (lbs/axle)	7000		
Curb Weight		4330	4500
Payload		9670	9500
CHASSIS			
Coupler	2-5/16" Adjustable Gooseneck		
Tongue	10" Flange, 12 lb/ft I-Beam, Gooseneck		
Tongue Jack	Dual 12K, 2-Speed Landing Gear		
Frame	6" Steel Channel		
Crossmembers	3" Steel Channel, 16" On-Center		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	Banjo Tie-Downs, Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Dovetail	Reverse Taper Cut		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Integrated Gooseneck Tool and Pump Box		
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
DIMENSIONS			
Overall Length	316	340	388

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC GN SPEEDLOADER 16K

82 x 24	
Model #	H-EX24-160G
CAPACITIES	
GVWR (lbs)	16000
GAWR (lbs/axle)	8000
Curb Weight	4560
Payload	11440
CHASSIS	
Coupler	2-5/16" Adjustable Gooseneck
Tongue	10" Flange, 12 lb/ft I-Beam, Gooseneck
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Frame	8" Steel Channel
Crossmembers	3" Steel Channel, 16" On-Center
Axle	(2) 8000 lb. Slipper Spring Brake
Hubs	Oil Bath
Exterior Finish	Industrial Grade Polymer Finish
Tires	215/75R17.5J 18-PLY
Wheels	17.5", 8-Lug Steel
Tie Downs	Banjo Tie-Downs
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Dovetail	Reverse Taper Cut
Decking	2" Pressure Treated Pine, Board Retainers
Exterior Storage	Spare Tire Carrier, Recessed In Neck, Tongue Mounted Lockable Battery and Pump Box
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead
DIMENSIONS	
Overall Length	388

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC GN SPEEDLOADER 7K

82 x 20	
Model #	H-EX20-070G
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
Curb Weight	3650
Payload	3350
CHASSIS	
Coupler	2-5/16" Adjustable Gooseneck
Tongue	10" Flange, 12 lb/ft I-Beam, Gooseneck
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Frame	6" Steel Channel
Crossmembers	3" Steel Channel, 16" On-Center
Axle	(2) 3500 lb. Slipper Spring Brake
Hubs	Easy Lube
Exterior Finish	Industrial Grade Polymer Finish
Tires	ST205/75R15C 6-PLY
Wheels	15", 5-Lug Steel
Tie Downs	Banjo Tie-Downs, Stake Pockets
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Dovetail	Reverse Taper Cut
Decking	2" Pressure Treated Pine, Board Retainers
Exterior Storage	Spare Tire Carrier, Recessed In Neck, Tongue Mounted Lockable Battery and Pump Box
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead
DIMENSIONS	
Overall Length	340

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC LP SPEEDLOADER 10K

	82 x 18	82 x 20	82 x 22
Model #	H-EXL18-100	H-EXL20-100	H-EXL22-100
CAPACITIES			
GVWR (lbs)	9900		
GAWR (lbs/axle)	5200		
Curb Weight		2650	3065
Payload		7250	6835
CHASSIS			
Coupler	2-5/16" A-Frame, Posi-Lock		
Tongue	5" Steel Channel, Fully Wrapped		
Tongue Jack	7K Drop Leg, Set-Back		
Frame	6" Steel Channel		
Crossmembers	3" Steel Channel, 16" On-Center		
Axle	(2) 5200 lb. Drop Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST225/75R15D 8-PLY		
Wheels	15", 6-Lug Steel		
Tie Downs	Banjo Tie-Downs, Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	HD Tube		
Dovetail	Reverse Taper Cut		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Tongue Mounted Lockable Battery and Pump Box		
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
DIMENSIONS			
Overall Length	276	300	324

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC LP SPEEDLOADER 14K

	82 x 22	82 x 24
Model #	H-EXL22-140	H-EXL24-140
CAPACITIES		
GVWR (lbs)	14000	
GAWR (lbs/axle)	7000	
Curb Weight	3200	3450
Payload	10800	10550
CHASSIS		
Coupler	2-5/16" Adjustable, Posi-Lock	
Tongue	6" Steel Channel, Fully Wrapped	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" Steel Channel	
Crossmembers	3" Steel Channel, 16" On-Center	
Axle	(2) 7000 lb. Drop Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16", 8-Lug Steel	
Tie Downs	Banjo Tie-Downs, Stake Pockets	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Bulkhead	Custom Formed	
Dovetail	Reverse Taper Cut	
Decking	2" Pressure Treated Pine, Board Retainers	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox	
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
DIMENSIONS		
Overall Length	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC LP SPEEDLOADER 7K

	82 x 18	82 x 20
Model #	H-EXL18-070	H-EXL20-070
CAPACITIES		
GVWR (lbs)	7000	
GAWR (lbs/axle)	3500	
Curb Weight	1960	1990
Payload	5040	5010
CHASSIS		
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue	5" Steel Channel, Fully Wrapped	
Tongue Jack	7K Drop Leg, Set-Back	
Frame	5" Steel Channel	
Crossmembers	3" Steel Channel	
Axle	(2) 3500 lb. Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST205/75R15C 6-PLY	
Wheels	15", 5-Lug Steel	
Tie Downs	Banjo Tie-Downs, Stake Pockets	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Bulkhead	Custom Formed	
Dovetail	Reverse Taper Cut	
Decking	2" Pressure Treated Pine, Board End Caps	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox	
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
DIMENSIONS		
Overall Length	276	300

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC SPEEDLOADER 10K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-EX18-100	H-EX20-100	H-EX22-100	H-EX24-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5200			
Curb Weight	2430	2620	2420	3030
Payload	7470	7280	7480	6870
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	5" Steel Channel, Fully Wrapped			
Tongue Jack	7K Drop Leg, Set-Back			
Frame	6" Steel Channel			
Crossmembers	3" Steel Channel, 16" On-Center			
Axle	(2) 5200 lb. Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST225/75R15D 8-PLY			
Wheels	15", 6-Lug Steel			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	Custom Formed			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine, Board End Caps			
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated			
DIMENSIONS				
Overall Length	276	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC SPEEDLOADER 16K

	82 x 20	82 x 24
Model #	H-EX20-160	H-EX24-160
CAPACITIES		
GVWR (lbs)	16000	
GAWR (lbs/axle)	8000	
Curb Weight	3380	4080
Payload	12620	11920
CHASSIS		
Coupler	2 5/16" Adjustable Channel Mount, Demco EZ Latch	
Tongue	6" Steel Channel, Fully Wrapped	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	8" Steel Channel	
Crossmembers	3" Steel Channel, 16" On-Center	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	Banjo Tie-Downs, Stake Pockets	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Bulkhead	Custom Formed	
Dovetail	Reverse Taper Cut	
Decking	2" Pressure Treated Pine, Board Retainers	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box	
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
DIMENSIONS		
Overall Length	300	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL ELECTRIC SPEEDLOADER 7K

82 x 18		82 x 20	
Model #	H-EX18-070		H-EX20-070
CAPACITIES			
GVWR (lbs)	7000		
GAWR (lbs/axle)	3500		
Curb Weight	1960		1990
Payload	5040		5010
CHASSIS			
Coupler	2-5/16" A-Frame, Posi-Lock		
Tongue	5" Steel Channel, Fully Wrapped		
Tongue Jack	7K Drop Leg, Set-Back		
Frame	5" Steel Channel		
Crossmembers	3" Steel Channel		
Axle	(2) 3500 lb. Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST205/75R15C 6-PLY		
Wheels	15", 5-Lug Steel		
Tie Downs	Banjo Tie-Downs, Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	Custom Formed		
Dovetail	Reverse Taper Cut		
Decking	2" Pressure Treated Pine, Board End Caps		
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox		
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
DIMENSIONS			
Overall Length	276	300	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL HEAVY DUTY ELECTRIC SPEEDLOADER 14K

	82 x 26	82 x 26	82 x 28
Model #	H-EXH26-140	H-EXH26-140G	H-EXH28-140G
CAPACITIES			
GVWR (lbs)	14000		
GAWR (lbs/axle)	7000		
Curb Weight	4000	4500	4800
Payload	10000	9500	9200
CHASSIS			
Coupler	2-5/16" Adjustable	2-5/16" Adjustable Gooseneck	
Tongue	6" Steel Channel, Fully Wrapped	10" Flange, 12 lb/ft I-Beam	
Tongue Jack	12K Drop Leg, Set-Back	Dual 12K Drop Leg	
Frame	8" Steel Channel		
Crossmembers	3" Steel Channel		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	Banjo Tie-Downs, Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Bulkhead	Custom Formed		
Dovetail	Reverse Taper Cut		
Decking	2" Pressure Treated Pine		
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox	Integrated Gooseneck Tool and Pump Box, Spare Tire Carrier, Recessed In Neck	
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
Coupler Height	13-21	34-42	
Deck Height	26.75		
Height Overall	35	71.75	
Width Interior	82.25		
Load Angle	10	8	
DIMENSIONS			
Overall Length	372	412	436
Deck Width	82.25		
Deck Height	26.75		
Coupler Height	13-21	34-42	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL HEAVY DUTY ELECTRIC SPEEDLOADER 16K

	82 x 26	82 x 26	82 x 28	82 x 30
Model #	H-EXH26-160	H-EXH26-160G	H-EXH28-160G	H-EXH30-160G
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
Curb Weight		4750		
Payload		11250		
CHASSIS				
Coupler	2 5/16" Adjustable Channel Mount, Demco EZ Latch	2-5/16" Adjustable Gooseneck		
Tongue	6" Steel Channel, Fully Wrapped	10" Flange, 12 lb/ft I-Beam, Gooseneck		
Frame	8" Steel Channel			
Crossmembers	3" Steel Channel, 16" On-Center			
Integrated Step(s)		Side Steps		
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Bulkhead	Custom Formed			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine			
Exterior Storage	Spare Tire Carrier, Tongue Mounted Toolbox	Integrated Gooseneck Tool and Pump Box, Spare Tire Carrier, Recessed In Neck, Tongue Mounted Lockable Battery and Pump Box		
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead			
DIMENSIONS				
Overall Length	372	412	436	460

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL MANUAL SPEEDLOADER 07K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-MX18-070	H-MX20-070	H-MX22-070	H-MX24-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
Curb Weight	1900	2010	2210	2450
Payload	5100	4990	4790	4550
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	5" Steel Channel, Fully Wrapped			
Tongue Jack	7K Drop Leg, Set-Back			
Frame	5" Steel Channel			
Crossmembers	3" Steel Channel, 16" On-Center			
Axle	(2) 3500 lb. Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST205/75R15C 6-PLY			
Wheels	15", 5-Lug Steel			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine, Board Retainers			
Exterior Storage	Spare Tire Carrier			
Hydraulic Components	Hydraulic Tilt Cylinder (MX) Manually Operated			
Deck Height	23.25			
Height Overall	33			
Width Interior	82.25			
Load Angle	14	12		
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width	82.25			
Deck Height	23.25			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL MANUAL SPEEDLOADER 10K

	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-MX18-100	H-MX20-100	H-MX22-100	H-MX24-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5200			
Curb Weight	2300	2450	2700	2830
Payload	7600	7450	7200	7070
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	5" Steel Channel, Fully Wrapped			
Tongue Jack	7K Drop Leg, Set-Back			
Frame	6" Steel Channel			
Crossmembers	3" Steel Channel, 16" On-Center			
Axle	(2) 5200 lb. Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST225/75R15D 8-PLY			
Wheels	15", 6-Lug Steel			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	Reverse Taper Cut			
Decking	2" Pressure Treated Pine, Board Retainers			
Exterior Storage	Spare Tire Carrier			
Hydraulic Components	Hydraulic Tilt Cylinder (MX) Manually Operated			
Deck Height			23.25	
Height Overall			33	
Width Interior			82.25	
Load Angle			11	9
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width			82.25	
Deck Height			23.25	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL TILT CAR HAULER ELECTRIC STEEL MANUAL SPEEDLOADER 14K

	82 x 20	82 x 22	82 x 24
Model #	H-MX20-140	H-MX22-140	H-MX24-140
CAPACITIES			
GVWR (lbs)	14000		
GAWR (lbs/axle)	7000		
Curb Weight	2800	3050	3150
Payload	11200	10950	10850
CHASSIS			
Coupler	2-5/16" Adjustable, Posi-Lock		
Tongue	6" Steel Channel, Fully Wrapped		
Tongue Jack	12K Drop Leg, Set-Back		
Frame	6" Steel Channel		
Crossmembers	3" Steel Channel, 16" On-Center		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	Banjo Tie-Downs, Stake Pockets		
Wiring	Sealed Wiring Harness		
Exterior Lights	Full LED, DOT Compliant		
Dovetail	Reverse Taper Cut		
Decking	2" Pressure Treated Pine, Board Retainers		
Exterior Storage	Spare Tire Carrier		
Hydraulic Components	Hydraulic Tilt Cylinder (MX) Manually Operated		
DIMENSIONS			
Overall Length	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.