

**POWERTRAIN**

ENGINE	KOHLER KT725	KAWASAKI FT730
HORSEPOWER	22	24
FUEL CAPACITY	10 GAL	10 GAL
GROUND SPEED	9 MPH	9 MPH
DISPLACEMENT	725 CC	725 CC
CRANKSHAFT	VERTICAL	VERTICAL
COOLING SYSTEM	AIR	AIR
CLUTCH	ELECTROMAGNETIC	ELECTROMAGNETIC
FUEL TYPE	GASOLINE	GASOLINE
TRANSMISSION	HYDRO-GEAR ZT-3200	HYDRO-GEAR ZT-3200

**GROUND FORCE DECK**

CUTTING HEIGHT	1.5" - 4.5"
SPINDLE SPECS	FORGED ALUMINUM HOUSING W/ SEALED BALL BEARINGS
BLADE TIP SPEED	17,500 FT/MIN
DECK THICKNESS	10 GA W/ 11 GAUGE REINFORCED SPINDLE MOUNT
BLADE SPECS	.203 STRAIGHTENED & HARDENED STEEL
DECK SIZE	44", 48", 54" & 60"

**OPERATOR'S STATION**

BACKREST	20" SEAT BACK
ROLLOVER PROTECTIVE STRUCTURES (UP/DOWN)	70" / 46.3"
ARM REST	PADDED ARM RESTS
TRACK	6" LOCKING TRACK
COVER	DURABLE SEWN VINYL COVER
STEERING CONTROLS	1.5" DIA GRIPS, ADJUSTABLE, DAMPENED
PARKING BRAKE	INTEGRATED INTO STEERING LEVERS

**CONSTRUCTION**

FRONT TIRES	13" X 6.5" X 6" FLAT FREE
OVERALL LENGTH	74 3/4"
REAR TIRES	44" & 48" DECKS - 23" X 8.5" • 54" & 60" DECKS - 22" X 12"
FEATURES	REINFORCED FORMED FRAME
FRAME GAUGE	7 GAUGE
OVERALL WIDTH (CHUTE UP)	44" - 44.75" • 48" - 48.75" • 54" - 54.75" • 60" - 60.75"
CASTER FORKS	3/8" FORMED
WEIGHT	44" - 950 LBS • 48" - 970 LBS • 54" - 1000 LBS • 60" - 1020 LBS
CASTER FORKS	SEALED BALL BEARINGS

**FEATURES TO MENTION**

FLOOR MAT	RUBBER FLOOR MAT
STORAGE	CUP HOLDER, DEEP STORAGE TRAY
DISCHARGE CHUTE	RUBBER DISCHARGE CHUTE
ACRES PER HOUR	4
MAINTENANCE	4 GREASE POINTS