

# RANGER PRO

## POWERTRAIN

ENGINE	KOHLER EKT750	KAWASAKI FX730
HORSEPOWER	27 EFI	23.5
FUEL CAPACITY	10 GAL	10 GAL
GROUND SPEED	10 MPH	10 MPH
DISPLACEMENT	747 CC	726 CC
CRANKSHAFT	VERTICAL	VERTICAL
COOLING SYSTEM	AIR	AIR
CLUTCH	ELECTROMAGNETIC	ELECTROMAGNETIC
FUEL TYPE	GASOLINE	GASOLINE
TRANSMISSION	HYDRO-GEAR ZT-3400	HYDRO-GEAR ZT-3400

## GROUND FORCE DECK

CUTTING HEIGHT	1.5" - 4.5"
SPINDLE SPECS	FORGED ALUMINUM HOUSING W/ SEALED BALL BEARINGS
BLADE TIP SPEED	18,000 FT/MIN
DECK THICKNESS	10 GA W/ 11 GAUGE REINFORCED SPINDLE MOUNT
BLADE SPECS	.203 STRAIGHTENED & HARDENED STEEL
DECK SIZE	54" & 60"

## OPERATOR'S STATION

BACKREST	18" SEAT BACK
ROLLOVER PROTECTIVE STRUCTURES (UP/DOWN)	70" / 46.3"
ARM REST	PADDED ARM RESTS
SUSPENSION	MECHANICAL
TRACK	6" LOCKING TRACK
COVER	DURABLE SEWN VINYL COVER
STEERING CONTROLS	1.5" DIA GRIPS, ADJUSTABLE, DAMPENED
PARKING BRAKE	INTEGRATED INTO STEERING LEVERS

## CONSTRUCTION

FRONT TIRES	13" X 6.5" X 6" FLAT - FREE
OVERALL LENGTH	74 3/4"
REAR TIRES	22" X 12" - 12R
FEATURES	REINFORCED FORMED FRAME
FRAME GAUGE	7 GAUGE
OVERALL WIDTH (CHUTE UP)	54" - 54.75" - 60" - 60.75"
CASTER FORKS	3/8" FORMED
WEIGHT	54" - 1040 LBS · 60" - 1060 LBS   54" - 1030 LBS · 60" - 1050 LBS
CASTER FORKS	SEALED BALL BEARINGS

## FEATURES TO MENTION

FLOOR MAT	RUBBER FLOOR MAT
STORAGE	CUP HOLDER, DEEP STORAGE TRAY
DISCHARGE CHUTE	RUBBER DISCHARGE CHUTE
ACRES PER HOUR	6



## NOTES

---



---



---