

POWERTRAIN

| | |
|----------------|--------------------|
| ENGINE | KOHLER ECV980 |
| HORSEPOWER | 38.5 EFI |
| FUEL CAPACITY | 12 GAL |
| GROUND SPEED | 12 MPH |
| DISPLACEMENT | 999 CC |
| CRANKSHAFT | VERTICAL |
| COOLING SYSTEM | AIR |
| CLUTCH | ELECTROMAGNETIC |
| FUEL TYPE | GASOLINE |
| TRANSMISSION | HYDRO-GEAR ZT-5400 |

DOMINATOR DECK

| | |
|-----------------|--|
| CUTTING HEIGHT | 1.5" - 5.5" |
| SPINDLE SPECS | CAST IRON HOUSING W/ TAPERED ROLLER BEARINGS |
| BLADE TIP SPEED | 18,500 FT/MIN |
| DECK THICKNESS | 7 GA SHELL W/ 7 GA DOUBLER PLATE |
| BLADE SPECS | .25 STRAIGHTENED & HARDENED STEEL |
| DECK SIZE | 60" & 72" |

OPERATOR'S STATION

| | |
|--|--------------------------------------|
| BACKREST | RECLINABLE |
| ROLLOVER PROTECTIVE STRUCTURES (UP/DOWN) | 75.5 / 48.5 |
| ARM REST | PADDED ADJUSTABLE ARM RESTS |
| SUSPENSION | PREMIUM AIR RIDE |
| TRACK | 6" LOCKING TRACK |
| COVER | DURABLE SEWN VINYL COVER |
| STEERING CONTROLS | 1.5" DIA GRIPS, ADJUSTABLE, DAMPENED |
| PARKING BRAKE | HAND LEVER OPERATED |
| DUAL USB PORT | W/ VOLTAGE |

CONSTRUCTION

| | |
|--------------------------|---------------------------------|
| FRONT TIRES | 13" X 6.5" X 6" FLAT FREE |
| OVERALL LENGTH | 85 1/4" |
| REAR TIRES | 26" X 12" - 12R |
| FEATURES | REINFORCED FORMED FRAME |
| FRAME GAUGE | 7 GAUGE |
| OVERALL WIDTH (CHUTE UP) | 60" - 61.5" / • 72" - 73.5" |
| CASTER FORKS | .5" FORMED |
| WEIGHT | 60" - 1567 LBS • 72" - 1601 LBS |
| CASTER FORKS | TAPERED ROLLER BEARINGS |

FEATURES TO MENTION

| | |
|-----------------|-------------------------------|
| FLOOR MAT | RUBBER FLOOR MAT |
| STORAGE | CUP HOLDER, DEEP STORAGE TRAY |
| DISCHARGE CHUTE | RUBBER DISCHARGE CHUTE |
| ACRES PER HOUR | 8 |
| MAINTENANCE | 9 GREASE POINTS |