



Model	Axle Description	Tire Size	GAWR	GVWR
GOOSENECK 240 LO PROFILE				
20x102" GN 240	2 - 10000# Dexter	ST235/80R/16 LRE	10000#	24000#
24x102" GN 240	2 - Electric Brakes Nev-R-Adjust			
28x102" GN 240	Oil Bath - 8 Lug			
32x102" GN 240				
36x102" GN 240				
40x102" GN 240				
20+5x102" GN 240				
25+5x102" GN 240				
27+5x102" GN 240				
30+5x102" GN 240				
35+5x102" GN 240				

Standard Equipment

- Coupler: 2 5/16" Round Adjustable
- Jack: Dual 10000# Drop Leg
- Floor: 2" Treated Pine
- Brake: Electric All Wheel
- Break Away Unit w/Charger
- Spare Tire Rack Inside Neck
- Lockable Toolbox Between Risers
- Winch Plate Between Risers
- Wiring Harness w/Sealed LED Lights
- Driver & Curb Side Steps w/Grab Handles
- DOT Reflective Tape
- 5 Leaf Slipper Spring Suspension
- Color: Black

Frame Structure

- Frame: 12"x16# I-Beam, 19# on 32' & Longer
- Neck: 12"x16# I-Beam
- Crossmembers: 3" Channel 16" OC Thru Frame
- Side Rails: 6" Channel
- 3/8x2 Flat Rubrail
- Stake Pockets 24" OC
- Pipe Spools Between Each Stake Pocket
- Frame to Crossmember Gussets
- Anti Flex Torx Tube on 32' & Longer
- Low Profile
- Dovetail w/Fold Over Spring Assist Ramps on +5 Models
- Deck Height: 34.5"

Options

- Spare ST235/80R/16 LRE on Dual
- Upgrade to ST235/85R/16 LRG on Dual
- Upgrade to 215/75R/17.5 LRH on Dual
- Single Wheel w/235/75R/17.5 LRJ Tire
- Jumbo Ramps
- 3rd Ramp on Dovetail
- HD Dozer Dovetail
- 7 1/2' Slide-N-Ramps
- Dual 2-Speed Jacks

- Dual Hydraulic Jack 12K Replacing Dual 12K Drop Leg Jack
- Deck Over Gooseneck
- 1" D-Rings
- Underbody Toolbox
- 2 - 10K Electric/Hydraulic Brakes w/Drum
- Dexter HD Adjustable Suspension
- Replace Slipper Spring Suspension w/Torsion
- Bridge Support Truss
- **Other Options Available**