



SPECIFICATIONS -ALUM UTILITY HHAORSA,HHAOTRSA ALUM RAIL SIDE

	5 x 10	6 x 12	7 x 14	5 x 8	6 x 10	7 x 10
Model #	H6010RSA-030	H6612RSA-030	H7614RSA-030	H6008RSA-030	H6610RSA-030	H7610RSA-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
Curb Weight	690	890	1010	650	810	830
Payload	2300	2100	1980	2340	2180	2160
CHASSIS						
Frame	3" x 2" x 3/16" Aluminum Angle					
Tongue	4" x 2" Aluminum Triple Tube, Fully Wrapped					
Crossmembers	3" x 2" x 3/16" Aluminum Angle					
Coupler	2" A-Frame, Posi-Lock					
Deck Width				60.25	66.25	76.25
Deck Height					17.5	
Tongue Jack	1K Swivel Jack with Caster Wheel					
Top Rail	2" x 2" Aluminum Tube					
Uprights	2" x 1 1/2" Aluminum Extrusion Tube					
Gate				57 x 54.5	63 x 54.5	73 x 54.5
Ramp(s)	54" Bi-Fold Aluminum					
Fenders	Radius Smooth Aluminum					
Axle	3500 lb. Spring Idler					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Decking	2" Pressure Treated Pine					
Tie Downs	Aluminum Stake Pockets					
Wiring	Sealed Wiring Harness					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Length Ramp					54.5	
Height Overall					49	
Width Interior				60.25	66.25	76.25
Width Ramp				57	63	73
DIMENSIONS						
Overall Length				142	165	172
Deck Width				60.25	66.25	76.25
Deck Height					17.5	
	7 x 12	7 x 12	7 x 12	7 x 14	7 x 14	7 x 14
Model #	H7612RSA-030	H8212RSA-030	H8212RSAV-030	H8214RSAV-030	H8214RSAV-030	H8214RSA-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
Curb Weight	920	980	1000	1090	1090	1050
Payload	2070	2010	1990	1900	1900	1940
CHASSIS						
Frame	3" x 2" x 3/16" Aluminum Angle					
Tongue	4" x 2" Aluminum Triple Tube, Fully Wrapped					
Crossmembers	3" x 2" x 3/16" Aluminum Angle					
Coupler	2" A-Frame, Posi-Lock					
Deck Width	76.25			82.25		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 12	7 x 12	7 x 12	7 x 14	7 x 14
Deck Height	17.5				
Tongue Jack	1K Swivel Jack with Caster Wheel				
Top Rail	2" x 2" Aluminum Tube				
Uprights	2" x 1 1/2" Aluminum Extrusion Tube				
Gate	73 x 54.5			79 x 54.5	
Ramp(s)	54" Bi-Fold Aluminum				
Fenders	Radius Smooth Aluminum				
Axle	3500 lb. Spring Idler				
Hubs	Easy Lube				
Tires	ST205/75R15C 6-PR				
Wheels	15", 5-Hole Aluminum				
Decking	2" Pressure Treated Pine				
Tie Downs	Aluminum Stake Pockets				
Wiring	Sealed Wiring Harness				
Exterior Lights	Full LED, DOT Compliant				
Warranty	Limited 3-Year Warranty				
Length Ramp	54.5				
Height Overall	49				
Width Interior	76.25			82.25	
Width Ramp	73			79	
DIMENSIONS					
Overall Length	196		201		225
Deck Width	76.25			82.25	
Deck Height	17.5				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM UTILITY HHAORSA,HHAOTRSA ALUM RAIL SIDE TANDEM

	7 x 20		7 x 22		82 x 24		7 x 24		7 x 14		7 x 14	
Model #	H7620TRSA-070		H8222TRSA-070		H8224TRSAV-070		H8224TRSA-070		H8214TRSA-070		H8214TRSAV-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
Curb Weight	1660		2100		2260				1485		1585	
Payload	5340		4900		4740				5515		5415	
CHASSIS												
Frame	3" x 2" x 3/16" Aluminum Angle				4" x 3" x 1/4" Aluminum Angle				3" x 2" x 3/16" Aluminum Angle			
Tongue	5" x 2" Aluminum Triple Tube											
Crossmembers	3" Aluminum Channel											
Coupler	2-5/16" A-Frame, Posi-Lock											
Deck Width	82.25											
Deck Height									18.5		17.5	
Tongue Jack	2K Set-Back											
Top Rail	2" x 2" Aluminum Tube											
Uprights	2" x 1 1/2" Aluminum Extrusion Tube											
Gate	79 x 54.5											
Ramp(s)	54" Bi-Fold Aluminum											
Fenders	Teardrop Smooth Aluminum											
Axle	(2) 3500 lb. Spring Brake											
Hubs	Easy Lube											
Tires	ST205/75R15C 6-PR											
Wheels	15", 5-Hole Aluminum						15", 5-Hole Aluminum					
Decking	2" Pressure Treated Pine											
Tie Downs	Aluminum Stake Pockets											
Wiring	Sealed Wiring Harness											
Exterior Lights	Full LED, DOT Compliant											
Warranty	Limited 3-Year Warranty						Limited 3-Year Warranty					
Length Ramp	54.5											
Height Overall	49											
Width Interior	82.25											
Width Ramp	79											
DIMENSIONS												
Overall Length	225											
Deck Width	82.25											
Deck Height									18.5		17.5	
	7 x 16		7 x 16		7 x 18		7 x 18		7 x 20		7 x 20	
Model #	H8216TRSAV-070		H8216TRSA-070		H8218TRSAV-070		H8218TRSA-070		H8220TRSA-070		H8220TRSAV-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
Curb Weight	1650		1550		1740		1640		1800		1900	
Payload	5350		5450		5260		5360		5200		5100	
CHASSIS												
Frame	3" x 2" x 3/16" Aluminum Angle				4" x 3" x 1/4" Aluminum Angle							
Tongue	5" x 2" Aluminum Triple Tube											
Crossmembers	3" Aluminum Channel											
Coupler	2-5/16" A-Frame, Posi-Lock											
Deck Width	82.25											
Deck Height	17.5		18.5		17.5		18.5		18.5		17.5	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 16	7 x 16	7 x 18	7 x 18	7 x 20	7 x 20
Tongue Jack	2K Set-Back					
Top Rail	2" x 2" Aluminum Tube					
Uprights	2" x 1 1/2" Aluminum Extrusion Tube					
Gate	79 x 54.5					
Ramp(s)	54" Bi-Fold Aluminum					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 3500 lb. Spring Brake					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum					
Decking	2" Pressure Treated Pine					
Tie Downs	Aluminum Stake Pockets					
Wiring	Sealed Wiring Harness					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Length Ramp	54.5					
Height Overall	49					
Width Interior	82.25					
Width Ramp	79					
DIMENSIONS						
Overall Length	249		273		297	
Deck Width	82.25					
Deck Height	17.5	18.5	17.5	18.5	17.5	
82 x 22						
Model #	H8222TRSAV-070					
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2180					
Payload	4820					
CHASSIS						
Frame	4" x 3" x 1/4" Aluminum Angle					
Tongue	5" x 2" Aluminum Triple Tube					
Crossmembers	3" Aluminum Channel					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	82.25					
Deck Height	17.5					
Tongue Jack	2K Set-Back					
Top Rail	2" x 2" Aluminum Tube					
Uprights	2" x 1 1/2" Aluminum Extrusion Tube					
Gate	79 x 54.5					
Ramp(s)	54" Bi-Fold Aluminum					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 3500 lb. Spring Brake					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Decking	2" Pressure Treated Pine					
Tie Downs	Aluminum Stake Pockets					
Wiring	Sealed Wiring Harness					
Exterior Lights	Full LED, DOT Compliant					
Length Ramp	54.5					
Height Overall	49					
Width Interior	82.25					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

82 x 22

Width Ramp	79
DIMENSIONS	
Overall Length	321
Deck Width	82.25
Deck Height	17.5

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.