

SPECIFICATIONS -CARGO STEEL ENCLOSED
HHSEHHRTR10,HHSEHHRTR14,HHSEHHRTR7,HHSETRTV10,HHSETRTV14,HHSETRTV7
HH SERIES CARGO ROUND TOP 10K

	6 x 12		8.5 x 14		8 x 14		6 x 14		7 x 12		7 x 14		
Model #	H7212TRT-100		H10114TRT-100		H9614TRT-100		H7214TRT-100		H8412TRT-100		H8414TRT-100		
CAPACITIES													
GVWR (lbs)	9900												
GAWR (lbs/axle)	5200												
Curb Weight			2700		2450				2100		2280		
Payload			7200		7450				7800		7620		
CHASSIS													
Frame	4" x 2" Steel Tube												
Tongue	4" x 2" Steel Tube		4" x 2" Steel Triple Tube				4" x 2" Steel Tube						
Crossmembers	Steel Formed Channel, 16" On-Center												
Coupler	2-5/16" A-Frame, Posi-Lock												
Deck Width											81		
Deck Length											153		177
Deck Height											19		
Tongue Jack	2K Coupler Mounted												
Wall Studs	Steel Tube, 24" On-Center												
Roof Bows	Galvanized Steel Tube, 24" On-Center												
Front Profile	Round												
Ramp(s)	4000 lb. with Assist												
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback												
Hubs	Easy Lube												
Tires	ST225/75R15D 8-PR												
Exterior Finish	.030" Aluminum												
Protective Coating(s)	Polyethylene Vapor Barrier												
Stone Guard	24" ATP												
Roof	Round Top												
Interior Walls	Engineered Wood												
Flooring	3/4" Engineered Wood												
Wiring	Enclosed in Conduit												
Exterior Lights	Full LED, DOT Compliant												
Warranty	Limited 3-Year Warranty												
Height Overall											103		
Height Interior											82		
Height Rear Opening											74.5		
Width Interior											81		
Width Rear Opening											78		
DIMENSIONS													
Overall Length											192		216
Deck Length											153		177
Deck Width											81		
Deck Height											19		
	7 x 16		8 x 16		8.5 x 16		7 x 18		8.5 x 18		8 x 18		
Model #	H8416TRT-100		H9616TRT-100		H10116TRT-100		H8418TRT-100		H10118TRT-100		H9618TRT-100		
CAPACITIES													
GVWR (lbs)	9900												
GAWR (lbs/axle)	5200												
Curb Weight	2400		2570		2850		2695		3150		2850		
Payload	7500		7330		7050		7205		6750		7050		
CHASSIS													

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 16	8 x 16	8.5 x 16	7 x 18	8.5 x 18	8 x 18
Frame	4" x 2" Steel Tube			6" x 2" Steel Tube		
Tongue	4" x 2" Steel Tube		4" x 2" Steel Triple Tube	6" x 2" Steel Tube	6" x 2" Steel Triple Tube	6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	81	93	98.5	81	98.5	93
Deck Length	201			225		
Deck Height	19	23		21	23	
Tongue Jack	2K Coupler Mounted			2K Coupler Mounted		
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	Round					
Ramp(s)	4000 lb. with Assist			4000 lb. with Assist		
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall	103	105		103	105	
Height Interior	82					
Height Rear Opening	74.5					
Width Interior	81	93	98.5	81	98.5	93
Width Between Fender	82			82		
Width Rear Opening	78	90		78	90	
DIMENSIONS						
Overall Length	242	246		266	270	
Deck Length	201			225		
Deck Width	81	93	98.5	81	98.5	93
Deck Height	19	23		21	23	
	7 x 20	8 x 20		8.5 x 20		
Model #	H8420TRT-100		H9620TRT-100		H10120TRT-100	
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	2770	3010		3200		
Payload	7130	6890		6700		
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Tube			6" x 2" Steel Triple Tube		
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	81	93		98.5		
Deck Length	249					
Deck Height	21	23				
Tongue Jack	2K Coupler Mounted					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

7 x 20

8 x 20

8.5 x 20

Front Profile	Round		
Ramp(s)		4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback		
Hubs	Easy Lube		
Tires	ST225/75R15D 8-PR		
Exterior Finish	.030" Aluminum		
Protective Coating(s)	Polyethylene Vapor Barrier		
Stone Guard	24" ATP		
Roof	Round Top		
Interior Walls	Engineered Wood		
Flooring	3/4" Engineered Wood		
Wiring	Enclosed in Conduit		
Exterior Lights	Full LED, DOT Compliant		
Warranty	Limited 3-Year Warranty		
Height Overall	103		105
Height Interior		82	
Height Rear Opening		74.5	
Width Interior	81	93	98.5
Width Between Fender			82
Width Rear Opening	78		90
DIMENSIONS			
Overall Length	290		294
Deck Length		249	
Deck Width	81	93	98.5
Deck Height	21		23

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

SPECIFICATIONS -CARGO STEEL ENCLOSED
HHSEHHRTR10,HHSEHHRTR14,HHSEHHRTR7,HHSETRTV10,HHSETRTV14,HHSETRTV7
HH SERIES CARGO ROUND TOP VNOSE 10K

	6 x 12		7 x 12		8.5 x 14		8 x 14		6 x 14		7 x 14	
Model #	H7212TRTV-100		H8412TRTV-100		H10114TRTV-100		H9614TRTV-100		H7214TRTV-100		H8414TRTV-100	
CAPACITIES												
GVWR (lbs)	9900											
GAWR (lbs/axle)	5200											
Curb Weight					2870		2490				2350	
Payload					7030		7410				7550	
CHASSIS												
Frame	4" x 2" Steel Tube											
Tongue	4" x 2" Steel Tube				4" x 2" Steel Triple Tube				4" x 2" Steel Tube			
Crossmembers	Steel Formed Channel, 16" On-Center											
Coupler	2-5/16" A-Frame, Posi-Lock											
Tongue Jack	2K Coupler Mounted											
Wall Studs	Steel Tube, 24" On-Center											
Roof Bows	Galvanized Steel Tube, 24" On-Center											
Ramp(s)	4000 lb. with Assist											
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback											
Hubs	Easy Lube											
Tires	ST225/75R15D 8-PR											
Exterior Finish	.030" Aluminum											
Protective Coating(s)	Polyethylene Vapor Barrier											
Stone Guard	24" ATP											
Roof	Round Top											
Interior Walls	Engineered Wood											
Flooring	3/4" Engineered Wood											
Wiring	Enclosed in Conduit											
Exterior Lights	Full LED, DOT Compliant											
Warranty	Limited 3-Year Warranty											
	7 x 16		8.5 x 16		8 x 16		7 x 18		8 x 18		8.5 x 18	
Model #	H8416TRTV-100		H10116TRTV-100		H9616TRTV-100		H8418TRTV-100		H9618TRTV-100		H10118TRTV-100	
CAPACITIES												
GVWR (lbs)	9900											
GAWR (lbs/axle)	5200											
Curb Weight	2500		2950		2650		2890				2850	
Payload	7400		6950		7250		7010				7050	
CHASSIS												
Frame	4" x 2" Steel Tube						6" x 2" Steel Tube					
Tongue	4" x 2" Steel Tube		4" x 2" Steel Triple Tube		4" x 2" Steel Tube		6" x 2" Steel Tube				6" x 2" Steel Triple Tube	
Crossmembers	Steel Formed Channel, 16" On-Center											
Coupler	2-5/16" A-Frame, Posi-Lock											
Tongue Jack	2K Coupler Mounted						2K Coupler Mounted					
Wall Studs	Steel Tube, 24" On-Center											
Roof Bows	Galvanized Steel Tube, 24" On-Center											
Ramp(s)	4000 lb. with Assist						4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback											
Hubs	Easy Lube											
Tires	ST225/75R15D 8-PR											
Exterior Finish	.030" Aluminum											
Protective Coating(s)	Polyethylene Vapor Barrier											
Stone Guard	24" ATP											
Roof	Round Top											

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 16	8.5 x 16	8 x 16	7 x 18	8 x 18	8.5 x 18
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8.5 x 20	7 x 20			8 x 20	
Model #	H10120TRTV-100	H8420TRTV-100			H9620TRTV-100	
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	3280	2870			3070	
Payload	6620	7030			6830	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube	6" x 2" Steel Tube				
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue Jack	2K Coupler Mounted				2K Coupler Mounted	
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Ramp(s)	4000 lb. with Assist				4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

SPECIFICATIONS -CARGO STEEL ENCLOSED
HHSEHHRTR10,HHSEHHRTR14,HHSEHHRTR7,HHSETRTV10,HHSETRTV14,HHSETRTV7
HH SERIES CARGO ROUND TOP 14K

	6 x 12	7 x 12	8 x 14	7 x 14	6 x 14	8.5 x 14
Model #	H7212TRT-140	H8412TRT-140	H9614TRT-140	H8414TRT-140	H7214TRT-140	H10114TRT-140
CAPACITIES						
GVWR (lbs)	14000	9900			14000	
GAWR (lbs/axle)	7000	5200			7000	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	Round					
Ramp(s)			4000 lb. with Assist			4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	7 x 16	8.5 x 16	8 x 16	8.5 x 18	7 x 18	8 x 18
Model #	H8416TRT-140	H10116TRT-140	H9616TRT-140	H10118TRT-140	H8418TRT-140	H9618TRT-140
CAPACITIES						
GVWR (lbs)				14000		
GAWR (lbs/axle)				7000		
Curb Weight	3050		2850	3500	3070	
Payload	10950		11150	10500	10930	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	Round					
Ramp(s)			4000 lb. with Assist			4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 16	8.5 x 16	8 x 16	8.5 x 18	7 x 18	8 x 18
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8 x 20	8.5 x 20			7 x 20	
Model #	H9620TRT-140	H10120TRT-140			H8420TRT-140	
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	3320	3250			3200	
Payload	10680	10750			10800	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	Round					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

SPECIFICATIONS -CARGO STEEL ENCLOSED
HHSEHHRTR10,HHSEHHRTR14,HHSEHHRTR7,HHSETRTV10,HHSETRTV14,HHSETRTV7
HH SERIES CARGO ROUND TOP VNOSE 14K

	7 x 12	6 x 12	6 x 14	7 x 14	8.5 x 14	8 x 14
Model #	H8412TRTV-140	H7212TRTV-140	H7214TRTV-140	H8414TRTV-140	H10114TRTV-140	H9614TRTV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight					3160	
Payload					10840	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Ramp(s)					4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	.030 Aluminum Sheet, Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8.5 x 16	7 x 16	8 x 16	7 x 18	8 x 18	8.5 x 18
Model #	H10116TRTV-140	H8416TRTV-140	H9616TRTV-140	H8418TRTV-140	H9618TRTV-140	H10118TRTV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	3190		2930		3250	
Payload	10810		11070		10750	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Ramp(s)	4000 lb. with Assist		4000 lb. with Assist		4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	.030 Aluminum Sheet, Round Top					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 16	7 x 16	8 x 16	7 x 18	8 x 18	8.5 x 18
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	7 x 20	8 x 20			8.5 x 20	
Model #	H8420TRTV-140	H9620TRTV-140			H10120TRTV-140	
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	3150	3400			3450	
Payload	10850	10600			10550	
CHASSIS						
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	.030 Aluminum Sheet, Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

SPECIFICATIONS -CARGO STEEL ENCLOSED
HHSEHHRTR10,HHSEHHRTR14,HHSEHHRTR7,HHSETRTV10,HHSETRTV14,HHSETRTV7
HH SERIES CARGO ROUND TOP 07K

	8.5 x 12		6 x 12		6 x 14		8.5 x 14		8 x 14		7 x 12	
Model #	H10112TRT-070		H7212TRT-070		H7214TRT-070		H10114TRT-070		H9614TRT-070		H8412TRT-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
Curb Weight					1770				2310		1850	
Payload					5230				4690		5150	
CHASSIS												
Frame	4" x 2" Steel Tube											
Tongue	4" x 2" Steel Triple Tube		4" x 2" Steel Tube				4" x 2" Steel Triple Tube				4" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center											
Coupler	2-5/16" A-Frame, Posi-Lock											
Deck Width												
Deck Length												
Deck Height												
Tongue Jack	2K Coupler Mounted								2K Coupler Mounted			
Wall Studs	Steel Tube, 24" On-Center											
Roof Bows	Galvanized Steel Tube, 24" On-Center											
Front Profile	Round											
Ramp(s)	4000 lb. with Assist								4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback											
Hubs	Easy Lube											
Tires	ST205/75R15C 6-PR											
Exterior Finish	.030" Aluminum											
Protective Coating(s)	Polyethylene Vapor Barrier											
Stone Guard	24" ATP											
Roof	Round Top											
Interior Walls	Engineered Wood											
Flooring	3/4" Engineered Wood											
Wiring	Enclosed in Conduit											
Exterior Lights	Full LED, DOT Compliant											
Warranty	Limited 3-Year Warranty											
Height Overall												
Height Interior												
Height Rear Opening												
Width Interior												
Width Rear Opening												
DIMENSIONS												
Overall Length												
Deck Length												
Deck Width												
Deck Height												
	7 x 14		7 x 16		8.5 x 16		8 x 16		7 x 18		8 x 18	
Model #	H8414TRT-070		H8416TRT-070		H10116TRT-070		H9616TRT-070		H8418TRT-070		H9618TRT-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
Curb Weight	2050		2180		2710		2350		2545		2670	
Payload	4950		4820		4290		4650		4455		4330	
CHASSIS												
Frame	4" x 2" Steel Tube						6" x 2" Steel Tube					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 14	7 x 16	8.5 x 16	8 x 16	7 x 18	8 x 18
Tongue	4" x 2" Steel Tube		4" x 2" Steel Triple Tube	4" x 2" Steel Tube	6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	81		98.5	93	81	93
Deck Length	177		201		225	
Deck Height	18		22		20	22
Tongue Jack			2K Coupler Mounted			2K Coupler Mounted
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	Round					
Ramp(s)			4000 lb. with Assist			4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall	102		104		102	104
Height Interior			82			
Height Rear Opening			74.5			
Width Interior	81		98.5	93	81	93
Width Between Fender			82			82
Width Rear Opening	78		90		78	90
DIMENSIONS						
Overall Length	216	242	246		266	270
Deck Length	177		201		225	
Deck Width	81		98.5	93	81	93
Deck Height	18		22		20	22
	8.5 x 18	7 x 20	8 x 20	8.5 x 20		
Model #	H10118TRT-070	H8420TRT-070	H9620TRT-070	H10120TRT-070		
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2750	2570	2800	2950		
Payload	4250	4430	4200	4050		
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube		6" x 2" Steel Tube		6" x 2" Steel Triple Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	98.5	81	93	98.5		
Deck Length	225		249			
Deck Height	22	20		22		
Tongue Jack	2K Coupler Mounted			2K Coupler Mounted		
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	Round					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 18	7 x 20	8 x 20	8.5 x 20
Ramp(s)	4000 lb. with Assist		4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Hubs	Easy Lube			
Tires	ST205/75R15C 6-PR			
Exterior Finish	.030" Aluminum			
Protective Coating(s)	Polyethylene Vapor Barrier			
Stone Guard	24" ATP			
Roof	Round Top			
Interior Walls	Engineered Wood			
Flooring	3/4" Engineered Wood			
Wiring	Enclosed in Conduit			
Exterior Lights	Full LED, DOT Compliant			
Warranty	Limited 3-Year Warranty			
Height Overall	104	102	104	
Height Interior	82			
Height Rear Opening	74.5			
Width Interior	98.5	81	93	98.5
Width Between Fender	82	82		
Width Rear Opening	90	78	90	
DIMENSIONS				
Overall Length	270	290	294	
Deck Length	225	249		
Deck Width	98.5	81	93	98.5
Deck Height	22	20	22	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

SPECIFICATIONS -CARGO STEEL ENCLOSED
HHSEHHRTR10,HHSEHHRTR14,HHSEHHRTR7,HHSETRTV10,HHSETRTV14,HHSETRTV7
HH SERIES CARGO ROUND TOP VNOSE 07K

	6 x 12	7 x 12	6 x 14	8 x 14	8.5 x 14	7 x 14
Model #	H7212TRTV-070	H8412TRTV-070	H7214TRTV-070	H9614TRTV-070	H10114TRTV-070	H8414TRTV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	1770	1930	1950	2530	2620	2125
Payload	5230	5070	5050	4470	4380	4875
CHASSIS						
Frame	4" x 2" Steel Tube					
Tongue	4" x 2" Steel Tube			4" x 2" Steel Triple Tube		4" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
	7 x 16	8 x 16	8.5 x 16	8.5 x 18	8 x 18	7 x 18
Model #	H8416TRTV-070	H9616TRTV-070	H10116TRTV-070	H10118TRTV-070	H9618TRTV-070	H8418TRTV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2230	2430	2790		2750	2450
Payload	4770	4570	4210		4250	4550
CHASSIS						
Frame	4" x 2" Steel Tube			6" x 2" Steel Tube		
Tongue	4" x 2" Steel Tube	4" x 2" Steel Triple Tube		6" x 2" Steel Triple Tube	6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 16	8 x 16	8.5 x 16	8.5 x 18	8 x 18	7 x 18
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
	8 x 20		7 x 20		8.5 x 20	
Model #	H9620TRTV-070		H8420TRTV-070		H10120TRTV-070	
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2880		2470		2830	
Payload	4120		4530		4170	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Tube			6" x 2" Steel Triple Tube		
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue Jack	2K Coupler Mounted				2K Coupler Mounted	
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Ramp(s)	4000 lb. with Assist				4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.