



**SPECIFICATIONS -ST DLX CARGO
ST DLX FLAT TOP V-NOSE 3K**

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Model #	K-DX6008-030	K-DX6010-030	K-DX7210-030	K-DX7212-030	K-DX7214-030	K-DX8412-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" x 2" Steel Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Crossmembers	Formed Steel, 24" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	66"		78"			84"
Ramp(s)	150 Series with Assist					250 Series with Assist
Side Door	No STD Side Entry Door	32" Wide Flush Lock, Plastic Holdback			36" Wide Flush Lock, Plastic Holdback	
Axle	3500 lb. Drop Spring Idler					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Luan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams (std colors only), Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	62		74			80
Width Rear Opening	53.5		65.5			77.5
Coupler Height	17					
Deck Height	18					
Height Overall	87		99			104
Deck Length	107	131		155	179	155
Width Interior	57		69			81
Length Interior Box	93	117		141	165	141
DIMENSIONS						
Overall Length	146	170		194	218	200
Deck Length	107	131		155	179	155
Deck Width	57		69			81
Deck Height	18					
Coupler Height	17					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -ST DLX CARGO
ST DLX FLAT TOP V-NOSE 7K**

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	8.5 x 14
Model #	K-DX7212-070	K-DX7214-070	K-DX8412-070	K-DX8414-070	K-DX8416-070	K-DX10214-070
CAPACITIES						
GVWR (lbs)				7000		
GAWR (lbs/axle)				3500		
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	4" x 2" Steel Tube				6" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Crossmembers	Formed Steel, 24" On-Center				Formed Steel, 16" On-Center	
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	78"			84"		
Ramp(s)	150 Series with Assist		250 Series with Assist		400 Series with Assist	
Side Door	36" Wide Flush Lock, Plastic Holdback					
Integrated Step(s)						Interior Recessed
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier				BATTLECOAT Polyurea Coating	
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Lauan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams (std colors only), Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount				(2) LED Dome Lights, Wall Mount	
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	74			80		
Width Rear Opening	65.5		77.5		93.5	
Coupler Height	18			20		
Deck Height	19			21		
Height Overall	100			105		
Deck Length	155	179	155	179	203	179
Width Interior	69		81			97
Width Between Fender	81.5					
Length Interior Box	141	165	141	165	189	165
DIMENSIONS						
Overall Length	194	218	200	224	248	224
Deck Length	155	179	155	179	203	179

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	8.5 x 14
Deck Width	69			81		97
Deck Height			19			21
Coupler Height			18			20

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	K-DX10216-070	K-DX10218-070	K-DX10220-070	K-DX10222-070	K-DX10224-070	K-DX10226-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	6" x 2" Steel Tube					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Plastic Holdback					
Integrated Step(s)	Interior Recessed					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Luan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams (std colors only), Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	80					
Width Rear Opening	93.5					
Coupler Height	20					
Deck Height	21					
Height Overall	107					
Deck Length	203	227	251	275	299	323
Width Interior	97					
Width Between Fender	81.5					
Length Interior Box	189	213	237	261	285	309
DIMENSIONS						
Overall Length	248	272	296	320	344	368
Deck Length	203	227	251	275	299	323

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Deck Width				97		
Deck Height				21		
Coupler Height				20		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -ST DLX CARGO
ST DLX FLAT TOP V-NOSE 10K**

	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Model #	K-DX10214-100	K-DX10216-100	K-DX10218-100	K-DX10220-100	K-DX10222-100	K-DX10224-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	6" x 2" Steel Tube					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Plastic Holdback					
Integrated Step(s)	Interior Recessed					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Luan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams (std colors only), Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST225/75R15D 8-PLY					
Wheels	15", 6-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	80					
Width Rear Opening	93.5					
Coupler Height	21					
Deck Height	22					
Height Overall	108					
Deck Length	179	203	227	251	275	299
Width Interior	97					
Width Between Fender	81.5					
Length Interior Box	165	189	213	237	261	285
DIMENSIONS						
Overall Length	224	248	272	296	320	344
Deck Length	179	203	227	251	275	299

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Deck Width				97		
Deck Height				22		
Coupler Height				21		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 26	
Model #	K-DX10226-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Coupler	2-5/16" A-Frame
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted
Front Profile	16" V-Nose
Frame	6" x 2" Steel Tube
Crossmembers	Formed Steel, 16" On-Center
Roof Bows	Steel Tube, 24" On-Center
Wall Posts	Steel Tube, 24" On-Center
Standard Interior Height	84"
Ramp(s)	400 Series with Assist
Side Door	36" Wide Flush Lock, Plastic Holdback
Integrated Step(s)	Interior Recessed
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Undercoating	Asphalt Emulsion
Protective Coating(s)	BATTLECOAT Polyurea Coating
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Engineered Wood Wall Transitions
Ceiling	Luan Strip
Exterior Finish	.030" Aluminum
Exterior Fastening	Color Matching Screws on Seams (std colors only), Semi-Screwless Sidewalls
Stone Guard	24" ATP
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion
Roof	Flat Top Seamless Aluminum
Tires	ST225/75R15D 8-PLY
Wheels	15", 6-Lug Steel
Vents	Sidewall Airflow
Interior Lights	(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Switches	(1) Dome Light, 12V
Height Rear Opening	80
Width Rear Opening	93.5
Coupler Height	21
Deck Height	22
Height Overall	108
Deck Length	323
Width Interior	97
Width Between Fender	81.5
Length Interior Box	309
DIMENSIONS	
Overall Length	368
Deck Length	323

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 26	
Deck Width	97
Deck Height	22
Coupler Height	21

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.