



## ALUMINUM SOLID SIDE - SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
<b>Model</b>	H6008SSA-030	H6010SSA-030	H6610SSA-030	H6612SSA-030	H7610SSA-030	H7612SSA-030	H8212SSA-030	H8214SSA-030
<b>GAWR (lb./axle)</b>	3500	3500	3500	3500	3500	3500	3500	3500
<b>GVWR (lb.)</b>	2990	2990	2990	2990	2990	2990	2990	2990
<b>Curb Weight (lb.)</b>	740	830	850	950	880	1010	1040	1130
<b>Payload Capacity (lb.)</b>	2250	2160	2140	2040	2110	1980	1950	1860
<b>Frame Construction</b>	Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP	
<b>Crossmembers</b>	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
<b>Top Rail</b>	None	None	None	None	None	None	None	None
<b>Uprights/Sides</b>	Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP		Formed 1/8" ATP	
<b>Tongue Construction</b>	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube
<b>Coupler</b>	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
<b>Coupler Height</b>	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
<b>Safety Chains</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>Jack</b>	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel	1K Swivel
<b>Axle Type</b>	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
<b>Brakes</b>	-	-	-	-	-	-	-	-
<b>Breakaway Kit</b>	-	-	-	-	-	-	-	-
<b>Tires</b>	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
<b>Wheels</b>	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
<b>Trailer Plug</b>	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
<b>Exterior Lighting</b>	LED	LED	LED	LED	LED	LED	LED	LED
<b>Decking</b>	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
<b>Ramp Style</b>	Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate	
<b>Ramp Length x Width</b>	54 1/2" x 57"	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
<b>Load Capacity (lb.)</b>	2200	2200	2200	2200	2200	2200	2200	2200
<b>Overall Length</b>	11'-10"	13'-10"	13'-9"	15'-9"	14'-4"	16'-4"	16'-9"	18'-9"
<b>Overall Width</b>	78 1/4"	78 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
<b>Overall Height</b>	49"	49"	49"	49"	49"	49"	49"	49"
<b>Deck Height</b>	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
<b>Deck Length</b>	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
<b>Deck Width</b>	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

### STANDARD FEATURES

<p>Formed 1/8" Polished Aluminum Diamond Plate Frame</p> <p>3" Aluminum Channel Crossmembers</p> <p>Formed 1/8" Polished Aluminum Diamond Plate Sides 15" Tall Sides</p> <p>Aluminum Tube Tongue with Cross Brace</p> <p>A-Frame Posi-Lock Coupler</p>	<p>Dual Safety Chains and Hooks</p> <p>1K Rated Swivel Jack with Caster Wheel</p> <p>2x8 Treated, #1 Grade Wood Decking</p> <p>Front and Rear End Caps</p> <p>54" Bi-fold Gate</p> <p>Aluminum Radius Fenders</p>	<p>Spring Suspension with Easy Lube Hubs</p> <p>Radial Tires on Aluminum Wheels</p> <p>Sealed Wiring Harness</p> <p>Full LED, DOT Compliant Lighting</p> <p>D-ring Tie Downs, Floor Mounted</p>
--	---	---