



SPECIFICATIONS -CAM DUMP PBTD132 CAM BEAST DUAL TELE DUMP 13.2K

	7 x 12	7 x 14
Model #	P-BTD8212-132	P-BTD8214-132
CAPACITIES		
GVWR (lbs)	13200	
GAWR (lbs/axle)	6000	
Curb Weight	4240	4500
Payload	8960	8700
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" x 3" x 3/16" Steel Tube	
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 6000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	ST235/80R16E 10-PR	
Wheels	16", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 20" Tall	
Gate	NaN	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM DUMP PBTD132
CAM BEAST DUAL TELE DUMP 15.4K**

	7 x 14	7 x 16
Model #	P-BTD8214-154	P-BTD8216-154
CAPACITIES		
GVWR (lbs)	15400	
GAWR (lbs/axle)	7000	
Curb Weight	4540	4800
Payload	10860	10600
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" x 3" x 3/16" Steel Tube	6" x 3" x 1/4" Steel Tube
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 7000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	ST235/80R16E 10-PR	
Wheels	16", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 20" Tall	
Gate	NaN	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM DUMP PBTD132
CAM BEAST DUAL TELE DUMP 17.6K**

	7 x 14	7 x 16
Model #	P-BTD8214-176	P-BTD8216-176
CAPACITIES		
GVWR (lbs)	17600	
GAWR (lbs/axle)	8000	
Curb Weight	5040	5300
Payload	12560	12300
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" x 3" x 3/16" Steel Tube	6" x 3" x 1/4" Steel Tube
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	215/75R17.5J 18-PR	
Wheels	17.5", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 20" Tall	
Gate	NaN	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM DUMP PBTD132
CAM BEAST DUAL TELE DUMP GN 15.4K**

	7 x 14	7 x 16
Model #	P-BTD8214-154G	P-BTD8216-154G
CAPACITIES		
GVWR (lbs)	15400	
GAWR (lbs/axle)	7000	
Curb Weight	4965	5225
Payload	10435	10175
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" x 3" x 3/16" Steel Tube	6" x 3" x 1/4" Steel Tube
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 7000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	ST235/80R16E 10-PR	
Wheels	16", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 20" Tall	
Gate	NaN	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM DUMP PBTD132
CAM BEAST DUAL TELE DUMP GN 17.6K**

	7 x 14	7 x 16
Model #	P-BTD8214-176G	P-BTD8216-176G
CAPACITIES		
GVWR (lbs)	17600	
GAWR (lbs/axle)	8000	
Curb Weight	5465	5725
Payload	12135	11875
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	6" x 3" x 3/16" Steel Tube	6" x 3" x 1/4" Steel Tube
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	215/75R17.5J 18-PR	
Wheels	17.5", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 20" Tall	
Gate	NaN	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM DUMP PBTD132
CAM BEAST HS DUAL TELE DUMP 15.4K**

	7 x 14	7 x 16
Model #	P-BTD48214-154	P-BTD48216-154
CAPACITIES		
GVWR (lbs)	15400	
GAWR (lbs/axle)	7000	
Curb Weight	4990	5250
Payload	10410	10150
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Frame	6" x 3" x 3/16" Steel Tube	6" x 3" x 1/4" Steel Tube
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Rear Door	Barn-Style Double with Cambar	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 7000 lb. Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	ST235/80R16E 10-PR	
Wheels	16", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 48" Tall	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM DUMP PBTD132
CAM BEAST HS DUAL TELE DUMP 17.6K**

	7 x 14	7 x 16
Model #	P-BTD48214-176	P-BTD48216-176
CAPACITIES		
GVWR (lbs)	17600	
GAWR (lbs/axle)	8000	
Curb Weight	5490	5750
Payload	12110	11850
CHASSIS		
Coupler	2-5/16" Adjustable	
Tongue	5" Steel Channel	
Frame	6" x 3" x 3/16" Steel Tube	6" x 3" x 1/4" Steel Tube
Crossmembers	3" Steel Channel	
Ramp(s)	3" x 6' Steel Ladder (Slide-In with Carrier)	
Rear Door	Barn-Style Double with Cambar	
Stabilizers	Rear Drop-Leg Jacks	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Fenders	Double Break Tread Plate	
Tires	215/75R17.5J 18-PR	
Wheels	17.5", 8-Hole Steel	
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail	
Exterior Lights	Full LED, DOT Compliant	
Sides	12-Gauge, 48" Tall	
Decking	7-Gauge Smooth Steel	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Underbody Secure Tool Storage	
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Dual Telescopic Cylinders)	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud	20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.