



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST FULL TILT 15.4K**

	7 x 18	7 x 20	7 x 22
Model #	P-BTEF8218-154	P-BTEF8220-154	P-BTEF8222-154
CAPACITIES			
GVWR (lbs)		15400	
GAWR (lbs/axle)		7000	
Curb Weight	3800	4000	4200
Payload	11600	11400	11200
CHASSIS			
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue	8" Flange, 13 lb/ft I-Beam		
Tongue Jack	12K, 2-Speed Drop Leg		
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle		
Crossmembers	3" x 2" Tube, 16" On-Center		
Ramp(s)	HD Diamond Plate Knife Edge Tail		
Integrated Step(s)	Side Steps		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Oil Bath		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets		
Exterior Lights	Full LED, DOT Compliant		
Decking	2" Pressure Treated Pine		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST FULL TILT 17.6K**

	7 x 18	7 x 20	7 x 22
Model #	P-BTEF8218-176	P-BTEF8220-176	P-BTEF8222-176
CAPACITIES			
GVWR (lbs)		17600	
GAWR (lbs/axle)		8000	
Curb Weight	4040	4240	4440
Payload	13560	13360	13160
CHASSIS			
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue	8" Flange, 13 lb/ft I-Beam		
Tongue Jack	12K, 2-Speed Drop Leg		
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle		
Crossmembers	3" x 2" Tube, 16" On-Center		
Ramp(s)	HD Diamond Plate Knife Edge Tail		
Integrated Step(s)	Side Steps		
Axle	(2) 8000 lb. Slipper Spring Brake		
Hubs	Oil Bath		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	215/75R17.5J 18-PLY		
Wheels	17.5", 8-Lug Steel		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets		
Exterior Lights	Full LED, DOT Compliant		
Decking	2" Pressure Treated Pine		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST FULL TILT 22K**

	7 x 18	7 x 20	7 x 22
Model #	P-BTEF8218-220	P-BTEF8220-220	P-BTEF8222-220
CAPACITIES			
GVWR (lbs)		22000	
GAWR (lbs/axle)		10000	
Curb Weight	4440	4640	4840
Payload	17560	17360	17160
CHASSIS			
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue	8" Flange, 13 lb/ft I-Beam		
Tongue Jack	12K, 2-Speed Drop Leg		
Frame	8", 15 lb/ft I-Beam		
Crossmembers	3" x 2" Tube, 16" On-Center		
Ramp(s)	HD Diamond Plate Knife Edge Tail		
Integrated Step(s)	Side Steps		
Axle	(2) 10000 lb. Torsion Brake		
Hubs	Oil Bath		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	215/75R17.5J 18-PLY	215/75R17.5J 18-PLY, ST235/75R17.15J 18-PLY	
Wheels	17.5", 8-Lug Steel		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets		
Exterior Lights	Full LED, DOT Compliant		
Decking	2" Pressure Treated Pine		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST SPLIT TILT 15.4K**

	7 x 20	7 x 22	7 x 22	7 x 24
Model #	P-BTES82164-154	P-BTES82184-154	P-BTES82166-154	P-BTES82204-154
CAPACITIES				
GVWR (lbs)		15400		
GAWR (lbs/axle)		7000		
Curb Weight	4000	4200		4400
Payload	11400	11200		11000
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" Flange, 13 lb/ft I-Beam			
Tongue Jack	12K, 2-Speed Drop Leg			
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle			
Crossmembers	3" x 2" Tube, 16" On-Center			
Integrated Step(s)	Side Steps			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(6) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	Diamond Plate Knife Edge			
Decking	2" Pressure Treated Pine			
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier			
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST SPLIT TILT 17.6K**

	7 x 20	7 x 22	7 x 22	7 x 24
Model #	P-BTES82164-176	P-BTES82184-176	P-BTES82166-176	P-BTES82204-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4240	4440	4450	4640
Payload	13360	13160	13150	12960
CHASSIS				
Coupler	Adjustable 4-Bolt Pintle Ring			
Tongue	8" Flange, 13 lb/ft I-Beam			
Tongue Jack	12K, 2-Speed Drop Leg			
Frame	8", 13 lb/ft I-Beam, Tilting Deck - 6" x 4" x 5/16" Reinforced Angle			
Crossmembers	3" x 2" Tube, 16" On-Center			
Ramp(s)	HD Diamond Plate Knife Edge Tail			
Integrated Step(s)	Side Steps			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(6) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets			
Exterior Lights	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier			
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST SPLIT TILT 22K**

	7 x 20	7 x 22	7 x 22	7 x 24	7 x 24	7 x 26
Model #	P-BTES82164-220	P-BTES82184-220	P-BTES82166-220	P-BTES82204-220	P-BTES82168-220	P-BTES82206-220
CAPACITIES						
GVWR (lbs)	22000					
GAWR (lbs/axle)	10000					
Curb Weight	4640	4840		5040	5280	5540
Payload	17360	17160		16960	16720	16460
CHASSIS						
Coupler	Adjustable 4-Bolt Pintle Ring					
Tongue	8" Flange, 13 lb/ft I-Beam					
Tongue Jack	12K, 2-Speed Drop Leg					
Frame	8", 15 lb/ft I-Beam					
Crossmembers	3" Steel Channel			3" x 2" Tube, 16" On-Center		
Ramp(s)	HD Diamond Plate Knife Edge Tail					
Integrated Step(s)	Side Steps					
Axle	(2) 10000 lb. Torsion Brake					
Hubs	Oil Bath					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/75R17.15J 18-PLY	215/75R17.5J 18-PLY		ST235/75R17.15J 18-PLY		
Wheels	17.5", 8-Lug Steel					
Tie Downs	(6) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets					
Exterior Lights	Full LED, DOT Compliant					
Decking	2" Pressure Treated Pine					
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier					
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.