

PB9600

STANDARD PLATFORM STAKE BODIES

For your
everyday
hauling
application



OPTIONS

- Floor: apitong hardwood, tread plate
- Full rear 10" drop light apron — Includes oval stop/tail, turn, reverse, and license plate lights with wiring harness
- Cab shield (standard sizes — 18", 36", & 48")
- Triple window in bulkhead

STAKE RACKS

- 42" high 4 slat racks
- Constructed with 11 ga. reinforced hat stakes and 16 ga. roll formed slats
- Spring-loaded latch system on stakes assures secure attachment to body
- Optional rear swing out racks with bolt-on rear post



Standard Specifications

- 42" or 48" high weld-on bulkhead with screened window. Also available in 54" or 60" high
- 3/4" LED marker and clearance light kit meets [FMVSS108]. Includes wiring harness.
- Primed and painted black
- Structural channel long sills
8'6" - 14'6" • 6" x 8.2 lb. channel
16'6" - 20'6" • 7" x 9.8 lb. channel
22'6" - 26'6" • 8" x 11.5 lb channel
- 3" Structural cross members 12" o.c.
- 4" Formed 3/16" channel rear rail with inset stake pockets
- 10 ga. smooth steel or shiplapped KDAT pine floor
- 10 ga. formed side rails
- 3/16" heavy-duty exterior stake pockets with 3/8" x 2" rub rail on sides
- Standard overall width 96" (optional 102" wide)

STANDARD OVERALL LENGTH AND APPROXIMATE WEIGHT IN POUNDS*											
Length	8'6"	9'6"	10'6"	12'6"	14'6"	16'6"	18'6"	20'6"	22'6"	24'6"	26'6"
Steel Floor Weight	1161	1266	1370	1575	1782	2039	2252	2464	2751	2972	3192
Wood Floor Weight	1116	1212	1307	1496	1687	1927	2124	2319	2590	2794	2998

PB9600SD

For your heaviest hauling applications

SUPER DUTY PLATFORM STAKE BODIES



OPTIONS

- Floor: Apitong hardwood, tread plate
- Full rear 10" drop light apron — Includes oval stop/tail, turn, reverse, and license plate lights with wiring harness
- Cab shield (standard sizes 18", 36", & 48")
- Triple window in bulkhead



Shown with optional rear swing racks and full 10" light apron

STAKE RACKS

- 42" high 4 slat racks
- Constructed with 11 ga. reinforced hat stakes and 16 ga. roll formed slats
- Spring-loaded latch system on stakes assures secure attachment to body
- Optional rear swing out racks with bolt-on rear post

Standard Specifications

- 48" high weld-on bulkhead with screened window. Also available in 54", and 60" high
- 3/4" LED Marker and clearance light kit meets (FMVSS108) Includes wiring harness
- Primed and painted black
- Structural channel long sills
12'6" – 18'6" • 7" x 9.8 lb. channel
20'6" – 26'6" • 8" x 11.5 lb. channel
- 4 " Structural channel cross members 12" o.c.
- 6" Structural channel rear and side rails
- 7 ga. smooth steel floor or shiplapped KDAT pine floor
- 3/16" heavy-duty exterior stake pockets with 3/8" x 3" rub rail on sides and rear
- Standard overall width 96" [optional 102" wide]

STANDARD OVERALL LENGTH AND APPROXIMATE WEIGHT IN POUNDS*								
Length	12'6"	14'6"	16'6"	18'6"	20'6"	22'6"	24'6"	26'6"
Weight with steel floor	2262	2556	2844	3134	3510	3797	4095	4395
Weight with wood floor	1971	2210	2447	2684	2994	3241	3484	3733