



SPECIFICATIONS -MIDSOTA DUMPS
MIDSOTA VERSA DUMP SCISSOR 15.4K

	82 x 12	82 x 14	82 x 16
Model #	N-HVS12-154	N-HVS14-154	N-HVS16-154
CAPACITIES			
GVWR (lbs)	15400		
GAWR (lbs/axle)	7000		
Curb Weight	4400	4600	4850
Payload	11000	10800	10550
CHASSIS			
Coupler	2-5/16" Adjustable EZ Latch 4-Bolt Flat Plate		
Tongue	6" x 3" Steel Tube		
Tongue Jack	12K Drop Leg, Set-Back		
Frame	6" x 4" Steel Tube		
Crossmembers	3" Steel Channel, 16" On-Center		
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Zinc Plated, Rear Drop Leg Jacks		
Axle	(2) 7000 lb. Drop Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(6) 5/8" D-Rings, Stake Pockets		
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring		
Exterior Lights	Full LED, DOT Compliant		
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders		
Top Rail	3" x 2" Steel Tube		
Sides	11-Gauge Formed Sides, 24" Tall		
Gate	NaN		
Mud Flaps	Yes		
Decking	7-Gauge, One-Piece Smooth Steel		
Exterior Storage	A-Frame Steel Lockable Toolbox, Pallet Fork Carrier, Spare Tire Carrier		
Hydraulic Components	Power Up, Gravity Down (Scissor Lift Hoist), Push Button Control with 15' Lead		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets		
Coupler Height	0	11.5-19.5	
Deck Height		25	
DIMENSIONS			
Overall Length		228.5	252.5
Deck Height		25	
Coupler Height	0	11.5-19.5	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA DUMPS

MIDSOTA VERSA DUMP SCISSOR 17.6K

	82 x 12	82 x 14	82 x 16	82 x 18	82 x 20
Model #	N-HVS12-176	N-HVS14-176	N-HVS16-176	N-HVS18-176	N-HVS20-176
CAPACITIES					
GVWR (lbs)	17600				
GAWR (lbs/axle)	8000				
Curb Weight	4350	4850	5100	5825	6075
Payload	13250	12750	12500	11775	11525
CHASSIS					
Coupler	2-5/16" Adjustable EZ Latch 4-Bolt Flat Plate				
Tongue	6" x 3" Steel Tube				
Tongue Jack	12K Drop Leg, Set-Back				
Frame	6" x 4" Steel Tube				
Crossmembers	3" Steel Channel, 16" On-Center			Rolled Grade 50 3" Steel Channel	
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)				
Integrated Step(s)	Side Steps				
Stabilizers	Zinc Plated, Rear Drop Leg Jacks				
Axle	(2) 8000 lb. Drop Slipper Spring Brake				
Hubs	Oil Bath				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	215/75R17.5J 18-PLY				
Wheels	17.5", 8-Lug Steel		16", 8-Lug Steel	17.5", 8-Lug Steel	
Tie Downs	(6) 5/8" D-Rings, Stake Pockets				
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring				
Exterior Lights	Full LED, DOT Compliant				
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders				
Top Rail	3" x 2" Steel Tube				
Sides	11-Gauge Formed Sides, 24" Tall				
Gate	NaN				
Mud Flaps	Yes				
Decking	7-Gauge, One-Piece Smooth Steel				
Exterior Storage	A-Frame Steel Lockable Toolbox, Pallet Fork Carrier, Spare Tire Carrier				
Hydraulic Components	Power Up, Gravity Down (Scissor Lift Hoist), Push Button Control with 15' Lead				
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets		20' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets		22' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets
Coupler Height	0	11.5-19.5			
Deck Height		25			
DIMENSIONS					
Overall Length		228.5	252.5	276.5	300.5
Deck Height		25			
Coupler Height	0	11.5-19.5			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	82 x 14	82 x 16
Model #	N-HVS14-161G	N-HVS16-161G
CAPACITIES		
GVWR (lbs)	16100	
GAWR (lbs/axle)	7000	
Curb Weight	5250	5500
Payload	10850	10600
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	Gooseneck, High Strength Manufactured I-Beam	
Tongue Jack	Dual 12K Drop Leg	
Crossmembers	Rolled Grade 50 3" Steel Channel	
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Zinc Plated, Rear Drop Leg Jacks	
Axle	(2) 7000 lb. Drop Slipper Spring Brake	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16", 8-Lug Steel	
Tie Downs	(6) 5/8" D-Rings, Stake Pockets	
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring	
Exterior Lights	Full LED, DOT Compliant	
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders	
Top Rail	3" x 2" Steel Tube	
Sides	11-Gauge Formed Sides, 24" Tall	
Gate	NaN	
Mud Flaps	Yes	
Decking	7-Gauge, One-Piece Smooth Steel	
Exterior Storage	Pallet Fork Carrier, Spare Tire Carrier	
Hydraulic Components	Power Up, Gravity Down (Scissor Lift Hoist), Push Button Control with 15' Lead	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets	
Coupler Height	0	
DIMENSIONS		
Coupler Height	0	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	82 x 14	82 x 16
Model #	N-HVS14-184G	N-HVS16-184G
CAPACITIES		
GVWR (lbs)	18400	
GAWR (lbs/axle)	8000	
Curb Weight	5500	5750
Payload	12900	12650
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	Gooseneck, High Strength Manufactured I-Beam	
Tongue Jack	Dual 12K Drop Leg	
Crossmembers	Rolled Grade 50 3" Steel Channel	
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Zinc Plated, Rear Drop Leg Jacks	
Axle	(2) 8000 lb. Drop Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(6) 5/8" D-Rings, Stake Pockets	
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring	
Exterior Lights	Full LED, DOT Compliant	
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders	
Top Rail	3" x 2" Steel Tube	
Sides	11-Gauge Formed Sides, 24" Tall	
Gate	NaN	
Mud Flaps	Yes	
Decking	7-Gauge, One-Piece Smooth Steel	
Exterior Storage	Pallet Fork Carrier, Spare Tire Carrier	
Hydraulic Components	Power Up, Gravity Down (Scissor Lift Hoist), Push Button Control with 15' Lead	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets	
Coupler Height	0	
DIMENSIONS		
Coupler Height	0	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA DUMPS
MIDSOTA VERSA DUMP TELE 15.4K

	82 x 12	82 x 14	82 x 16
Model #	N-HVT12-154	N-HVT14-154	N-HVT16-154
CAPACITIES			
GVWR (lbs)	15400		
GAWR (lbs/axle)	7000		
Curb Weight	4200	4375	4625
Payload	11200	11025	10775
CHASSIS			
Coupler	2-5/16" Adjustable EZ Latch 4-Bolt Flat Plate		
Tongue	6" x 3" Steel Tube		
Tongue Jack	12K Drop Leg, Set-Back		
Frame	6" x 4" Steel Tube		
Crossmembers	3" Steel Channel, 16" On-Center		
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Zinc Plated, Rear Drop Leg Jacks		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(6) 5/8" D-Rings, Stake Pockets		
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring		
Exterior Lights	Full LED, DOT Compliant		
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders		
Top Rail	3" x 2" Steel Tube		
Sides	11-Gauge Formed Sides, 24" Tall		
Gate	NaN		
Mud Flaps	Yes		
Decking	7-Gauge, One-Piece Smooth Steel		
Exterior Storage	A-Frame Steel Lockable Toolbox, Pallet Fork Carrier, Spare Tire Carrier		
Hydraulic Components	Power Up, Gravity Down (Telescopic Hoist), Push Button Control with 15' Lead		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets		
Coupler Height	11.5-19.5	0	11.5-19.5
Deck Height	25		25
DIMENSIONS			
Overall Length	204.5		252.5
Deck Height	25		25
Coupler Height	11.5-19.5	0	11.5-19.5

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

82 x 14		82 x 16	
Model #	N-HVT14-176		N-HVT16-176
CAPACITIES			
GVWR (lbs)	17600		
GAWR (lbs/axle)	8000		
Curb Weight	4650	4875	
Payload	12950	12725	
CHASSIS			
Coupler	2-5/16" Adjustable EZ Latch 4-Bolt Flat Plate		
Tongue	6" x 3" Steel Tube		
Tongue Jack	12K Drop Leg, Set-Back		
Frame	6" x 4" Steel Tube		
Crossmembers	3" Steel Channel, 16" On-Center		
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Zinc Plated, Rear Drop Leg Jacks		
Axle	(2) 8000 lb. Slipper Spring Brake		
Hubs	Oil Bath		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	215/75R17.5J 18-PLY		
Wheels	17.5", 8-Lug Steel	16", 8-Lug Steel	
Tie Downs	(6) 5/8" D-Rings, Stake Pockets		
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring		
Exterior Lights	Full LED, DOT Compliant		
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders		
Top Rail	3" x 2" Steel Tube		
Sides	11-Gauge Formed Sides, 24" Tall		
Gate	NaN		
Mud Flaps	Yes		
Decking	7-Gauge, One-Piece Smooth Steel		
Exterior Storage	A-Frame Steel Lockable Toolbox, Pallet Fork Carrier, Spare Tire Carrier		
Hydraulic Components	Power Up, Gravity Down (Telescopic Hoist), Push Button Control with 15' Lead		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets		
Coupler Height	11.5-19.5		
Deck Height	25		
DIMENSIONS			
Overall Length	228.5	252.5	
Deck Height	25		
Coupler Height	11.5-19.5		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA DUMPS
MIDSOTA VERSA DUMP TELE GN 16.1K

82 x 14		82 x 16	
Model #	N-HVT14-161G		N-HVT16-161G
CAPACITIES			
GVWR (lbs)	16100		
GAWR (lbs/axle)	7000		
Curb Weight	5025	5275	
Payload	11075	10825	
CHASSIS			
Coupler	2-5/16" Adjustable Gooseneck		
Tongue	Gooseneck, High Strength Manufactured I-Beam		
Tongue Jack	Dual 12K Drop Leg		
Frame	6" x 4" Steel Tube		
Crossmembers	Rolled Grade 50 3" Steel Channel		
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Zinc Plated, Rear Drop Leg Jacks		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(6) 5/8" D-Rings, Stake Pockets		
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring		
Exterior Lights	Full LED, DOT Compliant		
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders		
Top Rail	3" x 2" Steel Tube		
Sides	11-Gauge Formed Sides, 24" Tall		
Gate	NaN		
Mud Flaps	Yes		
Decking	7-Gauge, One-Piece Smooth Steel		
Exterior Storage	Pallet Fork Carrier, Spare Tire Carrier		
Hydraulic Components	Power Up, Gravity Down (Telescopic Hoist), Push Button Control with 15' Lead		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets		
Coupler Height	0		
DIMENSIONS			
Coupler Height	0		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	82 x 14	82 x 16
Model #	N-HVT14-184G	N-HVT16-184G
CAPACITIES		
GVWR (lbs)	18400	
GAWR (lbs/axle)	8000	
Curb Weight	5300	5525
Payload	13100	12875
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	Gooseneck, High Strength Manufactured I-Beam	
Tongue Jack	Dual 12K Drop Leg	
Frame	6" x 4" Steel Tube	
Crossmembers	Rolled Grade 50 3" Steel Channel	
Ramp(s)	4" x 72" Steel Ladder Style (Slide-In with Carrier)	
Integrated Step(s)	Side Steps	
Stabilizers	Zinc Plated, Rear Drop Leg Jacks	
Axle	(2) 8000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	215/75R17.5J 18-PLY	
Wheels	17.5", 8-Lug Steel	
Tie Downs	(6) 5/8" D-Rings, Stake Pockets	
Wiring	Midsota Exclusive Indicator Module, No Exposed Wiring	
Exterior Lights	Full LED, DOT Compliant	
Misc.	Greaseless Pivot Pins (Neverlube), Pallet Fork Holders	
Top Rail	3" x 2" Steel Tube	
Sides	11-Gauge Formed Sides, 24" Tall	
Gate	NaN	
Mud Flaps	Yes	
Decking	7-Gauge, One-Piece Smooth Steel	
Exterior Storage	Pallet Fork Carrier, Spare Tire Carrier	
Hydraulic Components	Power Up, Gravity Down (Telescopic Hoist), Push Button Control with 15' Lead	
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud, Tarp Brackets	
Coupler Height	0	
DIMENSIONS		
Coupler Height	0	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.