



SPECIFICATIONS -MIDSOTA DECKOVERS MDOFBGN

MIDSOTA FBGN SERIES

	102 x 26	102 x 28	102 x 28	102 x 30	102 x 30	102 x 32
Model #	NFB26-GN-259	NFB28-GN-230	NFB28-GN-259	NFB30-GN-259	NFB30-GN-230	NFB32-GN-259
CAPACITIES						
GVWR (lbs)	25900	23000	25900		23000	25900
GAWR (lbs/axle)	12000	10000	12000		10000	12000
Curb Weight	7200	7380	7780	8030	7630	8280
Payload	18700	15620	18120	17870	15370	17620
CHASSIS						
Frame	High Strength Manufactured I-Beam, Square Torque Tube					
Tongue	Gooseneck, High Strength Manufactured I-Beam					
Crossmembers	3" Steel Channel, 16" On-Center					
Integrated Step(s)	Side Steps					
Coupler	2-5/16" Adjustable Gooseneck					
Coupler Height	0					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Beavertail	5' Cleated					
Ramp(s)	Fold Over Wedge, Spring Assist					
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension	(2) 10000 lb. Slipper Spring Brake, Hutch Spring Suspension	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension		(2) 10000 lb. Slipper Spring Brake, Hutch Spring Suspension	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension
Hubs	Oil Bath					
Tires	ST235/80R16E 10-PR					
Wheels	16" Dual, 8-Hole Steel					
Mud Flaps	Yes					
Exterior Finish	Industrial Grade Polymer Finish					
Decking	2" Pressure Treated Pine, Board Retainers					
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail					
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier					
Wiring	No Exposed Wiring					
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant					
DIMENSIONS						
Coupler Height	0					
	102 x 34	102 x 34	102 x 36	102 x 36	102 x 40	102 x 40
Model #	NFB34-GN-368	NFB34-GN-259	NFB36-GN-259	NFB36-GN-368	NFB40-GN-368	NFB40-GN-259
CAPACITIES						
GVWR (lbs)	36800	25900		36800		25900
GAWR (lbs/axle)	16000	12000		16000		12000
Curb Weight	7975	8130	8780	8930	9580	9280
Payload	28825	17770	17120	27870	27220	16620
CHASSIS						
Frame	High Strength Manufactured I-Beam, Square Torque Tube					
Tongue	Gooseneck, High Strength Manufactured I-Beam					
Crossmembers	3" Steel Channel, 12" On-Center	3" Steel Channel, 16" On-Center		3" Steel Channel, 12" On-Center		3" Steel Channel, 16" On-Center
Integrated Step(s)	Side Steps					
Coupler	3" Square Gooseneck	2-5/16" Adjustable Gooseneck		3" Square Gooseneck		2-5/16" Adjustable Gooseneck
Coupler Height	0					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Beavertail	5' Cleated					
Ramp(s)	Fold Over Wedge, Spring Assist					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 34	102 x 34	102 x 36	102 x 36	102 x 40	102 x 40
Axle	(2) 16000 lb. Straight Brake, Hutch Spring Suspension	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension		(2) 16000 lb. Straight Brake, Hutch Spring Suspension		(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension
Hubs	Oil Bath					
Tires	215/75R17.5J 18-PR	ST235/80R16E 10-PR		215/75R17.5J 18-PR		ST235/80R16E 10-PR
Wheels	17.5" Dual, 8 on 275mm Steel	16" Dual, 8-Hole Steel		17.5" Dual, 8 on 275mm Steel		16" Dual, 8-Hole Steel
Mud Flaps	Yes					
Exterior Finish	Industrial Grade Polymer Finish					
Decking	2" Pressure Treated Pine, Board Retainers					
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail					
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier					
Wiring	No Exposed Wiring					
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant					
DIMENSIONS						
Coupler Height	0					
	102 x 44			102 x 32		102 x 36
Model #	NFB44-GN-259			NFB32-GN-230		NFB36-GN-230
CAPACITIES						
GVWR (lbs)	25900			23000		
GAWR (lbs/axle)	12000			10000		
Curb Weight	9400			7880		8380
Payload	16500			15120		14620
CHASSIS						
Frame	High Strength Manufactured I-Beam, Square Torque Tube					
Tongue	Gooseneck, High Strength Manufactured I-Beam					
Crossmembers	3" Steel Channel, 16" On-Center					
Integrated Step(s)	Side Steps					
Coupler	2-5/16" Adjustable Gooseneck					
Coupler Height	0			32.25 - 40.25		
Deck Height				34		
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Beavertail	5' Cleated					
Ramp(s)	Fold Over Wedge, Spring Assist					
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension			(2) 10000 lb. Slipper Spring Brake, Hutch Spring Suspension		
Hubs	Oil Bath					
Tires	ST235/80R16E 10-PR					
Wheels	16" Dual, 8-Hole Steel					
Mud Flaps	Yes					
Exterior Finish	Industrial Grade Polymer Finish					
Decking	2" Pressure Treated Pine, Board Retainers					
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail					
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier					
Wiring	No Exposed Wiring					
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant					
DIMENSIONS						
Overall Length				498		546
Deck Height				34		
Coupler Height	0			32.25 - 40.25		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.