



SPECIFICATIONS -ALUM UTILITY ALUM RAIL SIDE 3K

	60 x 8	66 x 10	76 x 12	82 x 12	82 x 14
Model #	H-RSA6008-030	H-RSA6610-030	H-RSA7612-030	H-RSA8212-030	H-RSA8214-030
CAPACITIES					
GVWR (lbs)	2990				
GAWR (lbs/axle)	3500				
Curb Weight	650	810	920	980	1050
Payload	2340	2180	2070	2010	1940
CHASSIS					
Coupler	2" A-Frame, Posi-Lock				
Tongue	4" x 2" Aluminum Triple Tube, Fully Wrapped				
Tongue Jack	1K Swivel Jack with Caster Wheel				
Frame	3" x 2" x 3/16" Aluminum Angle				
Crossmembers	3" x 2" x 3/16" Aluminum Angle				
Ramp(s)	54" Bi-Fold Aluminum				
Axle	3500 lb. Spring Idler				
Hubs	Easy Lube				
Tires	ST205/75R15C 6-PLY				
Wheels	15", 5-Lug Aluminum				
Tie Downs	Aluminum Stake Pockets				
Wiring	Sealed Wiring Harness				
Exterior Lights	Full LED, DOT Compliant				
Top Rail	2" x 2" Aluminum Tube				
Uprights	2" x 1 1/2" Aluminum Extrusion Tube				
Gate	57 x 54.5	63 x 54.5	73 x 54.5	79 x 54.5	
Decking	2" Pressure Treated Pine				
Deck Height	17.5				
Height Overall	49				
Deck Length	96	120	144		168
Width Interior	60.25	66.25	76.25	82.25	
Length Interior Box	96	120	144		168
Width Ramp	57	63	73	79	
Length Ramp	54.5				
DIMENSIONS					
Overall Length	140	164	188		212
Deck Length	96	120	144		168
Deck Width	60.25	66.25	76.25	82.25	
Deck Height	17.5				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -ALUM UTILITY ALUM RAIL SIDE TANDEM 7K

	82 x 14	82 x 16	82 x 18	82 x 20	82 x 22	82 x 24
Model #	H-RSA8214-070	H-RSA8216-070	H-RSA8218-070	H-RSA8220-070	H-RSA8222-070	H-RSA8224-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	1485		1640	1800		
Payload	5515		5360	5200		
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	5" x 2" Aluminum Triple Tube					
Tongue Jack	2K Set-Back					
Frame	3" x 2" x 3/16" Aluminum Angle			4" x 3" x 1/4" Aluminum Angle		
Crossmembers	3" Aluminum Channel					
Ramp(s)	54" Bi-Fold Aluminum					
Axle	(2) 3500 lb. Spring Brake					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Aluminum					
Tie Downs	Aluminum Stake Pockets					
Wiring	Sealed Wiring Harness					
Exterior Lights	Full LED, DOT Compliant					
Top Rail	2" x 2" Aluminum Tube					
Uprights	2" x 1 1/2" Aluminum Extrusion Tube					
Gate	79 x 54.5					
Decking	2" Pressure Treated Pine					
Deck Height	17.5					
Height Overall	49					
Deck Length	168	192	216	240	264	288
Width Interior	82.25					
Length Interior Box	168	192	216	240	264	288
Width Ramp	79					
Length Ramp	54.5					
DIMENSIONS						
Overall Length	218	242	266	290	314	338
Deck Length	168	192	216	240	264	288
Deck Width	82.25					
Deck Height	17.5					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.