



## SPECIFICATIONS -ALUM UTILITY ALUM RAIL SIDE 3K

	60 x 8	66 x 10	76 x 12	82 x 12	82 x 14
<b>Model #</b>	H-RSA6008-030	H-RSA6610-030	H-RSA7612-030	H-RSA8212-030	H-RSA8214-030
<b>CAPACITIES</b>					
<b>GVWR (lbs)</b>	2990				
<b>GAWR (lbs/axle)</b>	3500				
<b>Curb Weight</b>	650	810	920	980	1050
<b>Payload</b>	2340	2180	2070	2010	1940
<b>CHASSIS</b>					
<b>Coupler</b>	2" A-Frame, Posi-Lock				
<b>Tongue</b>	4" x 2" Aluminum Triple Tube, Fully Wrapped				
<b>Tongue Jack</b>	1K Swivel Jack with Caster Wheel				
<b>Frame</b>	3" x 2" x 3/16" Aluminum Angle				
<b>Crossmembers</b>	3" x 2" x 3/16" Aluminum Angle				
<b>Ramp(s)</b>	54" Bi-Fold Aluminum				
<b>Axle</b>	3500 lb. Spring Idler				
<b>Hubs</b>	Easy Lube				
<b>Tires</b>	ST205/75R15C 6-PLY				
<b>Wheels</b>	15", 5-Lug Aluminum				
<b>Tie Downs</b>	Aluminum Stake Pockets				
<b>Wiring</b>	Sealed Wiring Harness				
<b>Exterior Lights</b>	Full LED, DOT Compliant				
<b>Top Rail</b>	2" x 2" Aluminum Tube				
<b>Uprights</b>	2" x 1 1/2" Aluminum Extrusion Tube				
<b>Gate</b>	57 x 54.5	63 x 54.5	73 x 54.5	79 x 54.5	
<b>Decking</b>	2" Pressure Treated Pine				
<b>Deck Height</b>	17.5				
<b>Height Overall</b>	49				
<b>Deck Length</b>	96	120	144		168
<b>Width Interior</b>	60.25	66.25	76.25	82.25	
<b>Length Interior Box</b>	96	120	144		168
<b>Width Ramp</b>	57	63	73	79	
<b>Length Ramp</b>	54.5				
<b>DIMENSIONS</b>					
<b>Overall Length</b>	140	164	188		212
<b>Deck Length</b>	96	120	144		168
<b>Deck Width</b>	60.25	66.25	76.25	82.25	
<b>Deck Height</b>	17.5				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



# SPECIFICATIONS -ALUM UTILITY ALUM RAIL SIDE TANDEM 7K

	82 x 14	82 x 16	82 x 18	82 x 20	82 x 22	82 x 24
<b>Model #</b>	H-RSA8214-070	H-RSA8216-070	H-RSA8218-070	H-RSA8220-070	H-RSA8222-070	H-RSA8224-070
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	7000					
<b>GAWR (lbs/axle)</b>	3500					
<b>Curb Weight</b>	1485		1640	1800		1900
<b>Payload</b>	5515		5360	5200		5100
<b>CHASSIS</b>						
<b>Coupler</b>	2-5/16" A-Frame, Posi-Lock					
<b>Tongue</b>	5" x 2" Aluminum Triple Tube					
<b>Tongue Jack</b>	2K Set-Back					
<b>Frame</b>	3" x 2" x 3/16" Aluminum Angle			4" x 3" x 1/4" Aluminum Angle		
<b>Crossmembers</b>	3" Aluminum Channel					
<b>Ramp(s)</b>	54" Bi-Fold Aluminum					
<b>Axle</b>	(2) 3500 lb. Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Tires</b>	ST205/75R15C 6-PLY					
<b>Wheels</b>	15", 5-Lug Aluminum					
<b>Tie Downs</b>	Aluminum Stake Pockets					
<b>Wiring</b>	Sealed Wiring Harness					
<b>Exterior Lights</b>	Full LED, DOT Compliant					
<b>Top Rail</b>	2" x 2" Aluminum Tube					
<b>Uprights</b>	2" x 1 1/2" Aluminum Extrusion Tube					
<b>Gate</b>	79 x 54.5					
<b>Decking</b>	2" Pressure Treated Pine					
<b>Deck Height</b>	17.5					
<b>Height Overall</b>	49					
<b>Deck Length</b>	168	192	216	240	264	288
<b>Width Interior</b>	82.25					
<b>Length Interior Box</b>	168	192	216	240	264	288
<b>Width Ramp</b>	79					
<b>Length Ramp</b>	54.5					
<b>DIMENSIONS</b>						
<b>Overall Length</b>	218	242	266	290	314	338
<b>Deck Length</b>	168	192	216	240	264	288
<b>Deck Width</b>	82.25					
<b>Deck Height</b>	17.5					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.