

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	5 x 8
Model #	KF-SE6008-030	KF-SE6010-030	KF-SE7210-030	KF-SE7212-030	KF-SE7214-030	KF-SE6008-035
CAPACITIES						
GVWR (lbs)	2990					3500
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" x 2" Steel Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	24" Sloped V-Nose with 6" Drop					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	66"	78"				66"
Ramp(s)	150 Series with Assist, 16" Extension					
Side Door			32" Wide Flush Lock, Aluminum Holdback	36" Wide Flush Lock, Aluminum Holdback		
Axle	3500 lb. Drop Spring Idler					3500 lb. Drop Spring Brake
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop					
Roof	Brawn LightLID Translucent Roof					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel, Stainless Center Caps					
Vents	Sidewall Airflow					
Interior Lights	(1) LED					
Exterior Lights	Full LED, DOT Compliant					Full LED, DOT Compliant, Integrated Backup/Taillights
Switches	(1) Dome Light, 12V					
Height Rear Opening	62	74				62
Width Rear Opening	53.5	65.5				53.5
Coupler Height	17					
Deck Height	18					
Height Overall	87	99				87
Deck Length	115	139		163	187	115
Width Interior	57	69				57
Length Interior Box	93	117		141	165	93
DIMENSIONS						
Overall Length	146	170		194	218	146
Deck Length	115	139		163	187	115
Deck Width	57	69				57

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	5 x 8
Deck Height				18		
Coupler Height				17		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	5 x 10		6 x 10		6 x 12		6 x 14		7 x 12				
Model #	KF-SE6010-035		KF-SE7210-035			KF-SE7212-035		KF-SE7214-035		KF-SE8412-035			
CAPACITIES													
GVWR (lbs)						3500							
GAWR (lbs/axle)						3500							
CHASSIS													
Coupler						2" A-Frame							
Tongue						4" x 2" Steel Tube				6" x 2" Steel Tube			
Tongue Jack						2K Coupler Mounted							
Front Profile						24" Sloped V-Nose with 6" Drop							
Frame								4" x 2" Steel Tube					
Crossmembers						Formed Steel, 16" On-Center							
Roof Bows						Steel Tube, 16" On-Center							
Wall Posts						Steel Tube, 16" On-Center							
Standard Interior Height	66"		78"								84"		
Ramp(s)						150 Series with Assist, 16" Extension				16" Extension, 250 Series with Assist			
Side Door			32" Wide Flush Lock, Aluminum Holdback			36" Wide Flush Lock, Aluminum Holdback							
Axle						3500 lb. Drop Spring Brake							
Hubs						Easy Lube							
Undercoating						Asphalt Emulsion							
Protective Coating(s)						BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier							
Flooring						3/4" Engineered Wood							
Interior Walls						Engineered Wood							
Interior Trim						Aluminum H-Channel Wall Transitions							
Exterior Finish						Piedmont .080" Composite Panels							
Exterior Fastening						Screwless Sidewalls							
Stone Guard						24" ATP							
Exterior Trim						2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop							
Roof						Brawn LightLID Translucent Roof							
Tires						ST205/75R15C 6-PLY							
Wheels						15", 5-Lug Steel, Stainless Center Caps							
Vents						Sidewall Airflow							
Interior Lights						(1) LED							
Exterior Lights						Full LED, DOT Compliant, Integrated Backup/Taillights							
Switches						(1) Dome Light, 12V							
Height Rear Opening	62		74						80				
Width Rear Opening	53.5		65.5						77.5				
Coupler Height	17								18				
Deck Height	18								19				
Height Overall	87		99						105				
Deck Length	139					163		187		163			
Width Interior	57		69						81				
Length Interior Box	117					141		165		141			
DIMENSIONS													
Overall Length	170					194		218		200			
Deck Length	139					163		187		163			
Deck Width	57		69								81		
Deck Height	18											19	
Coupler Height	17											18	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 10	6 x 12	6 x 14	7 x 12	
Model #	KF-SE07210-030		KF-SE07212-030	KF-SE07214-030	KF-SE08412-035
CAPACITIES					
GVWR (lbs)	2990			3500	
GAWR (lbs/axle)	3500				
CHASSIS					
Coupler	2" A-Frame				
Tongue	4" x 2" Steel Tube			6" x 2" Steel Tube	
Tongue Jack	2K Coupler Mounted				
Front Profile	Round				
Frame				4" x 2" Steel Tube	
Crossmembers	Formed Steel, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Wall Posts	Steel Tube, 16" On-Center				
Standard Interior Height	78"			84"	
Ramp(s)	150 Series with Assist, 16" Extension			16" Extension, 250 Series with Assist	
Side Door	32" Wide Flush Lock, Aluminum Holdback		36" Wide Flush Lock, Aluminum Holdback		
Axle	3500 lb. Drop Spring Idler			3500 lb. Drop Spring Brake	
Hubs	Easy Lube				
Undercoating	Asphalt Emulsion				
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier				
Flooring	3/4" Engineered Wood				
Interior Walls	Engineered Wood				
Interior Trim	Aluminum H-Channel Wall Transitions				
Exterior Finish	Piedmont .080" Composite Panels				
Exterior Fastening	Screwless Sidewalls				
Stone Guard	24" ATP				
Exterior Trim	.080 Aluminum Roof Cove, 2.7" SCREWLESS Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Rear Hoop				
Roof Cap	TPO				
Roof	Brawn LightLID Translucent Roof				
Tires	ST205/75R15C 6-PLY				
Wheels	15", 5-Lug Steel, Stainless Center Caps				
Vents	Sidewall Airflow				
Interior Lights	(1) LED				
Exterior Lights	Full LED, DOT Compliant			Full LED, DOT Compliant, Integrated Backup/Taillights	
Switches	(1) Dome Light, 12V				
Height Rear Opening				72.25	
Width Rear Opening	65.5			77.5	
Width Interior	69			81	
DIMENSIONS					
Deck Width	69			81	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 10	6 x 12	6 x 14	7 x 12	7 x 14
Model #	KF-SE7210-050	KF-SE7212-050	KF-SE7214-050	KF-SE8412-050	KF-SE8414-050
CAPACITIES					
GVWR (lbs)	5000				
GAWR (lbs/axle)	5000				
CHASSIS					
Coupler	2" A-Frame				
Tongue	4" x 2" Steel Tube			6" x 2" Steel Tube	
Tongue Jack	2K Coupler Mounted				
Front Profile	24" Sloped V-Nose with 6" Drop				
Frame	4" x 2" Steel Tube				
Crossmembers	Formed Steel, 16" On-Center				
Roof Bows	Steel Tube, 16" On-Center				
Wall Posts	Steel Tube, 16" On-Center				
Standard Interior Height	78"			84"	
Ramp(s)	150 Series with Assist, 16" Extension			16" Extension, 250 Series with Assist	
Side Door	32" Wide Flush Lock, Aluminum Holdback		36" Wide Flush Lock, Aluminum Holdback		
Axle	5200 lb. Drop Spring Brake				
Hubs	Easy Lube				
Undercoating	Asphalt Emulsion				
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier				
Flooring	3/4" Engineered Wood				
Interior Walls	Engineered Wood				
Interior Trim	Aluminum H-Channel Wall Transitions				
Exterior Finish	Piedmont .080" Composite Panels				
Exterior Fastening	Screwless Sidewalls				
Stone Guard	24" ATP				
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop				
Roof	Brawn LightLID Translucent Roof				
Tires	ST225/75R15D 8-PLY				
Wheels	15", 6-Lug Steel, Stainless Center Caps				
Vents	Sidewall Airflow				
Interior Lights	(1) LED				
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights				
Switches	(1) Dome Light, 12V				
Height Rear Opening	74			80	
Width Rear Opening	65.5			77.5	
Coupler Height	18			19	
Deck Height	19			20	
Height Overall	100			106	
Deck Length	139	163	187	163	187
Width Interior	69			81	
Length Interior Box	117	141	165	141	165
DIMENSIONS					
Overall Length	170	194	218	200	224
Deck Length	139	163	187	163	187
Deck Width	69			81	
Deck Height	19			20	
Coupler Height	18			19	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 10	6 x 12	6 x 14	7 x 14	7 x 16	7 x 18
Model #	KF-SE7210-070	KF-SE7212-070	KF-SE7214-070	KF-SE8414-070	KF-SE8416-070	KF-SE8418-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	4" x 2" Steel Tube			6" x 2" Steel Tube		
Tongue Jack	2K Coupler Mounted					
Front Profile	24" Sloped V-Nose with 6" Drop					
Frame	4" x 2" Steel Tube					6" x 2" Steel Tube
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	78"			84"		
Ramp(s)	150 Series with Assist, 16" Extension			16" Extension, 250 Series with Assist		
Side Door	32" Wide Flush Lock, Aluminum Holdback	36" Wide Flush Lock, Aluminum Holdback				
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop					
Roof	Brawn LightLID Translucent Roof					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel, Stainless Center Caps					
Vents	Sidewall Airflow					
Interior Lights	(1) LED					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
Switches	(1) Dome Light, 12V					
Height Rear Opening	74				80	
Width Rear Opening	65.5				77.5	
Coupler Height	18					20
Deck Height	19					21
Height Overall	100				105	107
Deck Length	139	163	187		211	235
Width Interior	69				81	
Length Interior Box	117	141	165		189	213
DIMENSIONS						
Overall Length	170	194	218	224	248	272
Deck Length	139	163	187		211	235
Deck Width	69			81		
Deck Height	19					21
Coupler Height	18					20

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7.5 x 14		7.5 x 16		7.5 x 18		7.5 x 20		8.5 x 16		8.5 x 18	
Model #	KF-SE9014-070		KF-SE9016-070		KF-SE9018-070		KF-SE9020-070		KF-SE10216-070		KF-SE10218-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
CHASSIS												
Coupler	2-5/16" A-Frame											
Tongue	6" x 2" Steel Tube								6" x 2" Steel Tube with Center Drawbar			
Tongue Jack	2K Coupler Mounted											
Front Profile	24" Sloped V-Nose with 6" Drop								30" Sloped V-Nose with 6" Drop			
Frame	6" x 2" Steel Tube											
Crossmembers	Formed Steel, 16" On-Center											
Roof Bows	Steel Tube, 16" On-Center											
Wall Posts	Steel Tube, 16" On-Center											
Standard Interior Height	84"											
Ramp(s)	16" Extension, 250 Series with Assist								16" Extension, 400 Series with Assist			
Side Door	36" Wide Flush Lock, Aluminum Holdback											
Integrated Step(s)									Interior Recessed			
Axle	(2) 3500 lb. Drop Spring Brake											
Hubs	Easy Lube											
Undercoating	Asphalt Emulsion											
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier								BATTLECOAT Polyurea Coating			
Flooring	3/4" Engineered Wood											
Interior Walls	Engineered Wood											
Interior Trim	Aluminum H-Channel Wall Transitions											
Exterior Finish	Piedmont .080" Composite Panels											
Exterior Fastening	Screwless Sidewalls											
Stone Guard	24" ATP											
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop											
Roof	Brawn LightLID Translucent Roof											
Tires	ST205/75R15C 6-PLY											
Wheels	15", 5-Lug Steel, Stainless Center Caps											
Vents	Sidewall Airflow											
Interior Lights	(1) LED								(2) LED			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights											
Switches	(1) Dome Light, 12V											
Height Rear Opening	80											
Width Rear Opening									93.5			
Coupler Height	20											
Deck Height	21											
Height Overall	107											
Deck Length	187	211	235	259	217	241						
Width Interior	87								97			
Width Between Fender								81.5				
Length Interior Box	165	189	213	237	189	213						
DIMENSIONS												
Overall Length	224	248	272	296	248	272						
Deck Length	187	211	235	259	217	241						
Deck Width	87								97			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16	8.5 x 18
Deck Height				21		
Coupler Height				20		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	KF-SE10220-070	KF-SE10222-070	KF-SE10224-070	KF-SE10226-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
CHASSIS				
Coupler	2-5/16" A-Frame			
Tongue	6" x 2" Steel Tube with Center Drawbar			
Tongue Jack	2K Coupler Mounted			
Front Profile	30" Sloped V-Nose with 6" Drop			
Frame	6" x 2" Steel Tube			
Crossmembers	Formed Steel, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Wall Posts	Steel Tube, 16" On-Center			
Standard Interior Height	84"			
Ramp(s)	16" Extension, 400 Series with Assist			
Side Door	36" Wide Flush Lock, Aluminum Holdback			
Integrated Step(s)	Interior Recessed			
Axle	(2) 3500 lb. Drop Spring Brake			
Hubs	Easy Lube			
Undercoating	Asphalt Emulsion			
Protective Coating(s)	BATTLECOAT Polyurea Coating			
Flooring	3/4" Engineered Wood			
Interior Walls	Engineered Wood			
Interior Trim	Aluminum H-Channel Wall Transitions			
Exterior Finish	Piedmont .080" Composite Panels			
Exterior Fastening	Screwless Sidewalls			
Stone Guard	24" ATP			
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop			
Roof	Brawn LightLID Translucent Roof			
Tires	ST205/75R15C 6-PLY			
Wheels	15", 5-Lug Steel, Stainless Center Caps			
Vents	Sidewall Airflow			
Interior Lights	(2) LED			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			
Switches	(1) Dome Light, 12V			
Height Rear Opening	80			
Width Rear Opening	93.5			
Coupler Height	20			
Deck Height	21			
Height Overall	107			
Deck Length	265	289	313	337
Width Interior	97			
Width Between Fender	81.5			
Length Interior Box	237	261	285	309
DIMENSIONS				
Overall Length	296	320	344	368
Deck Length	265	289	313	337
Deck Width	97			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Deck Height			21	
Coupler Height			20	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	8.5 x 16
Model #	KF-SE07212-070	KF-SE08412-070	KF-SE08414-070	KF-SE08416-070	KF-SE08418-070	KF-SE010216-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	4" x 2" Steel Tube	6" x 2" Steel Tube				6" x 2" Steel Tube with Center Drawbar
Tongue Jack	2K Coupler Mounted					
Front Profile	Round					
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	78"	84"				
Ramp(s)	150 Series with Assist, 16" Extension	16" Extension, 250 Series with Assist				16" Extension, 400 Series with Assist
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Integrated Step(s)						Interior Recessed
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					BATTLECOAT Polyurea Coating
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	.080 Aluminum Roof Cove, 2.7" SCREWLESS Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Rear Hoop					
Roof Cap	TPO					
Roof	Brawn LightLID Translucent Roof					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel, Stainless Center Caps					
Vents	Sidewall Airflow					
Interior Lights	(1) LED					(2) LED
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
Switches	(1) Dome Light, 12V					
Height Rear Opening		78.25				
Width Rear Opening	65.5	77.5				93.5
Width Interior	69	81				97
Width Between Fender						81.5
DIMENSIONS						
Deck Width	69	81				97

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Model #	KF-SEO10218-070	KF-SEO10220-070	KF-SEO10222-070	KF-SEO10224-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
CHASSIS				
Coupler	2-5/16" A-Frame			
Tongue	6" x 2" Steel Tube with Center Drawbar			
Tongue Jack	2K Coupler Mounted			
Front Profile	Round			
Frame	6" x 2" Steel Tube			
Crossmembers	Formed Steel, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Wall Posts	Steel Tube, 16" On-Center			
Standard Interior Height	84"			
Ramp(s)	16" Extension, 400 Series with Assist			
Side Door	36" Wide Flush Lock, Aluminum Holdback			
Integrated Step(s)	Interior Recessed			
Axle	(2) 3500 lb. Drop Spring Brake			
Hubs	Easy Lube			
Undercoating	Asphalt Emulsion			
Protective Coating(s)	BATTLECOAT Polyurea Coating			
Flooring	3/4" Engineered Wood			
Interior Walls	Engineered Wood			
Interior Trim	Aluminum H-Channel Wall Transitions			
Exterior Finish	Piedmont .080" Composite Panels			
Exterior Fastening	Screwless Sidewalls			
Stone Guard	24" ATP			
Exterior Trim	.080 Aluminum Roof Cove, 2.7" SCREWLESS Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Rear Hoop			
Roof Cap	TPO			
Roof	Brawn LightLID Translucent Roof			
Tires	ST205/75R15C 6-PLY			
Wheels	15", 5-Lug Steel, Stainless Center Caps			
Vents	Sidewall Airflow			
Interior Lights	(2) LED			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			
Switches	(1) Dome Light, 12V			
Height Rear Opening	78.25			
Width Rear Opening	93.5			
Width Interior	97			
Width Between Fender	81.5			
DIMENSIONS				
Deck Width	97			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 14		7 x 16		7 x 18		7.5 x 14		7.5 x 16		7.5 x 18	
Model #	KF-SE8414-100		KF-SE8416-100		KF-SE8418-100		KF-SE9014-100		KF-SE9016-100		KF-SE9018-100	
CAPACITIES												
GVWR (lbs)	9900											
GAWR (lbs/axle)	5000											
CHASSIS												
Coupler	2-5/16" A-Frame											
Tongue	6" x 2" Steel Tube											
Tongue Jack	2K Coupler Mounted											
Front Profile	24" Sloped V-Nose with 6" Drop											
Frame	6" x 2" Steel Tube											
Crossmembers	Formed Steel, 16" On-Center											
Roof Bows	Steel Tube, 16" On-Center											
Wall Posts	Steel Tube, 16" On-Center											
Standard Interior Height	84"											
Ramp(s)	16" Extension, 250 Series with Assist											
Side Door	36" Wide Flush Lock, Aluminum Holdback											
Axle	(2) 5200 lb. Drop Spring Brake											
Hubs	Easy Lube											
Undercoating	Asphalt Emulsion											
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier											
Flooring	3/4" Engineered Wood											
Interior Walls	Engineered Wood											
Interior Trim	Aluminum H-Channel Wall Transitions											
Exterior Finish	Piedmont .080" Composite Panels											
Exterior Fastening	Screwless Sidewalls											
Stone Guard	24" ATP											
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop											
Roof	Brawn LightLID Translucent Roof											
Tires	ST225/75R15D 8-PLY											
Wheels	15", 6-Lug Steel, Stainless Center Caps											
Vents	Sidewall Airflow											
Interior Lights	(1) LED											
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights											
Switches	(1) Dome Light, 12V											
Height Rear Opening	80											
Width Rear Opening	77.5											
Coupler Height	21											
Deck Height	22											
Height Overall	108											
Deck Length	187	211	235	187	211	235						
Width Interior	81						87					
Length Interior Box	165	189	213	165	189	213						
DIMENSIONS												
Overall Length	224	248	272	224	248	272						
Deck Length	187	211	235	187	211	235						
Deck Width	81						87					
Deck Height	22											
Coupler Height	21											

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7.5 x 20	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Model #	KF-SE9020-100	KF-SE10216-100	KF-SE10218-100	KF-SE10220-100	KF-SE10222-100	KF-SE10224-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	6" x 2" Steel Tube	6" x 2" Steel Tube with Center Drawbar				
Tongue Jack	2K Coupler Mounted					
Front Profile	24" Sloped V-Nose with 6" Drop	30" Sloped V-Nose with 6" Drop				
Frame	6" x 2" Steel Tube					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	84"					
Ramp(s)	16" Extension, 250 Series with Assist	16" Extension, 400 Series with Assist				
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Integrated Step(s)		Interior Recessed				
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier	BATTLECOAT Polyurea Coating				
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop					
Roof	Brawn LightLID Translucent Roof					
Tires	ST225/75R15D 8-PLY					
Wheels	15", 6-Lug Steel, Stainless Center Caps					
Vents	Sidewall Airflow					
Interior Lights	(1) LED	(2) LED				
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
Switches	(1) Dome Light, 12V					
Height Rear Opening	80					
Width Rear Opening		93.5				
Coupler Height	21					
Deck Height	22					
Height Overall	108					
Deck Length	259	217	241	265	289	313
Width Interior	87	97				
Width Between Fender		81.5				
Length Interior Box	237	189	213	237	261	285
DIMENSIONS						
Overall Length	296	248	272	296	320	344
Deck Length	259	217	241	265	289	313
Deck Width	87	97				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7.5 x 20	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Deck Height		22				
Coupler Height		21				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 26	
Model #	KF-SE10226-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Coupler	2-5/16" A-Frame
Tongue	6" x 2" Steel Tube with Center Drawbar
Tongue Jack	2K Coupler Mounted
Front Profile	30" Sloped V-Nose with 6" Drop
Frame	6" x 2" Steel Tube
Crossmembers	Formed Steel, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Wall Posts	Steel Tube, 16" On-Center
Standard Interior Height	84"
Ramp(s)	16" Extension, 400 Series with Assist
Side Door	36" Wide Flush Lock, Aluminum Holdback
Integrated Step(s)	Interior Recessed
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Undercoating	Asphalt Emulsion
Protective Coating(s)	BATTLECOAT Polyurea Coating
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Aluminum H-Channel Wall Transitions
Exterior Finish	Piedmont .080" Composite Panels
Exterior Fastening	Screwless Sidewalls
Stone Guard	24" ATP
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop
Roof	Brawn LightLID Translucent Roof
Tires	ST225/75R15D 8-PLY
Wheels	15", 6-Lug Steel, Stainless Center Caps
Vents	Sidewall Airflow
Interior Lights	(2) LED
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights
Switches	(1) Dome Light, 12V
Height Rear Opening	80
Width Rear Opening	93.5
Coupler Height	21
Deck Height	22
Height Overall	108
Deck Length	337
Width Interior	97
Width Between Fender	81.5
Length Interior Box	309
DIMENSIONS	
Overall Length	368
Deck Length	337
Deck Width	97

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 26	
Deck Height	22
Coupler Height	21

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 14	7 x 16	7 x 18	8.5 x 16	8.5 x 18	8.5 x 20
Model #	KF-SE08414-100	KF-SE08416-100	KF-SE08418-100	KF-SE010216-100	KF-SE010218-100	KF-SE010220-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	6" x 2" Steel Tube			6" x 2" Steel Tube with Center Drawbar		
Tongue Jack	2K Coupler Mounted					
Front Profile	Round					
Frame	6" x 2" Steel Tube					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	84"					
Ramp(s)	16" Extension, 250 Series with Assist			16" Extension, 400 Series with Assist		
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Integrated Step(s)				Interior Recessed		
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier			BATTLECOAT Polyurea Coating		
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	.080 Aluminum Roof Cove, 2.7" SCREWLESS Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Rear Hoop					
Roof Cap	TPO					
Roof	Brawn LightLID Translucent Roof					
Tires	ST225/75R15D 8-PLY					
Wheels	15", 6-Lug Steel, Stainless Center Caps					
Vents	Sidewall Airflow					
Interior Lights	(1) LED			(2) LED		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					
Switches	(1) Dome Light, 12V					
Height Rear Opening	78.25					
Width Rear Opening	77.5			93.5		
Width Interior	81			97		
Width Between Fender				81.5		
DIMENSIONS						
Deck Width	81			97		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 22	8.5 x 24
Model #	KF-SE010222-100	KF-SE010224-100
CAPACITIES		
GVWR (lbs)	9900	
GAWR (lbs/axle)	5000	
CHASSIS		
Coupler	2-5/16" A-Frame	
Tongue	6" x 2" Steel Tube with Center Drawbar	
Tongue Jack	2K Coupler Mounted	
Front Profile	Round	
Frame	6" x 2" Steel Tube	
Crossmembers	Formed Steel, 16" On-Center	
Roof Bows	Steel Tube, 16" On-Center	
Wall Posts	Steel Tube, 16" On-Center	
Standard Interior Height	84"	
Ramp(s)	16" Extension, 400 Series with Assist	
Side Door	36" Wide Flush Lock, Aluminum Holdback	
Integrated Step(s)	Interior Recessed	
Axle	(2) 5200 lb. Drop Spring Brake	
Hubs	Easy Lube	
Undercoating	Asphalt Emulsion	
Protective Coating(s)	BATTLECOAT Polyurea Coating	
Flooring	3/4" Engineered Wood	
Interior Walls	Engineered Wood	
Interior Trim	Aluminum H-Channel Wall Transitions	
Exterior Finish	Piedmont .080" Composite Panels	
Exterior Fastening	Screwless Sidewalls	
Stone Guard	24" ATP	
Exterior Trim	.080 Aluminum Roof Cove, 2.7" SCREWLESS Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Rear Hoop	
Roof Cap	TPO	
Roof	Brawn LightLID Translucent Roof	
Tires	ST225/75R15D 8-PLY	
Wheels	15", 6-Lug Steel, Stainless Center Caps	
Vents	Sidewall Airflow	
Interior Lights	(2) LED	
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights	
Switches	(1) Dome Light, 12V	
Height Rear Opening	78.25	
Width Rear Opening	93.5	
Width Interior	97	
Width Between Fender	81.5	
DIMENSIONS		
Deck Width	97	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 14		7 x 16		7 x 18		8.5 x 16		8.5 x 18		8.5 x 20	
Model #	KF-SE8414-140		KF-SE8416-140		KF-SE8418-140		KF-SE10216-140		KF-SE10218-140		KF-SE10220-140	
CAPACITIES												
GVWR (lbs)						14000						
GAWR (lbs/axle)						7000						
CHASSIS												
Coupler	2-5/16" A-Frame											
Tongue	8" x 2" Steel Tube with Center Drawbar											
Tongue Jack	5K Coupler Mounted											
Front Profile	24" Sloped V-Nose with 6" Drop						30" Sloped V-Nose with 6" Drop					
Frame	8" x 2" Steel Tube											
Crossmembers	Formed Steel, 16" On-Center											
Roof Bows	Steel Tube, 16" On-Center											
Wall Posts	Steel Tube, 16" On-Center											
Standard Interior Height	84"											
Ramp(s)	16" Extension, 250 Series with Assist						16" Extension, 400 Series with Assist					
Side Door	36" Wide Flush Lock, Aluminum Holdback											
Integrated Step(s)							Interior Recessed					
Axle	(2) 7000 lb. Drop Spring Brake											
Hubs	Easy Lube											
Undercoating	Asphalt Emulsion											
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier						BATTLECOAT Polyurea Coating					
Flooring	3/4" Engineered Wood											
Interior Walls	Engineered Wood											
Interior Trim	Aluminum H-Channel Wall Transitions											
Exterior Finish	Piedmont .080" Composite Panels											
Exterior Fastening	Screwless Sidewalls											
Stone Guard	24" ATP											
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop											
Roof	Brawn LightLID Translucent Roof											
Tires	ST235/80R16E 10-PLY											
Wheels	16", 8-Lug Steel, Stainless Center Caps											
Vents	Sidewall Airflow											
Interior Lights	(1) LED						(2) LED					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights											
Switches	(1) Dome Light, 12V											
Height Rear Opening	80											
Width Rear Opening	77.5						93.5					
Coupler Height	24		22		24							
Deck Height	25		23		25							
Height Overall	111		109		111							
Deck Length	187		211		235		217		241		265	
Width Interior	81						97					
Width Between Fender					81.5							
Length Interior Box	165		189		213		189		213		237	
DIMENSIONS												
Overall Length	224		248		272		248		272		296	
Deck Length	187		211		235		217		241		265	
Deck Width	81						97					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 14	7 x 16	7 x 18	8.5 x 16	8.5 x 18	8.5 x 20
Deck Height	25	23			25	
Coupler Height	24	22			24	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 22		8.5 x 24		8.5 x 26		8.5 x 28		
Model #	KF-SE10222-140		KF-SE10224-140		KF-SE10226-140		KF-SE10228-140	
CAPACITIES								
GVWR (lbs)	14000							
GAWR (lbs/axle)	7000							
CHASSIS								
Coupler	2-5/16" A-Frame							
Tongue	8" x 2" Steel Tube with Center Drawbar							
Tongue Jack	5K Coupler Mounted							
Front Profile	30" Sloped V-Nose with 6" Drop							
Frame	8" x 2" Steel Tube							
Crossmembers	Formed Steel, 16" On-Center							
Roof Bows	Steel Tube, 16" On-Center							
Wall Posts	Steel Tube, 16" On-Center							
Standard Interior Height	84"							
Ramp(s)	16" Extension, 400 Series with Assist							
Side Door	36" Wide Flush Lock, Aluminum Holdback					48" Wide Flush Lock, Aluminum Holdback		
Integrated Step(s)	Interior Recessed							
Axle	(2) 7000 lb. Drop Spring Brake							
Hubs	Easy Lube							
Undercoating	Asphalt Emulsion							
Protective Coating(s)	BATTLECOAT Polyurea Coating							
Flooring	3/4" Engineered Wood							
Interior Walls	Engineered Wood							
Interior Trim	Aluminum H-Channel Wall Transitions							
Exterior Finish	Piedmont .080" Composite Panels							
Exterior Fastening	Screwless Sidewalls							
Stone Guard	24" ATP							
Exterior Trim	2.7" SCREWLESS Bottom Extrusion, 2.7" SCREWLESS Top Extrusion, ATP Nose Cap, Brite Aluminum Corners, Brite Aluminum Rear Hoop							
Roof	Brawn LightLID Translucent Roof							
Tires	ST235/80R16E 10-PLY							
Wheels	16", 8-Lug Steel, Stainless Center Caps							
Vents	Sidewall Airflow							
Interior Lights	(2) LED							
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights							
Switches	(1) Dome Light, 12V							
Height Rear Opening	80							
Width Rear Opening	93.5							
Coupler Height	24							
Deck Height	25							
Height Overall	111							
Deck Length	289	313	337	361				
Width Interior	97							
Width Between Fender	81.5							
Length Interior Box	261	285	309	333				
DIMENSIONS								
Overall Length	320	344	368	392				
Deck Length	289	313	337	361				
Deck Width	97							

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28
Deck Height			25	
Coupler Height			24	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.