



SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO FLAT TOP 10K

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20
Model #	H7212TFTV-100	H8412TFTV-100	H8414TFTV-100	H8416TFTV-100	H8418TFTV-100	H8420TFTV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight		2200	2550	2290	2630	2870
Payload		7700	7350	7610	7270	7030
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube				6" x 2" Steel Tube	
Front Profile	V-Nose					
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.030" Aluminum					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST225/75R15D 8-PLY					
Wheels	15", 6-Lug Steel					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	69					
Width Rear Opening	66	78				
Deck Height	20				21	
Height Overall	94	98				100
Deck Length	171	195		219	243	267
Width Interior	69	82				
Length Interior Box	171	195		219	243	267
DIMENSIONS						
Overall Length	210	214	238	262	286	322
Deck Length	171	195		219	243	267
Deck Width	69	82				
Deck Height	20				21	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8 x 14	8 x 16	8 x 18	8 x 20	8.5 x 14	8.5 x 16
Model #	H9614TFTV-100	H9616TFTV-100	H9618TFTV-100	H9620TFTV-100	H10114TFTV-100	H10116TFTV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight		2725	2900	3200		3000
Payload		7175	7000	6700		6900
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted					
Front Profile	V-Nose					
Frame	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.030" Aluminum					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST225/75R15D 8-PLY					
Wheels	15", 6-Lug Steel					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 18	8.5 x 20
Model #	H10118TFTV-100	H10120TFTV-100
CAPACITIES		
GVWR (lbs)	9900	
GAWR (lbs/axle)	5200	
Curb Weight	3370	
Payload	6530	
CHASSIS		
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue	6" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted	
Front Profile	V-Nose	
Frame	6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center	
Roof Bows	Galvanized Steel Tube, 24" On-Center	
Wall Posts	Steel Tube, 24" On-Center	
Ramp(s)	400 Series with Assist	
Side Door	36" Wide Flush Lock, Aluminum Holdback	
Axle	(2) 5200 lb. Drop Spring Brake	
Hubs	Easy Lube	
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel	
Flooring	3/4" Engineered Wood	
Interior Walls	Engineered Wood	
Interior Trim	Aluminum H-Channel Wall Transitions	
Exterior Finish	.030" Aluminum	
Stone Guard	24" ATP	
Roof	Flat Top .024 Aluminum Sheeted	
Tires	ST225/75R15D 8-PLY	
Wheels	15", 6-Lug Steel	
Wiring	Enclosed in Conduit	
Interior Lights	(2) LED Dome Lights, Wall Mount	
Exterior Lights	Full LED, DOT Compliant	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED HH SERIES CARGO FLAT TOP 14K

	7 x 14	7 x 16	7 x 18	7 x 20	8 x 16	8 x 18
Model #	H8414TFTV-140	H8416TFTV-140	H8418TFTV-140	H8420TFTV-140	H9616TFTV-140	H9618TFTV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	2690	2930				3250
Payload	11310	11070				10750
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	7K Drop Leg, Set-Back					
Front Profile	V-Nose					
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)					400 Series with Assist	
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.030" Aluminum					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST235/80R16E 10-PLY					
Wheels	16", 8-Lug Steel					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8 x 20	8.5 x 16	8.5 x 18	8.5 x 20
Model #	H9620TFTV-140	H10116TFTV-140	H10118TFTV-140	H10120TFTV-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	3570	3450	3650	
Payload	10430	10550	10350	
CHASSIS				
Coupler	2-5/16" Adjustable			
Tongue	6" x 2" Steel Triple Tube			
Tongue Jack	7K Drop Leg, Set-Back			
Front Profile	V-Nose			
Frame	6" x 2" Steel Tube			
Crossmembers	Steel Formed Channel, 16" On-Center			
Roof Bows	Galvanized Steel Tube, 16" On-Center			
Wall Posts	Steel Tube, 16" On-Center			
Ramp(s)	400 Series with Assist			
Side Door	36" Wide Flush Lock, Aluminum Holdback			
Axle	(2) 7000 lb. Drop Spring Brake			
Hubs	Easy Lube			
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel			
Flooring	3/4" Engineered Wood			
Interior Walls	Engineered Wood			
Interior Trim	Aluminum H-Channel Wall Transitions			
Exterior Finish	.030" Aluminum			
Stone Guard	24" ATP			
Roof	Flat Top .024 Aluminum Sheeted			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Wiring	Enclosed in Conduit			
Interior Lights	(2) LED Dome Lights, Wall Mount			
Exterior Lights	Full LED, DOT Compliant			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO FLAT TOP 03-05K

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Model #	H608SFTV-035	H6010SFTV-035	H7210SFTV-035	H7212SFTV-035	H7214SFTV-035	H8412SFTV-035
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
Curb Weight	1030	1230	1320	1375	1500	1650
Payload	1960	1760	1670	1615	1490	1340
CHASSIS						
Coupler	2" A-Frame, Posi-Lock					
Tongue	3" x 2" Steel Tube					4" x 2" Steel Tube
Tongue Jack	2K Swivel Jack with Foot					
Frame	3" x 2" Steel Tube					4" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Side Door		32" Wide Flush Lock, Aluminum Holdback				
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.030" Aluminum					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST205/75R15C 6-PLY					
Wiring	Enclosed in Conduit					
Interior Lights	(1) LED					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	65	70				
Width Rear Opening	58	66				78
Deck Height	18					
Height Overall	86	92				96
Deck Length	123	147	171		195	171
Width Interior	57	69		81		
Length Interior Box	123	147	171		195	171
DIMENSIONS						
Overall Length	162	186	210		234	210
Deck Length	123	147	171		195	171
Deck Width	57	69				81
Deck Height	18					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Model #	H608SFTV-050	H6010SFTV-050	H7210SFTV-050	H7212SFTV-050	H7214SFTV-050	H8412SFTV-050
CAPACITIES						
GVWR (lbs)	5000					
GAWR (lbs/axle)	5000	5200				
Curb Weight	1330		1485	1550	1675	1825
Payload	3670		3515	3450	3325	3175
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube					
Tongue Jack	2K Swivel Jack with Foot					
Frame	4" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Side Door		32" Wide Flush Lock, Aluminum Holdback				
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.030" Aluminum					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST225/75R15D 8-PLY					
Wiring	Enclosed in Conduit					
Interior Lights	(1) LED					
Exterior Lights	Full LED, DOT Compliant					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO FLAT TOP 07K

6 x 12		6 x 14		7 x 12	7 x 14	7 x 16	7 x 18
Model #	H7212TFTV-070	H7214TFTV-070		H8412TFTV-070	H8414TFTV-070	H8416TFTV-070	H8418TFTV-070
CAPACITIES							
GVWR (lbs)	7000						
GAWR (lbs/axle)	3500						
Curb Weight	1750	2050		1930	2100	2220	2380
Payload	5250	4950		5070	4900	4780	4620
CHASSIS							
Coupler	2-5/16" A-Frame, Posi-Lock						
Tongue	4" x 2" Steel Tube						6" x 2" Steel Tube
Front Profile	V-Nose						
Frame	4" x 2" Steel Tube			4" x 2" Steel Tube			6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center	Steel Formed Channel, 24" On-Center		Steel Formed Channel, 16" On-Center			
Roof Bows	Galvanized Steel Tube, 24" On-Center						
Wall Posts	Steel Tube, 24" On-Center						
Side Door	36" Wide Flush Lock, Aluminum Holdback	36" Wide Flush Lock		36" Wide Flush Lock, Aluminum Holdback			
Axle	(2) 3500 lb. Drop Spring Brake						
Hubs	Easy Lube			Easy Lube			
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel			Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel			
Interior Walls	Engineered Wood			Engineered Wood			
Interior Trim	Aluminum H-Channel Wall Transitions			Aluminum H-Channel Wall Transitions			
Exterior Finish	.030" Aluminum						
Stone Guard	24" ATP						
Roof	Flat Top .024 Aluminum Sheeted						
Tires	ST205/75R15C 6-PLY						
Wheels	15", 5-Lug Steel			15", 5-Lug Steel			
Wiring	Sealed Wiring Harness						
Interior Lights	(2) LED Dome Lights, Wall Mount						
Exterior Lights	Full LED, DOT Compliant						
Height Rear Opening	69			69			
Width Rear Opening	66			78			
Deck Height	19			19			20
Height Overall	93			97			99
Deck Length	171			171	195	219	243
Width Interior	69			82			
Length Interior Box	171			171	195	219	243
DIMENSIONS							
Overall Length	210			214	238	262	286
Deck Length	171			171	195	219	243
Deck Width	69			82			
Deck Height	19			19			20

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 20	8 x 14	8 x 16	8 x 18	8 x 20	8.5 x 14
Model #	H8420TFTV-070	H9614TFTV-070	H9616TFTV-070	H9618TFTV-070	H9620TFTV-070	H10114TFTV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2470	2680	2500	2590	2760	2500
Payload	4530	4320	4500	4410	4240	4500
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	6" x 2" Steel Tube	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Triple Tube
Tongue Jack		2K Coupler Mounted				
Front Profile	V-Nose					
Frame	6" x 2" Steel Tube	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Ramp(s)		400 Series with Assist				
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.030" Aluminum					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Wiring	Sealed Wiring Harness					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	69					
Width Rear Opening	78					
Deck Height	20					
Height Overall	99					
Deck Length	267					
Width Interior	82					
Length Interior Box	267					
DIMENSIONS						
Overall Length	322					
Deck Length	267					
Deck Width	82					
Deck Height	20					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 16	8.5 x 18	8.5 x 20
Model #	H10116TFTV-070	H10118TFTV-070	H10120TFTV-070
CAPACITIES			
GVWR (lbs)	7000		
GAWR (lbs/axle)	3500		
Curb Weight	2600	2810	3100
Payload	4400	4190	3900
CHASSIS			
Coupler	2-5/16" A-Frame, Posi-Lock		
Tongue	4" x 2" Steel Triple Tube	6" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted		
Front Profile	V-Nose		
Frame	4" x 2" Steel Tube	6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center		
Roof Bows	Galvanized Steel Tube, 24" On-Center		
Wall Posts	Steel Tube, 24" On-Center		
Ramp(s)	400 Series with Assist		
Side Door	36" Wide Flush Lock, Aluminum Holdback		
Axle	(2) 3500 lb. Drop Spring Brake		
Hubs	Easy Lube		
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel		
Interior Walls	Engineered Wood		
Interior Trim	Aluminum H-Channel Wall Transitions		
Exterior Finish	.030" Aluminum		
Stone Guard	24" ATP		
Roof	Flat Top .024 Aluminum Sheeted		
Tires	ST205/75R15C 6-PLY		
Wheels	15", 5-Lug Steel		
Wiring	Sealed Wiring Harness		
Interior Lights	(2) LED Dome Lights, Wall Mount		
Exterior Lights	Full LED, DOT Compliant		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.