



SPECIFICATIONS -EQUIPMENT - STEEL
C-CHANNEL EQUIPMENT 14K

	7 x 16	7 x 18	7 x 20	7 x 22	7 x 24
Model #	ST-ET8216-140	ST-ET8218-140	ST-ET8220-140	ST-ET8222-140	ST-ET8224-140
CAPACITIES					
GVWR (lbs)	14000				
GAWR (lbs/axle)	7000				
Curb Weight	2800	2870	3195	3500	3680
Payload	11200	11130	10805	10500	10320
CHASSIS					
Coupler	2-5/16" Adjustable				
Tongue	6" Steel Channel, Fully Wrapped				
Tongue Jack	12K Drop Leg, Set-Back				
Frame	6" Steel Channel, Winch Ready Frame				Winch Ready Frame
Crossmembers	3" Steel Channel, 16" On-Center				
Beavertail	24"				
Ramp(s)	4" x 5' Spring Assist with Adjustable Support Legs				
Axle	(2) 7000 lb. Slipper Spring Brake				
Hubs	Easy Lube				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	ST235/80R16E 10-PLY				
Wheels	16", 8-Lug Steel				
Tie Downs	(4) 1/2" D-Rings, Stake Pockets and Rub Rail				
Exterior Lights	Full LED, DOT Compliant				
Bulkhead	HD Tube				
Decking	2" Pressure Treated Pine				
Exterior Storage	Ready for Drop-In (Recessed) Lockable Toolbox, Spare Tire Carrier				
Coupler Height	19-27				
Deck Height	24				
Width Between Fender	82				
Length Ramp	60				
DIMENSIONS					
Overall Length	273	297	321	345	369
Deck Height	24				
Coupler Height	19-27				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.