



SPECIFICATIONS -DUMP
PRO SERIES TELESCOPIC DUMP GN 15.4K

7 x 14		7 x 16	
Model #	ST-BTL8214-154G		ST-BTL8216-154G
CAPACITIES			
GVWR (lbs)	15400		
GAWR (lbs/axle)	7000		
Curb Weight	5020		
Payload	10380		
CHASSIS			
Coupler	2-5/16" Adjustable Gooseneck		
Tongue	Fabricated Single Piece Gooseneck	8" Flange, 13 lb/ft I-Beam, Fabricated Single Piece Gooseneck	
Tongue Jack	Dual 12K, 2-Speed Landing Gear		
Frame	8", 13 lb/ft I-Beam		
Ramp(s)	4" x 80" Steel Ladder Style (Slide-In with Carrier)		
Integrated Step(s)	Side Steps		
Stabilizers	Rear Drop-Leg Jacks		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Easy Lube		
Exterior Finish	Industrial Grade Polymer Finish		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Steel		
Tie Downs	(5) 1/2" D-Rings, Stake Pockets		
Exterior Lights	Full LED, DOT Compliant		
Top Rail	3" x 2" Steel Tube		
Sides	48" Tall Rigid Panels	24" Tall Rigid Panels, Board Holders	
Gate	NaN		
Decking	7-Gauge Smooth Steel		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Hydraulic Components	12 Volt Hydraulic Pump, Power Up, Gravity Down (Telescopic Hoist)		
Tarp	18' Mesh Tarp Kit (Installed), Anti-Sail Kit with Integrated Tie-Down, Integrated Tarp Mount and Shroud		
Coupler Height	31-39.75		
Deck Height	27.75		
Width Interior	82		
Length Interior Box	169	193	
DIMENSIONS			
Overall Length	277	301	
Deck Width	82		
Deck Height	27.75		
Coupler Height	31-39.75		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.