



SPECIFICATIONS -STEEL UTILITY OPEN STEEL RAIL SIDE SINGLE 3K

	60 x 8	66 x 10	76 x 10	76 x 12	82 x 12	82 x 14
Model #	H-RS6008-030	H-RS6610-030	H-RS7610-030	H-RS7612-030	H-RS8212-030	H-RS8214-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
Curb Weight	750	890	970	1050	1110	1210
Payload	2240	2100	2020	1940	1880	1780
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" Steel Channel					
Tongue Jack	2K Set-Back					
Frame	3" x 2" x 3/16" Steel Angle					
Crossmembers	3" x 2" x 3/16" Steel Angle					
Ramp(s)	50" Fold-Flat, Spring-Assist with Grab Handle					
Axle	3500 lb. Spring Idler					
Hubs	Easy Lube					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Tie Downs	Stake Pockets					
Wiring	Enclosed Sealed Wiring Harness					
Exterior Lights	Full LED, DOT Compliant					
Top Rail	2" x 2" Steel Tube					
Uprights	2" x 1 1/2" Steel Tube					
Decking	2" Pressure Treated Pine, Board Retainers					
Exterior Storage	Spare Tire Carrier					
Deck Height	20.25					
Height Overall	70.25					
Width Interior	60.25	66.25	76.25		82.25	
Width Ramp	55	61	71		77	
Length Ramp	50					
DIMENSIONS						
Overall Length	140	164		188		212
Deck Width	60.25	66.25	76.25		82.25	
Deck Height	20.25					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL UTILITY OPEN STEEL RAIL SIDE TANDEM 7K

	82 x 14	82 x 16	82 x 18	82 x 20	82 x 24
Model #	H-RS8214-070	H-RS8216-070	H-RS8218-070	H-RS8220-070	H-RS8224-070
CAPACITIES					
GVWR (lbs)	7000				
GAWR (lbs/axle)	3500				
Curb Weight	1610	1790	1890	1970	2700
Payload	5390	5210	5110	5030	4300
CHASSIS					
Coupler	2-5/16" A-Frame, Posi-Lock				
Tongue	4" Steel Channel, Fully Wrapped				
Tongue Jack	2K Set-Back				
Frame	4" x 3" x 1/4" Steel Angle				
Crossmembers	3" x 2" x 3/16" Steel Angle				
Ramp(s)	50" Fold-Flat, Spring-Assist with Grab Handle				
Axle	(2) 3500 lb. Spring Brake				
Hubs	Easy Lube				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	ST205/75R15C 6-PLY				
Wheels	15", 5-Lug Steel				
Tie Downs	Stake Pockets				
Wiring	Enclosed Sealed Wiring Harness				
Exterior Lights	Full LED, DOT Compliant				
Top Rail	2" x 2" Steel Tube				
Uprights	2" x 1 1/2" Steel Tube				
Decking	2" Pressure Treated Pine, Board Retainers				
Exterior Storage	Spare Tire Carrier				
Deck Height	20.25				
Height Overall	70.25				
Width Interior	82.25				
Width Ramp	77				
Length Ramp	50				
DIMENSIONS					
Overall Length	218	242	266	290	338
Deck Width	82.25				
Deck Height	20.25				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.