

140T - Heavy Duty Over-The-Axle Tilt

STANDARD FEATURES & OPTIONS

Tires	ST235/80 R-16 Load Range E Radial Tires	Wiring	Sealed, Modular Cold-Weather Wiring Harness
Brakes	Forward Self-Adjusting Electric Brakes on Both Axles	Bolt Pattern	8-Bolt
Suspension	Multi-Leaf Slipper Spring w/ Equalizer	Spare Mount	Front Spare Tire Mount
Axles	2 - 7,000# Premium, with Quick-Lubricating Hubs	Spare Tire	Not Included
Coupler	Adjustable 2-5/16" Demco EZ Latch, Round Adjustable Pin 2-5/16" on Gooseneck Model	Paint Type	Professional Finish w/ Primer Standard
Safety Chains	3/8" Grade 70 w/ Safety Latch Hook (2 ea)	Paint Color	Black
Jack	12,000# Drop-Leg Jack (Side Wind) Dual Jacks on Gooseneck Model	Tilt Deck Dimensions	102" Wide with 1/4" Diamond plate Knife Edge
Frame	8" I-Beam, 10# / 13# on 26' Models	Tilt Deck Operation	Power Up/Power Down with Hydraulic System
Cross-Members	3" Channel	Rub Rail	Rub Rail Along Both Sides
Front Stop Rail	3/16" Fabricated Front Stop Rail (Bumper Pull Only)	Break-Away Kit	Complete Breakaway System w/ Zip™ Breakaway Cable and Charger
Floor	Treated Pine Floor	Power	Power Up/Power Down & Gravity Down Hydraulic Pump
Stake Pockets	Stake Pockets Along Both Sides (Quantity Varies by Length)	Tilt Deck Angle	16°
Trailer Plug	7-Way RV	Winch Plate	Front Mounted Steel Winch Plate
Lights	Recessed, Grommet-Mounted L.E.D. Lighting		

MODELS & DIMENSIONS

Model	Pull Type	GVWR	GAWR (Ea. Axle)	Empty Weight	Cargo Capacity	Bed Length	Bed Width
140T-22	Bumperpull	14000	7000	4745	9255	22'	102"
140T-24	Bumperpull	14000	7000	4950	9050	24'	102"
140T-26	Bumperpull	14000	7000	5290	8710	26'	102"
140T-22GN	Bumperpull	14000	7000	4970	9030	22'	102"
140T-24GN	Bumperpull	14000	7000	5175	8825	24'	102"
140T-26GN	Bumperpull	14000	7000	5155	8845	26'	102"

MEASUREMENTS

Model	Payload	A	B	C	Tongue Length
140T-22		264"	141"	123"	73-3/8"
140T-24		288"	159"	129"	73-3/8"
140T-26		312"	171"	141"	73-3/8"
140T-22GN		264"	141"	123"	96-1/8"
140T-24GN		288"	159"	129"	96-1/8"
140T-26GN		312"	171"	141"	96-1/8"

