



SPECIFICATIONS -QUAKE CARGO
QUAKE FLAT TOP V-NOSE 3K

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Model #	KI-DX6008-030	KI-DX6010-030	KI-DX7210-030	KI-DX7212-030	KI-DX7214-030	KI-DX8412-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" x 2" Steel Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Crossmembers	Formed Steel, 24" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	66"	78"				84"
Ramp(s)	150 Series with Assist					250 Series with Assist
Side Door	No STD Side Entry Door	32" Wide Flush Lock, Plastic Holdback		36" Wide Flush Lock, Plastic Holdback		
Axle	3500 lb. Drop Spring Idler					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Luan Strip					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	62	74				80
Width Rear Opening	53.5	65.5				77.5
Coupler Height	17					
Deck Height	18					
Height Overall	87	99				104
Deck Length	107	131		155	179	155
Width Interior	57	69				81
Length Interior Box	93	117		141	165	141
DIMENSIONS						
Overall Length	146	170		194	218	200
Deck Length	107	131		155	179	155
Deck Width	57	69				81
Deck Height	18					
Coupler Height	17					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Model #	KI-DX6008-035	KI-DX6010-035	KI-DX7210-035	KI-DX7212-035	KI-DX7214-035	KI-DX8412-035
CAPACITIES						
GVWR (lbs)	3500					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" x 2" Steel Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Crossmembers	Formed Steel, 24" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	66"	78"				84"
Ramp(s)	150 Series with Assist					250 Series with Assist
Side Door	No STD Side Entry Door	32" Wide Flush Lock, Plastic Holdback		36" Wide Flush Lock, Plastic Holdback		
Axle	3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Luan Strip					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	62	74				80
Width Rear Opening	53.5	65.5				77.5
Coupler Height	17					
Deck Height	18					
Height Overall	87	99				104
Deck Length	107	131		155	179	155
Width Interior	57	69				81
Length Interior Box	93	117		141	165	141
DIMENSIONS						
Overall Length	146	170		194	218	200
Deck Length	107	131		155	179	155
Deck Width	57	69				81
Deck Height	18					
Coupler Height	17					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

7 x 14	
Model #	KI-DX8414-035
CAPACITIES	
GVWR (lbs)	3500
GAWR (lbs/axle)	3500
CHASSIS	
Coupler	2" A-Frame
Tongue	4" x 2" Steel Tube
Tongue Jack	2K Coupler Mounted
Front Profile	16" V-Nose
Crossmembers	Formed Steel, 24" On-Center
Roof Bows	Steel Tube, 24" On-Center
Wall Posts	Steel Tube, 24" On-Center
Standard Interior Height	84"
Ramp(s)	250 Series with Assist
Side Door	36" Wide Flush Lock, Plastic Holdback
Axle	3500 lb. Drop Spring Brake
Hubs	Easy Lube
Undercoating	Asphalt Emulsion
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Engineered Wood Wall Transitions
Ceiling	Luan Strip
Exterior Finish	Piedmont .080" Composite Panels
Exterior Fastening	Screwless Sidewalls
Stone Guard	24" ATP
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Tires	ST205/75R15C 6-PLY
Wheels	15", 5-Lug Steel
Vents	Sidewall Airflow
Interior Lights	(1) LED Dome Light, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Switches	(1) Dome Light, 12V
Height Rear Opening	80
Width Rear Opening	77.5
Coupler Height	17
Deck Height	18
Height Overall	104
Deck Length	179
Width Interior	81
Length Interior Box	165
DIMENSIONS	
Overall Length	224
Deck Length	179
Deck Width	81
Deck Height	18
Coupler Height	17

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -QUAKE CARGO
QUAKE FLAT TOP V-NOSE 7K

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	8.5 x 14
Model #	KI-DX7212-070	KI-DX7214-070	KI-DX8412-070	KI-DX8414-070	KI-DX8416-070	KI-DX10214-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	4" x 2" Steel Tube				6" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Crossmembers	Formed Steel, 24" On-Center				Formed Steel, 16" On-Center	
Roof Bows	Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center				Steel Tube, 16" On-Center	
Standard Interior Height	78"		84"			
Ramp(s)	150 Series with Assist		250 Series with Assist			400 Series with Assist
Side Door	36" Wide Flush Lock, Plastic Holdback					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier				BATTLECOAT Polyurea Coating	
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Lauan Strip					
Exterior Finish	Piedmont .080" Composite Panels					
Exterior Fastening	Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount				(2) LED Dome Lights, Wall Mount	
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Height Rear Opening	74		80			
Width Rear Opening	65.5		77.5			93.5
Coupler Height	18				20	
Deck Height	19				21	
Height Overall	100		105			107
Deck Length	155	179	155	179	203	179
Width Interior	69		81			97
Width Between Fender						81.5
Length Interior Box	141	165	141	165	189	165
DIMENSIONS						
Overall Length	194	218	200	224	248	224
Deck Length	155	179	155	179	203	179
Deck Width	69		81			97

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	8.5 x 14
Deck Height			19			21
Coupler Height			18			20

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 16		8.5 x 18		8.5 x 20		8.5 x 22		8.5 x 24		8.5 x 26	
Model #	KI-DX10216-070		KI-DX10218-070		KI-DX10220-070		KI-DX10222-070		KI-DX10224-070		KI-DX10226-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
CHASSIS												
Coupler	2-5/16" A-Frame											
Tongue	6" x 2" Steel Triple Tube											
Tongue Jack	2K Coupler Mounted											
Front Profile	16" V-Nose											
Frame	6" x 2" Steel Tube											
Crossmembers	Formed Steel, 16" On-Center											
Roof Bows	Steel Tube, 24" On-Center											
Wall Posts	Steel Tube, 16" On-Center											
Standard Interior Height	84"											
Ramp(s)	400 Series with Assist											
Side Door	36" Wide Flush Lock, Plastic Holdback											
Axle	(2) 3500 lb. Drop Spring Brake											
Hubs	Easy Lube											
Undercoating	Asphalt Emulsion											
Protective Coating(s)	BATTLECOAT Polyurea Coating											
Flooring	3/4" Engineered Wood											
Interior Walls	Engineered Wood											
Interior Trim	Engineered Wood Wall Transitions											
Ceiling	Lauan Strip											
Exterior Finish	Piedmont .080" Composite Panels											
Exterior Fastening	Screwless Sidewalls											
Stone Guard	24" ATP											
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop											
Roof	Flat Top Seamless Aluminum											
Tires	ST205/75R15C 6-PLY											
Wheels	15", 5-Lug Steel											
Vents	Sidewall Airflow											
Interior Lights	(2) LED Dome Lights, Wall Mount											
Exterior Lights	Full LED, DOT Compliant											
Switches	(1) Dome Light, 12V											
Height Rear Opening	80											
Width Rear Opening	93.5											
Coupler Height	20											
Deck Height	21											
Height Overall	107											
Deck Length	203	227	251	275	299	323						
Width Interior	97											
Width Between Fender	81.5											
Length Interior Box	189	213	237	261	285	309						
DIMENSIONS												
Overall Length	248	272	296	320	344	368						
Deck Length	203	227	251	275	299	323						
Deck Width	97											

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Deck Height				21		
Coupler Height				20		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -QUAKE CARGO
QUAKE FLAT TOP V-NOSE 10K

	8.5 x 14		8.5 x 16		8.5 x 18		8.5 x 20		8.5 x 22		8.5 x 24	
Model #	KI-DX10214-100		KI-DX10216-100		KI-DX10218-100		KI-DX10220-100		KI-DX10222-100		KI-DX10224-100	
CAPACITIES												
GVWR (lbs)	9900											
GAWR (lbs/axle)	5000											
CHASSIS												
Coupler	2-5/16" A-Frame											
Tongue	6" x 2" Steel Triple Tube											
Tongue Jack	2K Coupler Mounted											
Front Profile	16" V-Nose											
Frame	6" x 2" Steel Tube											
Crossmembers	Formed Steel, 16" On-Center											
Roof Bows	Steel Tube, 24" On-Center											
Wall Posts	Steel Tube, 16" On-Center											
Standard Interior Height	84"											
Ramp(s)	400 Series with Assist											
Side Door	36" Wide Flush Lock, Plastic Holdback											
Axle	(2) 5200 lb. Drop Spring Brake											
Hubs	Easy Lube											
Undercoating	Asphalt Emulsion											
Protective Coating(s)	BATTLECOAT Polyurea Coating											
Flooring	3/4" Engineered Wood											
Interior Walls	Engineered Wood											
Interior Trim	Engineered Wood Wall Transitions											
Ceiling	Lauan Strip											
Exterior Finish	Piedmont .080" Composite Panels											
Exterior Fastening	Screwless Sidewalls											
Stone Guard	24" ATP											
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop											
Roof	Flat Top Seamless Aluminum											
Tires	ST225/75R15D 8-PLY											
Wheels	15", 6-Lug Steel											
Vents	Sidewall Airflow											
Interior Lights	(2) LED Dome Lights, Wall Mount											
Exterior Lights	Full LED, DOT Compliant											
Switches	(1) Dome Light, 12V											
Height Rear Opening	80											
Width Rear Opening	93.5											
Coupler Height	21											
Deck Height	22											
Height Overall	108											
Deck Length	179	203	227	251	275	299						
Width Interior	97											
Width Between Fender	81.5											
Length Interior Box	165	189	213	237	261	285						
DIMENSIONS												
Overall Length	224	248	272	296	320	344						
Deck Length	179	203	227	251	275	299						
Deck Width	97											

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Deck Height				22		
Coupler Height				21		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 26	
Model #	KI-DX10226-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Coupler	2-5/16" A-Frame
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted
Front Profile	16" V-Nose
Frame	6" x 2" Steel Tube
Crossmembers	Formed Steel, 16" On-Center
Roof Bows	Steel Tube, 24" On-Center
Wall Posts	Steel Tube, 16" On-Center
Standard Interior Height	84"
Ramp(s)	400 Series with Assist
Side Door	36" Wide Flush Lock, Plastic Holdback
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Undercoating	Asphalt Emulsion
Protective Coating(s)	BATTLECOAT Polyurea Coating
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Engineered Wood Wall Transitions
Ceiling	Luan Strip
Exterior Finish	Piedmont .080" Composite Panels
Exterior Fastening	Screwless Sidewalls
Stone Guard	24" ATP
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Tires	ST225/75R15D 8-PLY
Wheels	15", 6-Lug Steel
Vents	Sidewall Airflow
Interior Lights	(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Switches	(1) Dome Light, 12V
Height Rear Opening	80
Width Rear Opening	93.5
Coupler Height	21
Deck Height	22
Height Overall	108
Deck Length	323
Width Interior	97
Width Between Fender	81.5
Length Interior Box	309
DIMENSIONS	
Overall Length	368
Deck Length	323
Deck Width	97

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 26	
Deck Height	22
Coupler Height	21

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.