



SPECIFICATIONS -STEEL UTILITY OPEN STEEL ATV SINGLE 3K

82 x 12		82 x 14
Model #	H-RSV8212-030	H-RSV8214-030
CAPACITIES		
GVWR (lbs)	2990	
GAWR (lbs/axle)	3500	
Curb Weight	1390	1410
Payload	1600	1580
CHASSIS		
Coupler	2" A-Frame, Posi-Lock	
Tongue	4" Steel Channel	
Tongue Jack	2K Set-Back	
Frame	4" x 3" x 1/4" Steel Angle	
Crossmembers	3" x 2" x 3/16" Steel Angle	
Ramp(s)	50" Fold-Flat, Spring-Assist with Grab Handle	
Axle	3500 lb. Spring Idler	
Hubs	Easy Lube	
Exterior Finish	Industrial Grade Polymer Finish	
Wheels	15", 5-Lug Steel	
Tie Downs	Stake Pockets	
Exterior Lights	Full LED, DOT Compliant	
Top Rail	2" x 2" Steel Tube	
Uprights	2" x 1 1/2" Steel Tube	
Sides	(2) 2" x 5' Steel Side Ramp Conversions	
Decking	2" Pressure Treated Pine, Board Retainers	
Deck Height	20.25	
Height Overall	70.25	
Width Interior	82.25	
Width Ramp	77	
Length Ramp	50	
DIMENSIONS		
Overall Length	188	212
Deck Width	82.25	
Deck Height	20.25	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL UTILITY OPEN STEEL ATV TANDEM 10K

	82 x 14	82 x 16	82 x 18	82 x 20
Model #	H-HRSV8214-100	H-HRSV8216-100	H-HRSV8218-100	H-HRSV8220-100
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	5200			
Curb Weight		2050		
Payload		4950		
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	5" Steel Channel, Fully Wrapped			
Tongue Jack	7K Drop Leg, Set-Back			
Frame	5" x 3" x 1/4" Steel Angle			
Crossmembers	3" x 2" x 3/16" Steel Angle			
Ramp(s)	50" Fold Flat HD Reinforced Spring Assist with Grab Handle (Ladder Style)			
Axle	(2) 5200 lb. Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST225/75R15D 8-PLY			
Wheels	15", 6-Lug Steel			
Tie Downs	Stake Pockets			
Wiring	Enclosed Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Top Rail	3" x 2" Steel Tube			
Uprights	2" x 1 1/2" Steel Tube			
Sides	(2) 2" x 5' Steel Side Ramp Conversions			
Decking	2" Pressure Treated Pine, Board Retainers			
Exterior Storage	Spare Tire Carrier			
Deck Height	20.25			
Height Overall	70.25			
Width Interior	82.25			
Width Ramp	77			
Length Ramp	50			
DIMENSIONS				
Overall Length	228	252	276	300
Deck Width	82.25			
Deck Height	20.25			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -STEEL UTILITY OPEN STEEL ATV TANDEM 7K

	82 x 14	82 x 16	82 x 18	82 x 20
Model #	H-RSV8214-070	H-RSV8216-070	H-RSV8218-070	H-RSV8220-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
Curb Weight	1960	2050	2140	2230
Payload	5040	4950	4860	4770
CHASSIS				
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue	4" Steel Channel, Fully Wrapped			
Tongue Jack	2K Set-Back			
Frame	4" x 3" x 1/4" Steel Angle			
Crossmembers	3" x 2" x 3/16" Steel Angle			
Ramp(s)	50" Fold-Flat, Spring-Assist with Grab Handle			
Axle	(2) 3500 lb. Spring Brake			
Hubs	Easy Lube			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST205/75R15C 6-PLY			
Wheels	15", 5-Lug Steel			
Tie Downs	Stake Pockets			
Wiring	Enclosed Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Top Rail	2" x 2" Steel Tube			
Uprights	2" x 1 1/2" Steel Tube			
Sides	(2) 2" x 5' Steel Side Ramp Conversions			
Decking	2" Pressure Treated Pine, Board Retainers			
Exterior Storage	Spare Tire Carrier			
Deck Height	20.25			
Height Overall	70.25			
Width Interior	82.25			
Width Ramp	77			
Length Ramp	50			
DIMENSIONS				
Overall Length	228	252	276	300
Deck Width	82.25			
Deck Height	20.25			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.