

LOW PROFILE GOOSENECK DUMP



MODEL	AXLE DESCRIPTION	TIRE SIZE	GAWR	GVWR
GOOSENECK LOW PROFILE DUMP				
14x83" DX16GN			8000#	17500#
16x83" DX16GN				

Options

- DX Spring Loaded Long Arm Retractable Tarp ILO Standard Tarp
- Ground Level Crank Kit For Spring Loaded Long Arm Retractable Tarp (3-4' Sides Only)
- Motorized Spring Loaded Long Arm Retractable Tarp ILO Standard Tarp
- Gas Engine Powered Pump in Lieu of Electric Pump
- Spare ST215/75R/17.5 LRH on 8-Hole
- Dual Hydraulic 12K Jack Replacing Dual 12K Jack
- Hoist Upgrade w/10" Frame Upgrade
- Telescopic Hoist ILO Scissor Hoist
- Solar Battery Charger
- Jumbo Step (40" Replaces 18" Side Step)

Frame Structure

- Frame: 8" I-Beam
- Neck & Risers: 10" I-Beam
- Sides: 24" Tall 10 GA Sheet Metal w/Toprail
- Floor: 7 GA Sheet Metal
- Toprail: Rigid 3x2x7 GA Rectangular Tubing
- Uprights: Formed Channel

- Dump Body Frame: 6" Channel
- Crossmembers: 3" Channel 16" OC

Standard Equipment

- ST215/75R/17.5 LRH Tires on 8-Hole
- 8000# Dexter Oil Bath 1/2 Cambered Axles w/5/8" Lug Studs
- Electric Brake on 2-Axles w/2 1/4" Brake Pads
- 2 5/16" Round Adjustable Coupler
- Dual 10000# Drop Leg Jacks
- HD Diamond Plate Fender (Double Broke)
- Width: 83" Inside Box
- Break Away Unit w/Charger
- DOT Reflective Tape
- Primed & Painted Underside
- Dual Action Swing Out Doors/1 Piece Spreader Gate
- Slide-N Ramp 6' Channel
- 5/8" D-Rings in Box (4)
- Spare Rack
- Sealed Flush Mount LED Lights
- Side Step (Driver Side)
- Wiring Harness
- Lockable Battery/Pump Box
- Crank Style Roll Tarp & Tie Downs
- Rear Stabilizer Stands
- Color: Black

Dump Components

- 520 Scissor Hoist On 14'-16'
- Power Up/Power Down/Gravity Down
- Control: Pistol Grip w/10' Cord
- Safety Prop
- Caulked Seams on Dump Body
- Deep Cycle 12V Marine Battery
- 110 Volt-5 Amp Charger

High Sides

- 3' Tall Sheet Metal Sides
- 4' Tall Sheet Metal Sides