



SPECIFICATIONS -MIDSOTA OPENS

MIDSOTA STWB 17.6K

	102 x 22	102 x 24	102 x 26	102 x 28	102 x 30
Model #	N-STWB22-176	N-STWB24-176	N-STWB26-176	N-STWB28-176	N-STWB30-176
CAPACITIES					
GVWR (lbs)	17600				
GAWR (lbs/axle)	8000				
Curb Weight	4595	4785	4995	5185	5395
Payload	13005	12815	12605	12415	12205
CHASSIS					
Coupler	2 5/16" Adjustable Channel Mount, Demco EZ Latch				
Tongue Jack	12K Drop Leg, Set-Back				
Frame	8" x 3" Steel Tube				
Crossmembers	Rolled Grade 50 3" Steel Channel				
Beavertail	4'				
Axle	(2) 8000 lb. Slipper Spring Brake				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	215/75R17.5J 18-PLY				
Tie Downs	Stake Pockets and Rub Rail				
Wiring	No Exposed Wiring				
Exterior Lights	Full LED, DOT Compliant				
Decking	2" Pressure Treated Pine				
Coupler Height	11.5 - 19.5				
Deck Height	28				
Load Angle	14.5				
DIMENSIONS					
Overall Length	338	362	386	410	434
Deck Height	28				
Coupler Height	11.5 - 19.5				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 24	102 x 26	102 x 28	102 x 30	102 x 32
Model #	N-STWB24-184G	N-STWB26-184G	N-STWB28-184G	N-STWB30-184G	N-STWB32-184G
CAPACITIES					
GVWR (lbs)	18400				
GAWR (lbs/axle)	8000				
Curb Weight	5385	5595	5785	5995	6500
Payload	13015	12805	12615	12405	11900
CHASSIS					
Coupler	2-5/16" Adjustable Gooseneck				
Tongue Jack	12K, 2-Speed Drop Leg				
Frame	8" x 3" Steel Tube				
Crossmembers	Rolled Grade 50 3" Steel Channel				
Beavertail	4'				
Axle	(2) 8000 lb. Slipper Spring Brake				(2) 8000 lb. Slipper Spring Brake
Exterior Finish	Industrial Grade Polymer Finish				
Tires	215/75R17.5J 18-PLY				
Tie Downs	Stake Pockets and Rub Rail				
Wiring	No Exposed Wiring				
Exterior Lights	Full LED, DOT Compliant				
Decking	2" Pressure Treated Pine				
Exterior Storage	Receiver Tube Winch Mount, Spare Tire Carrier				
Coupler Height	0				
DIMENSIONS					
Coupler Height	0				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 26	102 x 28	102 x 30	102 x 32
Model #	N-STWBHB26-176	N-STWBHB28-176	N-STWBHB30-176	N-STWBHB32-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4995	5185	5750	5585
Payload	12605	12415	11850	12015
CHASSIS				
Coupler	2 5/16" Adjustable Channel Mount, Demco EZ Latch			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	8" x 3" Steel Tube			
Crossmembers	3" Steel Channel			
Beavertail	7' Hydraulic			
Axle	(2) 8000 lb. Slipper Spring Brake			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Tie Downs	Stake Pockets and Rub Rail			
Wiring	No Exposed Wiring			
Exterior Lights	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Exterior Storage	Poly Toolbox			
Coupler Height	0			
DIMENSIONS				
Coupler Height	0			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 26	102 x 28	102 x 30	102 x 32
Model #	N-STWBHB26-184G	N-STWBHB28-184G	N-STWBHB30-184G	N-STWBHB32-184G
CAPACITIES				
GVWR (lbs)	18400			
GAWR (lbs/axle)	8000			
Curb Weight	6260	6495	6717	6790
Payload	12140	11905	11683	11610
CHASSIS				
Coupler	2-5/16" Adjustable Gooseneck			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Frame	8" x 3" Steel Tube			
Crossmembers	3" Steel Channel			
Beavertail	7' Hydraulic			
Axle	(2) 8000 lb. Slipper Spring Brake			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	215/75R17.5J 18-PLY			
Tie Downs	Stake Pockets and Rub Rail			
Wiring	No Exposed Wiring			
Exterior Lights	Full LED, DOT Compliant			
Decking	2" Pressure Treated Pine			
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier			
Coupler Height	0			
DIMENSIONS				
Coupler Height	0			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.