



SPECIFICATIONS -MIDSOTA DECKOVER
MIDSOTA FB GN 23K

	102 x	102 x 24	102 x 26	102 x 28	102 x 30	102 x 32
Model #	N-FB40-230G	N-FB24-230G	N-FB26-230G	N-FB28-230G	N-FB30-230G	N-FB32-230G
CAPACITIES						
GVWR (lbs)	23000					
GAWR (lbs/axle)	10000					
Curb Weight	8880	6880	6650	7380	7630	7880
Payload	14120	16120	16350	15620	15370	15120
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Gooseneck, High Strength Manufactured I-Beam					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Frame	High Strength Manufactured I-Beam, Square Torque Tube					
Crossmembers	3" Steel Channel, 16" On-Center					
Beavertail	5' Cleated					
Ramp(s)	Fold Over Wedge, Spring Assist					
Integrated Step(s)	Side Steps					
Axle	(2) 10000 lb. Slipper Spring Brake					
Hubs	Oil Bath					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/80R16E 10-PLY					
Wheels	16" Dual, 8-Lug Steel					
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail					
Wiring	No Exposed Wiring					
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant					
Mud Flaps	Yes					
Decking	2" Pressure Treated Pine, Board Retainers					
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier					
Coupler Height	32.25 - 40.25		0			32.25 - 40.25
Deck Height	34					34
DIMENSIONS						
Overall Length	594	402				498
Deck Height	34					34
Coupler Height	32.25 - 40.25		0			32.25 - 40.25

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 34	102 x 36
Model #	N-FB34-230G	N-FB36-230G
CAPACITIES		
GVWR (lbs)	23000	
GAWR (lbs/axle)	10000	
Curb Weight	8130	8380
Payload	14870	14620
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	Gooseneck, High Strength Manufactured I-Beam	
Tongue Jack	Dual 12K, 2-Speed Landing Gear	
Frame	High Strength Manufactured I-Beam, Square Torque Tube	
Crossmembers	3" Steel Channel, 16" On-Center	
Beavertail	5' Cleated	
Ramp(s)	Fold Over Wedge, Spring Assist	
Integrated Step(s)	Side Steps	
Axle	(2) 10000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16" Dual, 8-Lug Steel	
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail	
Wiring	No Exposed Wiring	
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant	
Mud Flaps	Yes	
Decking	2" Pressure Treated Pine, Board Retainers	
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier	
Coupler Height	0	32.25 - 40.25
Deck Height		34
DIMENSIONS		
Overall Length		546
Deck Height		34
Coupler Height	0	32.25 - 40.25

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 24	102 x 26	102 x 28	102 x 30	102 x 32	102 x 34
Model #	N-FB24-259G	N-FB26-259G	N-FB28-259G	N-FB30-259G	N-FB32-259G	N-FB34-259G
CAPACITIES						
GVWR (lbs)	25900					
GAWR (lbs/axle)	12000					
Curb Weight	7280	7200	7780	8030	8280	8130
Payload	18620	18700	18120	17870	17620	17770
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Gooseneck, High Strength Manufactured I-Beam					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Frame	High Strength Manufactured I-Beam, Square Torque Tube					
Crossmembers	3" Steel Channel, 16" On-Center					
Beavertail	5' Cleated					
Ramp(s)	Fold Over Wedge, Spring Assist					
Integrated Step(s)	Side Steps					
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension					
Hubs	Oil Bath					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/80R16E 10-PLY					
Wheels	16" Dual, 8-Lug Steel					
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail					
Wiring	No Exposed Wiring					
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant					
Mud Flaps	Yes					
Decking	2" Pressure Treated Pine, Board Retainers					
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier					
Coupler Height	0					
DIMENSIONS						
Coupler Height	0					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 36	102 x 40
Model #	N-FB36-259G	N-FB40-259G
CAPACITIES		
GVWR (lbs)	25900	
GAWR (lbs/axle)	12000	
Curb Weight	8780	9280
Payload	17120	16620
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	Gooseneck, High Strength Manufactured I-Beam	
Tongue Jack	Dual 12K, 2-Speed Landing Gear	
Frame	High Strength Manufactured I-Beam, Square Torque Tube	
Crossmembers	3" Steel Channel, 16" On-Center	
Beavertail	5' Cleated	
Ramp(s)	Fold Over Wedge, Spring Assist	
Integrated Step(s)	Side Steps	
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16" Dual, 8-Lug Steel	
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail	
Wiring	No Exposed Wiring	
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant	
Mud Flaps	Yes	
Decking	2" Pressure Treated Pine, Board Retainers	
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier	
Coupler Height	0	
DIMENSIONS		
Coupler Height	0	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x 30	102 x 32	102 x 34	102 x 36	102 x 40
Model #	N-FB30-368G	N-FB32-368G	N-FB34-368G	N-FB36-368G	N-FB40-368G
CAPACITIES					
GVWR (lbs)	36800				
GAWR (lbs/axle)	16000				
Curb Weight	8330	8630	7975	8930	9580
Payload	28470	28170	28825	27870	27220
CHASSIS					
Coupler	3" Square Gooseneck				
Tongue	Gooseneck, High Strength Manufactured I-Beam				
Tongue Jack	Dual 12K, 2-Speed Landing Gear				
Frame	High Strength Manufactured I-Beam, Square Torque Tube				
Crossmembers	3" Steel Channel, 12" On-Center				
Beavertail	5' Cleated				
Ramp(s)	Fold Over Wedge, Spring Assist				
Integrated Step(s)	Side Steps				
Axle	(2) 16000 lb. Straight Brake, Hutch Spring Suspension				
Hubs	Oil Bath				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	215/75R17.5J 18-PLY				
Wheels	17.5" Dual, 8 on 275mm Steel				
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail				
Wiring	No Exposed Wiring				
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant				
Mud Flaps	Yes				
Decking	2" Pressure Treated Pine, Board Retainers				
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier				
Coupler Height	0				
DIMENSIONS					
Coupler Height	0				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.