



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE CAR HAULER RT 10K

	8.5 x 20		8.5 x 24		8.5 x 26		8.5 x 28		8.5 x 30	
Model #	H10120CRCH-100		H10124CRCH-100		H10126CRCH-100		H10128CRCH-100		H10130CRCH-100	
CAPACITIES										
GVWR (lbs)					9900					
GAWR (lbs/axle)					5200					
Curb Weight	3750		4060		4480				4690	
Payload	6150		5840		5420				5210	
CHASSIS										
Coupler	2-5/16" A-Frame, Posi-Lock									
Tongue	6" x 2" Steel Triple Tube									
Tongue Jack	7K Drop Leg, Set-Back									
Frame	6" x 2" Steel Tube									
Crossmembers	Steel Tube, 16" On-Center									
Roof Bows	Galvanized Steel Tube, 16" On-Center									
Wall Posts	Steel Tube, 16" On-Center									
Ramp(s)	400 Series with Assist and Integrated Transition									
Side Door	36" Wide Flush Lock, Aluminum Holdback									
Integrated Step(s)	Interior Recessed									
Axle	(2) 5200 lb. Torsion Brake									
Hubs	Easy Lube									
Undercoating	Rubberized									
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel									
Flooring	3/4" Engineered Wood									
Interior Walls	Engineered Wood									
Exterior Finish	.040" Aluminum									
Exterior Fastening	VHB Bonded (Screwless)									
Stone Guard	24" ATP									
Exterior Trim	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap									
Roof Cap	Custom Formed Fiberglass									
Roof	.030 Aluminum Sheet, Round Top									
Tires	ST225/75R15D 8-PLY									
Wheels	15", 6-Lug Aluminum									
Cargo Control	10' Surface Mounted E-Track, (4) E-Track Clips									
Vents	Posi-Vent									
Wiring	Enclosed in Conduit									
Interior Lights	(2) LED Dome Lights, Wall Mount									
Exterior Lights	Full LED, DOT Compliant									
Switches	(1) Dome Light, 12V									
Dovetail	4' Interior									
Height Rear Opening	76.5						76.5			
Width Rear Opening	95						95			
Deck Height	24						24			
Height Overall	106						106			
Deck Length	249		297				345			
Width Interior	98.5						98.5			
Width Between Fender	82						82			
Length Interior Box	249		297				345			
DIMENSIONS										
Overall Length	295		343				391			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 20	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
Deck Length	249	297		345	
Deck Width		98.5		98.5	
Deck Height		24		24	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE GOOSENECK CH 10K

	8.5 x 20	8.5 x 24	8.5 x 24	8.5 x 26	8.5 x 26	8.5 x 28
Model #	H10120CRCHGNV-100	H10124CRCHGN-100	H10124CRCHGNV-100	H10126CRCHGN-100	H10126CRCHGNV-100	H10128CRCHGNV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	5000		5330			5980
Payload	4900		4570			3920
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Full Tubular Steel Gooseneck					
Tongue Jack	Dual 12K Drop Leg					
Front Profile	V-Nose	Round	V-Nose	Round	V-Nose	
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 5200 lb. Torsion Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Stone Guard	Lower ATP Bulkhead					
Exterior Trim	Polished Cast Aluminum Roof Corners					
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Tires	ST225/75R15D 8-PLY					
Wheels	15", 6-Lug Aluminum					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening		74.5				
Width Rear Opening		95				
Coupler Height		35-43				
Deck Height		26				
Height Overall		108				
Deck Length		282				
Width Interior		98.5				
Width Between Fender		82.5				
Length Interior Box		282				
DIMENSIONS						
Overall Length		388				
Deck Length		282				
Deck Width		98.5				
Deck Height		26				
Coupler Height		35-43				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE CAR HAULER RT 14K

	8.5 x 20	8.5 x 20	8.5 x 22	8.5 x 22	8.5 x 24	8.5 x 24
Model #	H10120CRCH-140	H10120CRCHV-140	H10122CRCHV-140	H10122CRCH-140	H10124CRCH-140	H10124CRCHV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	4000	4200	4150		4275	4330
Payload	10000	9800	9850		9725	9670
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	7K Drop Leg, Set-Back					
Front Profile	Round	V-Nose		Round		V-Nose
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Integrated Step(s)	Interior Recessed					
Axle	(2) 7000 lb. Torsion Brake					
Hubs	Easy Lube					
Undercoating	Rubberized					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Stone Guard	24" ATP					
Exterior Trim	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap		1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners		1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Tires	ST235/80R16E 10-PLY					
Wheels	16", 8-Lug Aluminum					
Cargo Control	10' Surface Mounted E-Track, (4) E-Track Clips					
Vents	Posi-Vent					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening	76.5				76.5	
Width Rear Opening	95				95	
Deck Height	25				25	
Height Overall	107				107	
Deck Length	249				297	
Width Interior	99.5				100.5	
Width Between Fender	82				82	
Length Interior Box	249				297	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 20	8.5 x 20	8.5 x 22	8.5 x 22	8.5 x 24	8.5 x 24
DIMENSIONS						
Overall Length	331				343	
Deck Length	249				297	
Deck Width	99.5				100.5	
Deck Height	25				25	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 26	8.5 x 26	8.5 x 28	8.5 x 28	8.5 x 30	8.5 x 30
Model #	H10126CRCHV-140	H10126CRCH-140	H10128CRCHV-140	H10128CRCH-140	H10130CRCH-140	H10130CRCHV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	4450	5070			5000	
Payload	9550	8930			9000	
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	7K Drop Leg, Set-Back					
Front Profile	V-Nose	Round	V-Nose	Round	V-Nose	
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Integrated Step(s)	Interior Recessed					
Axle	(2) 7000 lb. Torsion Brake					
Hubs	Easy Lube					
Undercoating	Rubberized					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Stone Guard	24" ATP					
Exterior Trim	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners	1.5" Top Extrusion, 3" Bottom Extrusion, Brite Aluminum Corners, Brite Aluminum Nose Cap	
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Tires	ST235/80R16E 10-PLY					
Wheels	16", 8-Lug Aluminum					
Cargo Control	10' Surface Mounted E-Track, (4) E-Track Clips					
Vents	Posi-Vent					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening				76.5		
Width Rear Opening				95		
Deck Height				25		
Height Overall				107		
Deck Length				345		
Width Interior				101.5		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 26	8.5 x 26	8.5 x 28	8.5 x 28	8.5 x 30	8.5 x 30
Width Between Fender				82		
Length Interior Box				345		
DIMENSIONS						
Overall Length				391		
Deck Length				345		
Deck Width				101.5		
Deck Height				25		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE GOOSENECK CH 14K

	8.5 x 20	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 24	8.5 x 26
Model #	H10120CRCHGN-140	H10120CRCHGNV-140	H10122CRCHGNV-140	H10124CRCHGN-140	H10124CRCHGNV-140	H10126CRCHGN-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight		5400	5250	5500	5550	5965
Payload		8600	8750	8500	8450	8035
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Full Tubular Steel Gooseneck					
Tongue Jack	Dual 12K Drop Leg					
Front Profile	Round	V-Nose		Round	V-Nose	Round
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 7000 lb. Torsion Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Stone Guard	Lower ATP Bulkhead					
Exterior Trim	Polished Cast Aluminum Roof Corners					
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Tires	ST235/80R16E 10-PLY					
Wheels	16", 8-Lug Aluminum					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening	74.5			74.5		
Width Rear Opening	95			95		
Coupler Height	35-43			35-43		
Deck Height	26			26		
Height Overall	107			109		
Deck Length	234			282		
Width Interior	99.5			100.5		
Width Between Fender	82.5			82.5		
Length Interior Box	234			282		
DIMENSIONS						
Overall Length	340			388		
Deck Length	234			282		
Deck Width	99.5			100.5		
Deck Height	26			26		
Coupler Height	35-43			35-43		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 26	8.5 x 28	8.5 x 28	8.5 x 30	8.5 x 30	8.5 x 32
Model #	H10126CRCHGNV-140	H10128CRCHGN-140	H10128CRCHGNV-140	H10130CRCHGN-140	H10130CRCHGNV-140	H10132CRCHGNV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight	5965	5870			5950	
Payload	8035	8130			8050	
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Full Tubular Steel Gooseneck					
Tongue Jack	Dual 12K Drop Leg					
Front Profile	V-Nose	Round	V-Nose	Round	V-Nose	
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 7000 lb. Torsion Brake					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Stone Guard	Lower ATP Bulkhead					
Exterior Trim	Polished Cast Aluminum Roof Corners					
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Tires	ST235/80R16E 10-PLY					
Wheels	16", 8-Lug Aluminum					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening		74.5				
Width Rear Opening		95				
Coupler Height		35-43				
Deck Height		26				
Height Overall		109				
Deck Length		330				
Width Interior		101.5				
Width Between Fender		82.5				
Length Interior Box		330				
DIMENSIONS						
Overall Length		436				
Deck Length		330				
Deck Width		101.5				
Deck Height		26				
Coupler Height		35-43				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE CAR HAULER RT 16K

	8.5 x 20	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 24	8.5 x 26
Model #	H10120CRCH-160	H10120CRCHV-160	H10122CRCHV-160	H10124CRCH-160	H10124CRCHV-160	H10126CRCHV-160
CAPACITIES						
GVWR (lbs)	16000					
GAWR (lbs/axle)	8000					
Curb Weight	5040					
Payload	10960					
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	7K Drop Leg, Set-Back					
Front Profile	Round	V-Nose		Round	V-Nose	
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 8000 lb. Torsion Brake					
Hubs	Oil Bath					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Stone Guard	24" ATP					
Exterior Trim	Polished Cast Aluminum Roof Corners					
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Wheels	17.5", 8-Lug Steel					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening	76.5					
Width Rear Opening	95					
Deck Height	25					
Height Overall	107					
Deck Length	249					
Width Interior	99.5					
Width Between Fender	82					
Length Interior Box	249					
DIMENSIONS						
Overall Length	331					
Deck Length	249					
Deck Width	99.5					
Deck Height	25					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 28	
Model #	H10128CRCHV-160
CAPACITIES	
GVWR (lbs)	16000
GAWR (lbs/axle)	8000
Curb Weight	4800
Payload	11200
CHASSIS	
Coupler	2-5/16" Adjustable
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	7K Drop Leg, Set-Back
Front Profile	V-Nose
Frame	6" x 2" Steel Tube
Crossmembers	Steel Tube, 16" On-Center
Roof Bows	Galvanized Steel Tube, 16" On-Center
Wall Posts	Steel Tube, 16" On-Center
Ramp(s)	400 Series with Assist and Integrated Transition
Side Door	36" Wide Flush Lock, Aluminum Holdback
Axle	(2) 8000 lb. Torsion Brake
Hubs	Oil Bath
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Aluminum H-Channel Wall Transitions
Exterior Finish	.040" Aluminum
Stone Guard	24" ATP
Exterior Trim	Polished Cast Aluminum Roof Corners
Roof Cap	Custom Formed Fiberglass
Roof	.030 Aluminum Sheet, Round Top
Wheels	17.5", 8-Lug Steel
Wiring	Enclosed in Conduit
Interior Lights	(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Dovetail	4' Interior

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE GOOSENECK CH 16K

	8.5 x 20	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 24	8.5 x 26
Model #	H10120CRCHGNV-160	H10120CRCHGN-160	H10122CRCHGNV-160	H10124CRCHGN-160	H10124CRCHGNV-160	H10126CRCHGNV-160
CAPACITIES						
GVWR (lbs)	16000					
GAWR (lbs/axle)	8000					
Curb Weight	7150					
Payload	8850					
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Full Tubular Steel Gooseneck					
Tongue Jack	Dual 12K Drop Leg					
Front Profile	V-Nose	Round	V-Nose	Round	V-Nose	
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Ramp(s)	400 Series with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 8000 lb. Torsion Brake					
Hubs	Oil Bath					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.040" Aluminum					
Stone Guard	Lower ATP Bulkhead					
Exterior Trim	Polished Cast Aluminum Roof Corners					
Roof Cap	Custom Formed Fiberglass					
Roof	.030 Aluminum Sheet, Round Top					
Wheels	17.5", 8-Lug Steel					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening				74.5		
Width Rear Opening				95		
Coupler Height				35-43		
Deck Height				26		
Height Overall				109		
Deck Length				282		
Width Interior				104.5		
Width Between Fender				82.5		
Length Interior Box				282		
DIMENSIONS						
Overall Length				388		
Deck Length				282		
Deck Width				104.5		
Deck Height				26		
Coupler Height				35-43		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 28	8.5 x 28	8.5 x 30	8.5 x 30	8.5 x 32
Model #	H10128CRCHGN-160	H10128CRCHGNV-160	H10130CRCHGN-160	H10130CRCHGNV-160	H10132CRCHGNV-160
CAPACITIES					
GVWR (lbs)	16000				
GAWR (lbs/axle)	8000				
Curb Weight				6430	
Payload				9570	
CHASSIS					
Coupler	2-5/16" Adjustable Gooseneck				
Tongue	Full Tubular Steel Gooseneck				
Tongue Jack	Dual 12K Drop Leg				
Front Profile	Round	V-Nose	Round	V-Nose	
Frame	6" x 2" Steel Tube				
Crossmembers	Steel Tube, 16" On-Center				
Roof Bows	Galvanized Steel Tube, 16" On-Center				
Wall Posts	Steel Tube, 16" On-Center				
Ramp(s)	400 Series with Assist and Integrated Transition				
Side Door	36" Wide Flush Lock, Aluminum Holdback				
Axle	(2) 8000 lb. Torsion Brake				
Hubs	Oil Bath				
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel				
Flooring	3/4" Engineered Wood				
Interior Walls	Engineered Wood				
Interior Trim	Aluminum H-Channel Wall Transitions				
Exterior Finish	.040" Aluminum				
Stone Guard	Lower ATP Bulkhead				
Exterior Trim	Polished Cast Aluminum Roof Corners				
Roof Cap	Custom Formed Fiberglass				
Roof	.030 Aluminum Sheet, Round Top				
Wheels	17.5", 8-Lug Steel				
Wiring	Enclosed in Conduit				
Interior Lights	(2) LED Dome Lights, Wall Mount				
Exterior Lights	Full LED, DOT Compliant				
Dovetail	4' Interior				
Height Rear Opening	74.5				
Width Rear Opening	95				
Coupler Height	35-43				
Deck Height	26				
Height Overall	109				
Deck Length	330				
Width Interior	105.5				
Width Between Fender	82.5				
Length Interior Box	330				
DIMENSIONS					
Overall Length	436				
Deck Length	330				
Deck Width	105.5				
Deck Height	26				
Coupler Height	35-43				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE CAR HAULER RT 21K

	8.5 x 26	101 x 32	8.5 x 32
Model #	H10126CRCH-210	H10132CRCH-210	H10132CRCHV-210
CAPACITIES			
GVWR (lbs)	21000		
GAWR (lbs/axle)	7000		
CHASSIS			
Coupler	2-5/16" Adjustable		
Tongue	8" x 2" Steel Triple Tube	6" x 2" Steel Triple Tube	
Tongue Jack	7K Drop Leg, Set-Back		
Front Profile	Round		
Frame	8" x 2" Steel Tube		
Crossmembers	Steel Tube, 16" On-Center		
Roof Bows	Galvanized Steel Tube, 16" On-Center		
Wall Posts	Steel Tube, 16" On-Center		
Ramp(s)	400 Series with Assist and Integrated Transition		
Side Door	36" Wide Flush Lock, Aluminum Holdback	36" Wide Flush Lock	
Axle	(3) 7000 lb. Torsion Brake		
Hubs	Easy Lube		
Flooring	3/4" Engineered Wood		
Interior Walls	Engineered Wood		
Interior Trim	Aluminum H-Channel Wall Transitions		
Exterior Finish	.040" Aluminum		
Stone Guard	24" ATP		
Exterior Trim	Polished Cast Aluminum Roof Corners		
Roof Cap	Custom Formed Fiberglass		
Roof	.030 Aluminum Sheet, Round Top		
Tires	ST235/80R16E 10-PLY		
Wheels	16", 8-Lug Aluminum		
Wiring	Enclosed in Conduit		
Interior Lights	(2) LED Dome Lights, Wall Mount		
Exterior Lights	Full LED, DOT Compliant		
Dovetail	4' Interior		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE GOOSENECK CH 21K

8.5 x 26	
Model #	H10126CRCHGNV-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Coupler	2-5/16" Adjustable Gooseneck
Tongue	Full Tubular Steel Gooseneck
Front Profile	V-Nose
Frame	8" x 2" Steel Tube
Crossmembers	Steel Tube, 16" On-Center
Roof Bows	Galvanized Steel Tube, 16" On-Center
Wall Posts	Steel Tube, 16" On-Center
Ramp(s)	400 Series with Assist and Integrated Transition
Side Door	36" Wide Flush Lock, Aluminum Holdback
Axle	(3) 7000 lb. Torsion Brake
Hubs	Easy Lube
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Aluminum H-Channel Wall Transitions
Exterior Finish	.040" Aluminum
Stone Guard	Lower ATP Bulkhead
Exterior Trim	Polished Cast Aluminum Roof Corners
Roof Cap	Custom Formed Fiberglass
Roof	.030 Aluminum Sheet, Round Top
Tires	ST235/80R16E 10-PLY
Wheels	16", 8-Lug Aluminum
Wiring	Enclosed in Conduit
Interior Lights	(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Dovetail	4' Interior

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE CAR HAULER RT 24K

101 x 32	
Model #	H10132CRCH-240
CAPACITIES	
GVWR (lbs)	6940
GAWR (lbs/axle)	8000
CHASSIS	
Coupler	2-5/16" Adjustable, 25k Rated
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	7K Drop Leg, Set-Back
Frame	8" x 2" Steel Tube
Crossmembers	Steel Tube, 16" On-Center
Roof Bows	Galvanized Steel Tube, 16" On-Center
Wall Posts	Steel Tube, 16" On-Center
Side Door	36" Wide Flush Lock, Aluminum Holdback
Axle	(3) 8000 lb. Torsion Brake
Hubs	Oil Bath
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Exterior Finish	.040" Aluminum
Exterior Trim	Polished Cast Aluminum Roof Corners
Roof	.030 Aluminum Sheet, Round Top
Wheels	17.5", 8-Lug Steel
Wiring	Enclosed in Conduit
Interior Lights	(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Dovetail	4' Interior

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED TOPLINE GOOSENECK CH 24K

8.5 x 28		8.5 x 28
Model #	H10128CRCHGN-240	H10128CRCHGNV-240
CAPACITIES		
GVWR (lbs)	24000	
GAWR (lbs/axle)	8000	
CHASSIS		
Coupler	2-5/16" Adjustable Gooseneck	
Tongue	Full Tubular Steel Gooseneck	
Tongue Jack	Dual 12K Drop Leg	
Front Profile	Round	V-Nose
Frame	8" x 2" Steel Tube	
Crossmembers	Steel Tube, 16" On-Center	
Roof Bows	Galvanized Steel Tube, 16" On-Center	
Wall Posts	Steel Tube, 16" On-Center	
Ramp(s)	400 Series with Assist and Integrated Transition	
Side Door	36" Wide Flush Lock, Aluminum Holdback	
Axle	(3) 8000 lb. Torsion Brake	
Hubs	Oil Bath	
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel	
Flooring	3/4" Engineered Wood	
Interior Walls	Engineered Wood	
Interior Trim	Aluminum H-Channel Wall Transitions	
Exterior Finish	.040" Aluminum	
Stone Guard	Lower ATP Bulkhead	
Exterior Trim	Polished Cast Aluminum Roof Corners	
Roof Cap	Custom Formed Fiberglass	
Roof	.030 Aluminum Sheet, Round Top	
Wheels	17.5", 8-Lug Steel	
Wiring	Enclosed in Conduit	
Interior Lights	(2) LED Dome Lights, Wall Mount	
Exterior Lights	Full LED, DOT Compliant	
Dovetail	4' Interior	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.