# UE

UF07

2" X 3" Angle Frame Utility Trailer

## STANDARD FEATURES



- 7,000 lb GVWR
- 3,500 lb GAWR
- 4" Channel Tongue
- 2" X 3" X 3/16" Angle Frame
- 2" x 3" Angle, 24" OC Cross-members
- (2) 3,500 lb DEXTER \*1 Electric Brake/1 Idler
- Multi-Leaf Spring Suspension
- 15" 5-Hole Wheels
- ST205/75 R15 LRC Tires
- (1) 2,000 lb Top-wind Jack
- 2" A-Frame Coupler
- Straight Deck With Board Slides
- Weld-On 2" x 2" Square Tube Side Rails
- Smooth Plate Fenders (weld-on)
- (4) U-Hooks
- Treated Pine Floor
- (2) Safety Chains
- LED Lighting
- 16 Ga. 4-Way Double-Insulated Harness w/4-way RV Plug & Front Polar Cord
- •Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black Polyester TGIC Gloss Powder Topcoat With PRIMER STANDARD

Standard features shown are based on the UE07 model. Standard features vary by model. Axles available with electric or hydraulic brakes. 2ft dove tail available on 12ft+ models only.



## **AXLE OPTIONS**

3,500 Lb Dexter 2 Electric/Spring (FSA)

# **COUPLER OPTIONS**

2" or 2-5/16" Adjustable Coupler 2" or 2-5/16" A-Frame Coupler

# TAIL. GATES & RAMPS

2' Dove Tail 3', 4' or 5' Fold-up Gate

3', 4', or 5' Split Fold-up Gate

3', 4', or 5' HD Fold-up Gate

3', 4', or 5' Fold-In Gate

Front-Mount Fold-Up Gate

# TAIL. GATES & RAMPS

Spring Assist For Gate Side-Mount Gate Bi-Fold Gate Side Rail Ramps

## POPULAR OPTIONS

ST225/75 R15 LRD Tires Rough Oak Floor Douglas Fir Floor BlackwoodLumber (classic or PRO) Steel Diamond Plate Floor 12" or 16" On-Center Cross-members Steel Diamond Plate Fenders **Aluminum Fenders** 7K Drop-Leg Jack

# **POPULAR OPTIONS**

LOAD TRAIL

Stock photo. May be shown with additional options.

5K Swivel Jack

3" D-rings

Angle Iron Side Rails (weld-on or removable) Pipe-top Side Rails (weld-on or removable) Square Tube Side Rails (weld-on or removable)

16" Solid Metal Sides

16" Expanded Metal Sides

**Tongue-Mount Toolbox** 

Expanded Metal Tool Cage

**Trimmer Rack** 

Rear Support Stands (Tube or Jacks)

**Additional Stake Pockets** 

Spare Tire & Mount (eld-on or removable)

**GVWR** 

7.000 lbs

**LENGTHS** 10 - 18 ft

**WIDTHS** 60 - 83"

**DECK HEIGHT** 

19"

**BASE WEIGHT** 

1.045 - 1.812 lbs

G.A.W.R.

3.500 lbs/Axle