

MORITZ
FDH DT SERIES
Pintle Ring

MORITZ

The Lord is my strength and song, And He has become my salvation. Psalm 118:14 KJV

BUILT
TO LAST
PERFORMANCE



DLH SERIES



ELH AR SERIES



ELH GT SERIES



ELH HT SERIES



FDH DT SERIES



FDH HT SERIES



TBA SERIES



TB SERIES

STANDARD FEATURES

tongue	HD I-beam tongue
nose plate	one piece formed plate
chassis	torque chassis (torque resistant cross tubes)
	cambered main beams
	pierced main beams
dovetail & ramps	steel dozer ramps
	adjustable spring tension
	12-1/2 degree loading angle
	increased ground clearance dovetail
	HD fade away hinge system
	ramp hold down latch (to deck)
	vertical ramp bars
	5' self cleaning dovetail
deck	low profile - 33" high
	102" wide
	cross sills - 16" center
	(24" center 15,900 gvw)
	side rails - 6"@8.2 lb/ft channel
	stake pockets - 3" x 1/4"
	rub rail - 2" x 5/16"
	extra running lights
	pipe spools
tool box	extra large steel diamond plate
	light inside tool box
	addition storage infront of toolbox
suspension	7k & 8k axles - torsion
	10k & 12k axles - spring
brakes	electric
tires & wheels	ST235/80 R16 LRE
jack	dual 15k
pinle ring	21 ton
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty (see warranty for details)	

prototype photos - some details may change on production version



OPTIONS

under body tool box	disc brakes with electric over hydraulic brakes
dual two speed jacks	solar charger (for use with hydraulic jacks)
dual hydraulic jacks	spare tire & wheel
winch - 12000 lb	ultimate ramps
electric over hydraulic brakes (drum brakes)	COLORS
	black - red - charcoal

SPECIFICATIONS BY GVWR

GVWR	Main Beams	Axles	Tires & Wheels
15900	12" @ 14 lb/ft	2 - 7k torsion	ST235/80R 16 LRE single
17900	12" @ 14 lb/ft	2 - 8k torsion	LT215/75R 17.5 LRH single
22900	14" @ 22 lb/ft	2 - 10k spring	ST235/80R 16 LRE dual
25900	14" @ 22 lb/ft	2 - 12k spring	ST235/80R 16 LRE dual