

EDH AR
SERIES

MORITZ

That if thou shalt confess with thy mouth the Lord Jesus, and shalt believe in thine heart that God hath raised him from the dead, thou shalt be saved. Romans 10:9 KJV



BUILT
TO LAST
PERFORMANCE



DLH SERIES



ELH AR SERIES



ELH GT SERIES



ELH HT SERIES



FH SERIES



FH+10 SERIES



TBA SERIES



TB SERIES



EDH AR - 20+4 16000 LB GVWR

(16000 lb GVWR built with two 8000 lb axles)

- Heavy Duty 4" Aluminum Channel Ramps (standard)
- Aluminum Tool Box (standard)
- 17.5" Tires & Wheels



Step to
Access Deck



Aluminum
Tool Box



Heavy Duty 4" Channel Aluminum Ramps
These Ramps Tested Stronger Than our 3" Steel Channel
Ramps on our Previous Model

EDH - 18 140000 LB GVWR
(140000 lb GVWR built with two 70000 lb axles)
• EDH No Tail (Optional)



Heavy Duty
4 Bolt Adjustable
Coupler



Optional
Traction Angles
Across Tail



Optional
Under Body
Tool Box



Optional
Hydraulic Jack

STANDARD SPECIFICATIONS

deck height	33"
deck width	100"
frame	8" I-beam
stake pockets	3" x 1/4" formed bar
tool box	aluminum diamond plate
ramps	aluminum 4" channel
fenders	3/16" steel diamond plate
suspension	rubber ride (low maintenance)
brakes	electric (all wheels)
tires & wheels	
	12000 lb & 14000 lb GVWR - 16" 10 ply rated 8 bolt
	16000 lb GVWR - 17.5" 16 ply rated 8 bolt
jack	12000 lb
coupler	2-5/16" adjustable (4 bolt)
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty (see warranty for details)	

OPTIONS

under body tool box	
hydraulic jack	
pintle ring	
split mesh gates (made from steel)	
pallet fork holder	
traction angles across tail	
pipe spools	
solar panel with hydraulic jack	
spare tire & wheel	
COLORS	black - red - charcoal

FRAME SPECIFICATIONS

frame & tongue		cross members		fenders	
8" I-beam		3" channel (12k & 14K 24" Center) (16k 16" centers)		3/16" steel diamond plate	
18' Bumper Pull		20' Bumper Pull		22' Bumper Pull	
GVWR	beam specs	GVWR	beam specs	GVWR	beam specs
12000	8" @ 10 lb/ft	12000	8" @ 10 lb/ft	12000	8" @ 15 lb/ft
14000	8" @ 10 lb/ft	14000	8" @ 10 lb/ft	14000	8" @ 15 lb/ft
16000	8" @ 15 lb/ft	16000	8" @ 15 lb/ft	16000	8" @ 15 lb/ft

AXLE SPECIFICATIONS (rubber ride suspension)

GVWR		axles	
12000 lb		6000 lb with electric brakes & easy lube spindles	
14000 lb		7000 lb with electric brakes & easy lube spindles	
16000 lb		8000 lb with electric brakes & easy lube spindles	

WEIGHT SPECIFICATIONS

Bumper Pull (Tail)

Length	12000 GVWR	14000 GVWR	16000 GVWR	12000 GVWR	14000 GVWR	16000 GVWR
18'	3560 lbs	3580 lbs	3990 lbs	2860 lbs	2880 lbs	3350 lbs
20'	3955 lbs	3975 lbs	4520 lbs	3270 lbs	3340 lbs	3810 lbs
22'	N/A	4500 lbs	4970 lbs	N/A	3800 lbs	4270 lbs
24'	N/A	4950 lbs	5420 lbs	N/A	4260 lbs	4720 lbs

Bumper Pull (No Tail)

Length	12000 GVWR	14000 GVWR	16000 GVWR	12000 GVWR	14000 GVWR	16000 GVWR
18'	3560 lbs	3580 lbs	3990 lbs	2860 lbs	2880 lbs	3350 lbs
20'	3955 lbs	3975 lbs	4520 lbs	3270 lbs	3340 lbs	3810 lbs
22'	N/A	4500 lbs	4970 lbs	N/A	3800 lbs	4270 lbs
24'	N/A	4950 lbs	5420 lbs	N/A	4260 lbs	4720 lbs



MORITZ INTERNATIONAL, INC.
665 North Main Street, Mansfield, Ohio 44902
Phone (419)526-5222 www.moritzint.com