

MORITZ

ELH AR

SERIES

TRAILERS & TRUCK BODIES



Trust in the LORD with all thine heart; and lean not unto thine own understanding. Proverbs 3:5 KJV

BUILT
TO LAST
PERFORMANCE

TBA SERIES




DLH SERIES



ELH GT SERIES



FH SERIES




FH+10 SERIES



UDC SERIES



LRA SERIES



CR SERIES





ELBH - 18 AR 14000 LB GVWR

- Heavy Duty 4" Aluminum Channel Ramps (*standard*)
- Aluminum Tool Box (*standard*)



Cold Formed
8" I Beam



Aluminum
Tool Box



Heavy Duty 4" Channel Aluminum Ramps
These Ramps Tested Stronger Than our 3" Steel
Channel Ramps on our Previous Model



Tie Down
Between Fenders
(flush w/deck & fenders)



ELBH - 20 AR 16000 LB GVWR

(16000 lb GVWR built with two 8000 lb axles)


- 17.5" Tires & Wheels
- Heavy Duty 4" Aluminum Channel Ramps *(standard)*
- Aluminum Tool Box *(standard)*
- Fender Tool Box *(optional)*



Heavy Duty
4" x 1/4" Bar
Stake Pockets



Step To
Access Deck



Heavy Duty
4 Bolt Adjustable
Coupler



Optional
Fender Tool Boxes
(ratchet boomer storage)



Optional
Hydraulic Jack

STANDARD SPECIFICATIONS

deck height	22" to 23"
between fenders	81-1/2"
frame	8" cold formed I-beam
stake pockets	4" x 1/4" formed bar
tool box	aluminum diamond plate
ramps	aluminum 4" channel
fenders	1/8" steel diamond plate
suspension	rubber ride (low maintenance)
brakes	electric (all wheels)
tires & wheels	
	12000 lb & 14000 lb GVWR - 16" 10 ply rated 8 bolt
	16000 lb GVWR - 17.5" 16 ply rated 8 bolt
jack	12000 lb
coupler	2-5/16" adjustable (4 bolt)
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty (see warranty for details)	

OPTIONS

fenders with built in tool boxes
hydraulic jack
pintle ring
split mesh gates (made from steel)
pallet fork holder
aluminum wheels
spare tire & wheel

COLORS

black - red - charcoal

FRAME SPECIFICATIONS

frame & tongue	cross members	fenders
one piece cold formed 8" I-beam	3" channel on 16" centers	1/8" steel diamond plate

AXLE SPECIFICATIONS (*rubber ride suspension*)

GVWR	axles
12000 lb	6000 lb with electric brakes & easy lube spindles
14000 lb	7000 lb with electric brakes & easy lube spindles
16000 lb	8000 lb with electric brakes & oil bath hubs

WEIGHT SPECIFICATIONS

Bumper Pull

Length	12000 GVWR	14000 GVWR	16000 GVWR	Gooseneck 12000 GVWR	14000 GVWR	16000 GVWR
18'	2900 lbs	2920 lbs	3740 lbs	3680 lbs	3700 lbs	4520 lbs
20'	3060 lbs	3080 lbs	3900 lbs	3840 lbs	3860 lbs	4680 lbs
22'	3500 lbs	3520 lbs	4080 lbs	4280 lbs	4300 lbs	4860 lbs

