



Specification Page

ALUMINUM SPEED LOADER® TILT

CAR HAULER



	MXA - Manual Tilt				EXA - Electric Tilt			
	82" x 18' (7K)	82" x 20' (7K)	82" x 22' (10K)	82" x 24' (10K)	82" x 18' (7K)	82" x 20' (7K)	82" x 22' (10K)	82" x 24' (10K)
Model	H8218MXA-070	H8220MXA-070	H8222MXA-100	H8224MXA-100	H8218EXA-070	H8220EXA-070	H8222EXA-100	H8224EXA-100
GAWR (lb./axle)	3500	3500	5200	5200	3500	3500	5200	5200
GVWR (lb.)	7000	7000	9900	9900	7000	7000	9900	9900
Curb Weight (lb.)	1590	1670	2170	2270	1670	1750	2250	2350
Payload Capacity (lb.)	5410	5330	7730	7630	5330	5250	7650	7550
Frame Construction	6" Channel	6" Channel	8" Channel	8" Channel	6" Channel	6" Channel	8" Channel	8" Channel
Crossmembers	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel	3" Channel
Tongue Construction	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel	6" Channel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	7K Rated Drop Leg, Set-Back				7K Rated Drop Leg, Set-Back			
Axle Type	Leaf Spring Brake				Leaf Spring Brake			
Brakes	4-Wheel Electric				4-Wheel Electric			
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST225/75R15 'D'	ST225/75R15 'D'	ST205/75R15 'C'	ST205/75R15 'C'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 6 on 5.5	15", 6 on 5.5	15", 5 on 4.5	15", 5 on 4.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine				Pressure Treated Pine			
Dovetail	Reverse Taper Cut Dovetail				Reverse Taper Cut Dovetail			
Ramp Style	-	-	-	-	-	-	-	-
Ramp Length x Width	-	-	-	-	-	-	-	-
Load Capacity (lb.)	-	-	-	-	-	-	-	-
Overall Length	23'-4"	25'-4"	27'-4"	29'-4"	23'-4"	25'-4"	27'-4"	29'-4"
Overall Width	102"	102"	102"	102"	102"	102"	102"	102"
Overall Height	34"	34"	36"	36"	34"	34"	36"	36"
Deck Height	24"	24"	26"	26"	24"	24"	26"	26"
Deck Length	18'-2"	20'-2"	22'-2"	24'-2"	18'-2"	20'-2"	22'-2"	24'-2"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"
Load Angle	14 Deg.	12 Deg.	11 Deg.	9 Deg.	14 Deg.	12 Deg.	11 Deg.	9 Deg.

STANDARD FEATURES

Aluminum Channel Frame 3" Aluminum Channel Crossmembers 6" Aluminum Channel Tongue Aluminum Tube Bulkhead 2 5/16" A-Frame Posi-Lock Coupler Dual Safety Chain and Hooks	7K Drop Leg Jack, Set-Back 2x8 Treated, #1 Grade Wood Decking Front and Rear Board Caps Reverse Taper Cut Dovetail Removable Aluminum Teardrop Fenders Spring Brake Suspension with Easy Lube Hubs	Sealed Wiring Harness Full LED, DOT Compliant Lighting Multiple Stake Pockets and Rub Rails Hydraulic Jack (MXA) Manual Hand Operated Hydraulic Jack (EXA) Power Pack Electric - Battery and Pump Box Included
--	---	---