

STANDARD FEATURES

gooseneck	proprietary HD gooseneck design
winch mount	standard on all goosenecks
chassis	torque chassis <i>(torque resistant cross tubes)</i>
	cambered main beams
	pierced main beams
dovetail & ramps	aluminum wedge ramps
	adjustable spring tension
	12-1/2 degree loading angle
	increased ground clearance dovetail
	HD fade away hinge system
	ramp hold down latch <i>(to deck)</i>
	vertical ramp bars
	5' self cleaning dovetail
	low profile - 33" high
	102" wide
deck	cross sills - 16" center <i>(24" center 15,900 gvw)</i>
	side rails - 6"@8.2 lb/ft channel
	stake pockets - 3" x 1/4"
	rub rail - 2" x 5/16"
	extra running lights
tool box	pipe spools
	extra large steel diamond plate
	light inside tool box
	chain rack inside tool box
suspension	7k & 8k axles - torsion
	10k & 12k axles - spring
brakes	electric
tires & wheels	ST235/80 R16 LRE
jack	dual 12k
coupler	2-5/16" adjustable
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
2 year limited warranty <i>(see warranty for details)</i>	

prototype photos - some details may change on production version



OPTIONS

under body tool box	disc brakes with electric over hydraulic brakes
dual two speed jacks	solar charger <i>(for use with hydraulic jacks)</i>
dual hydraulic jacks	spare tire & wheel
winch - 12000 lb	dozer ramps <i>(HD steel ramps)</i>
electric over hydraulic brakes <i>(drum brakes)</i>	COLORS black - red - charcoal

SPECIFICATIONS BY GVWR

GVWR	Main Beams	Axles	Tires & Wheels
15900	12" @ 14 lb/ft	2 - 7k torsion	ST235/80R 16 LRE single
17900	12" @ 14 lb/ft	2 - 8k torsion	LT215/75R 17.5 LRH single
22900	14" @ 22 lb/ft	2 - 10k spring	ST235/80R 16 LRE dual
25900	14" @ 22 lb/ft	2 - 12k spring	ST235/80R 16 LRE dual