



Specification Page

ALUMINUM RAIL SIDE UTILITY - SINGLE AXLE

UTILITY TRAILERS



	60" x 8' (3K)	60" x 10' (3K)	66" x 10' (3K)	66" x 12' (3K)	76" x 10' (3K)	76" x 12' (3K)	82" x 12' (3K)	82" x 14' (3K)
Model	H6008RSA-030	H6010RSA-030	H6610RSA-030	H6612RSA-030	H7610RSA-030	H7612RSA-030	H8212RSA-030	H8214RSA-030
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	650	690	810	890	830	920	980	1050
Payload Capacity (lb.)	2340	2300	2180	2100	2160	2070	2010	1940
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube	4" Tube
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel	1K Rated Swivel
Axle Type	Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler		Leaf Spring Idler	
Brakes	-	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong	4-Prong
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine		Pressure Treated Pine	
Ramp Style	Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate		Bi-fold Ramp Gate	
Ramp Length x Width	54 1/2" x 57"	54 1/2" x 57"	54 1/2" x 63"	54 1/2" x 63"	54 1/2" x 73"	54 1/2" x 73"	54 1/2" x 79"	54 1/2" x 79"
Load Capacity (lb.)	2200	2200	2200	2200	2200	2200	2200	2200
Overall Length	11'-10"	13'-10"	13'-9"	15'-9"	14'-4"	16'-4"	16'-9"	18'-9"
Overall Width	78 1/4"	78 1/4"	84 1/4"	84 1/4"	94 1/4"	94 1/4"	100 1/4"	100 1/4"
Overall Height	49"	49"	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	8'-0"	10'-0"	10'-0"	12'-0"	10'-0"	12'-0"	12'-0"	14'-0"
Deck Width	60 1/4"	60 1/4"	66 1/4"	66 1/4"	76 1/4"	76 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

Aluminum Angle Extrusion Frame Aluminum Angle Crossmembers 2" x 1-1/2" Aluminum Extrusion Tube Uprights 2" x 2" Aluminum Tube Top Rail 4" Aluminum Tube Tongue A-Frame Posi-Lock Coupler	Dual Safety Chains and Hooks 1K Rated Swivel Jack with Caster Wheel 2x8 Treated, #1 Grade Wood Decking Front and Rear End Caps 54" Bi-fold Gate Aluminum Fenders with Backs	Spring Suspension with Easy Lube Hubs Radial Tires on Aluminum Wheels Sealed Wiring Harness Full LED, DOT Compliant Lighting Aluminum Stake Pockets
---	--	---