

## 3500 Standards

2 - 5/16" Coupler Spring Axle with 4" Drop Radial Tires on Gray Wheels **Rubberized Armor-Coated Tongue and Bumpers Automotive Grade Undercoating Painted Roof Bows Flat Front Tube Main Rails** 16" On-Center Floor Crossmembers 16" On- Center Wall Posts and **Tube Roof Bows** (4) Recessed 5,000 lb. D-Rings w/ Ramp Door

Ramp Door w/ Flap or Double Rear Doors 36" Solid RV Side Door w/ Barlock 3/4" High-Performance Floor 3/8" Plywood Walls w/ 3/8" Plywood Trim **One-Piece Aluminum Roof** 

LED Loading Light w/ Switch Over Rear

**LED Porch Light by Side Door Brite Front Corners Brite Wrap Between Front Cast Corners Brite Rear Hoop Aluminum Side Wall Vents** .030 Exterior Metal Semi-Screwless Exterior w/ **Color Matching Screws on Seams** 24" Tall .045 Stoneguard .063 Smooth Fenders 3" Aluminum Top Trim 3" Aluminum Bottom Trim **Aluminum Door Holdbacks** 7-Way Connector w/ Backup Tail Breakaway Battery, Box, and Switch for All Brake Axles (2) LED Dome lights w/ Switch **All LED Lighting** 3-Year Limited Warranty

**SHOWN WITH: HD CONTRACTOR PACKAGE EXTENDED TONGUE 7K JACK REAR SPOILER OVER RAMP** 

Scan to learn more!





## 



notice.	ge without i	Specs, are subject to change without notice	are subje		*With Beaver Tail	*With I	<sup>1</sup> Main Floor Length
5,990 lbs.	6,950 lbs.	3,650 lbs.	4,320 lbs.	4,570 lbs.	4,580 lbs.	4,700 lbs.	Payload Capacity
4,000 lbs.	3,400 lbs.	3,250 lbs.	2,680 lbs.	2,430 lbs.	2,420 lbs.	2,300 lbs.	Curb Weight
500 lbs.	450 lbs.	400 lbs.	180 lbs.	170 lbs.	230 lbs.	200 lbs.	Hitch Weight
9,990 lbs.	9,990 lbs	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs	7,000 lbs.	GVWR
							Weights
Electric	Electric	Electric	Electric	Electric	Electric	Electric	Brakes
4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	4" Drop	Axle Type
Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Axles
6-Bolt/5.5	6-Bolt/5.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	5-Bolt/4.5	Wheel Bolt Pattern
D	D	C	C	C	C	C	Load Range
ST225/ 75R15	ST225/ 75R15	ST205/ 75R15	ST205/ 75R15	ST205/ 75R15	ST205/ 75R15	ST205/ 75R15	Tire Size
25/16"	25/16"	25/16"	25/16"	25/16"	25/16"	25/16"	Hitch Ball Size
20"	20"	19"	19"	19"	19"	19"	Top of Hitch Ball
							Hitch, Tires, Axles
91"	91"	91"	81"	81"	75"	75"	Dist. Between Cables
92"	92"	92"	82"	82"	76"	76"	Rear Opening Width
75"*	75"*	75"*	72"	72"	72"	72"	Rear Opening Height
21"	21"	20"	20"	20"	20"	20"	Platform Height
78"	78"	78"	78"	78"	72"	72"	Interior Height
96"	96"	96"	86"	86"	80"	80"	Interior Width
24'	20'	20'	16'	14'	16'	14'	Interior Length <sup>1</sup>
101"	101"	101"	101"	101"	91"	91"	Overall Height
102"	102"	102"	102"	102"	102"	102"	Overall Width
28'	24'	24'	20'	18'	20'	18'	Overall Length
							Dimensions
8.5x24 TA52	8.5x20 TA52	8.5x20 TA35	7.5x16 TA35	7.5x14 TA35	7x16 TA35	7x14 TA35	







METALLICFINISH

Trailer Black

Victory Red

Polar White

Indigo Blue

Light Pewter

Silver Mist

Charcoal



Office: (269) 464-2620 White Pigeon, MI 49099 500 S Miller Drive

Fax: (269) 464-2621