



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST FULL TILT 15.4K**

	7 x 23	7 x 25	7 x 27
Model #	P-BTEF8218-154	P-BTEF8220-154	P-BTEF8222-154
CAPACITIES			
GVWR (lbs)		15400	
GAWR (lbs/axle)		7000	
Curb Weight	3800	4000	4200
Payload	11600	11400	11200
CHASSIS			
Frame	8", 15 lb/ft I-Beam		
Tongue	8" Flange, 13 lb/ft I-Beam		
Crossmembers	3" Steel Channel		
Integrated Step(s)	Side Steps		
Coupler	2-5/16" 4-Bolt Flat Plate		
Tongue Jack	12K, 2-Speed Drop Leg		
Ramp(s)	HD Diamond Plate Knife Edge Tail		
Fenders	Double Break Tread Plate		
Axle	(2) 7000 lb. Slipper Spring Brake		
Hubs	Oil Bath		
Tires	215/75R17.5J 18-PR		
Wheels	17.5", 8-Hole Steel		
Exterior Finish	Industrial Grade Polymer Finish		
Decking	2" Pressure Treated Pine		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Exterior Lights	Full LED, DOT Compliant		
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST FULL TILT 17.6K**

	7 x 23	7 x 25	7 x 27
Model #	P-BTEF8218-176	P-BTEF8220-176	P-BTEF8222-176
CAPACITIES			
GVWR (lbs)		17600	
GAWR (lbs/axle)		8000	
Curb Weight	4040	4240	4440
Payload	13560	13360	13160
CHASSIS			
Frame	8", 15 lb/ft I-Beam		
Tongue	8" Flange, 13 lb/ft I-Beam		
Crossmembers	3" Steel Channel		
Integrated Step(s)	Side Steps		
Coupler	2-5/16" 4-Bolt Flat Plate		
Tongue Jack	12K, 2-Speed Drop Leg		
Ramp(s)	HD Diamond Plate Knife Edge Tail		
Fenders	Double Break Tread Plate		
Axle	(2) 8000 lb. Slipper Spring Brake		
Hubs	Oil Bath		
Tires	215/75R17.5J 18-PR		
Wheels	17.5", 8-Hole Steel		
Exterior Finish	Industrial Grade Polymer Finish		
Decking	2" Pressure Treated Pine		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Exterior Lights	Full LED, DOT Compliant		
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST FULL TILT 22K**

	7 x 23	7 x 25	7 x 27
Model #	P-BTEF8218-220	P-BTEF8220-220	P-BTEF8222-220
CAPACITIES			
GVWR (lbs)		22000	
GAWR (lbs/axle)		10000	
Curb Weight	4440	4640	4840
Payload	17560	17360	17160
CHASSIS			
Frame	8", 15 lb/ft I-Beam		
Tongue	8" Flange, 13 lb/ft I-Beam		
Crossmembers	3" Steel Channel		
Integrated Step(s)	Side Steps		
Coupler	Adjustable 4-Bolt Pintle Ring		
Tongue Jack	12K, 2-Speed Drop Leg		
Ramp(s)	HD Diamond Plate Knife Edge Tail		
Fenders	Double Break Tread Plate		
Axle	(2) 10000 lb. Torsion Brake		
Hubs	Oil Bath		
Tires	215/75R17.5J 18-PR		
Wheels	17.5", 8-Hole Steel		
Exterior Finish	Industrial Grade Polymer Finish		
Decking	2" Pressure Treated Pine		
Tie Downs	(4) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets		
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier		
Exterior Lights	Full LED, DOT Compliant		
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST SPLIT TILT 15.4K**

	7 x 25	7 x 27	7 x 27	7 x 29
Model #	P-BTES82164-154	P-BTES82166-154	P-BTES82184-154	P-BTES82204-154
CAPACITIES				
GVWR (lbs)	15400			
GAWR (lbs/axle)	7000			
Curb Weight	4000	4200		4400
Payload	11400	11200		11000
CHASSIS				
Frame	8", 15 lb/ft I-Beam			
Tongue	8" Flange, 13 lb/ft I-Beam			
Crossmembers	3" Steel Channel			
Integrated Step(s)	Side Steps			
Coupler	2-5/16" 4-Bolt Flat Plate			
Tongue Jack	12K, 2-Speed Drop Leg			
Ramp(s)	HD Diamond Plate Knife Edge Tail			
Fenders	Double Break Tread Plate			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine			
Tie Downs	(6) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets			
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST SPLIT TILT 17.6K**

	7 x 22	7 x 25	7 x 27	7 x 29
Model #	P-BTES82166-176	P-BTES82164-176	P-BTES82184-176	P-BTES82204-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4450	4240	4440	4640
Payload	13150	13360	13160	12960
CHASSIS				
Frame	8", 15 lb/ft I-Beam			
Tongue	8" Flange, 13 lb/ft I-Beam			
Crossmembers	3" Steel Channel			
Integrated Step(s)	Side Steps			
Coupler	2-5/16" 4-Bolt Flat Plate			
Tongue Jack	12K, 2-Speed Drop Leg			
Ramp(s)	HD Diamond Plate Knife Edge Tail			
Fenders	Double Break Tread Plate			
Axle	(2) 8000 lb. Slipper Spring Brake			
Hubs	Oil Bath			
Tires	215/75R17.5J 18-PR			
Wheels	17.5", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine			
Tie Downs	(6) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets			
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



**SPECIFICATIONS -CAM TILT PBTEF154
CAM BEAST SPLIT TILT 22K**

	7 x 25	7 x 27	7 x 27	7 x 29	7 x 29	7 x 31
Model #	P-BTES82164-220	P-BTES82184-220	P-BTES82166-220	P-BTES82168-220	P-BTES82204-220	P-BTES82206-220
CAPACITIES						
GVWR (lbs)	22000					
GAWR (lbs/axle)	10000					
Curb Weight	4640	4840		5280	5040	5540
Payload	17360	17160		16720	16960	16460
CHASSIS						
Frame	8", 15 lb/ft I-Beam					
Tongue	8" Flange, 13 lb/ft I-Beam					
Crossmembers	3" Steel Channel					
Integrated Step(s)	Side Steps					
Coupler	Adjustable 4-Bolt Pintle Ring					
Tongue Jack	12K, 2-Speed Drop Leg					
Ramp(s)	HD Diamond Plate Knife Edge Tail					
Fenders	Double Break Tread Plate					
Axle	(2) 10000 lb. Torsion Brake					
Hubs	Oil Bath					
Tires	215/75R17.5J 18-PR					
Wheels	17.5", 8-Hole Steel					
Exterior Finish	Industrial Grade Polymer Finish					
Decking	2" Pressure Treated Pine					
Tie Downs	(6) 3/4" D-Rings, Banjo Tie-Downs, Oversize 5" x 1/4" Thick Stake Pockets, Stake Pockets					
Exterior Storage	Large Hydraulic Pump Box with Divider, Interior Light and Gas Spring, Spare Tire Carrier					
Exterior Lights	Full LED, DOT Compliant					
Hydraulic Components	Hydraulic Cushion Load Cylinder with Stop Valve					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.