



# SE03 2" X 3" Angle Frame Utility Trailer

## STANDARD FEATURES

- 2,990 lb GVWR
- 3,500 lb GAWR
- 3" Channel Tongue
- 2" X 3" Angle Frame
- 2" x 2" Angle, 24" OC Cross-members
- (1) 3,500 lb DEXTER Idler/Spring Axle
- Multi-Leaf Spring Suspension
- 15" 5-Hole Wheels w/ ST205/75 R15 LRC Tires
- (1) 2,000 lb Top-wind Jack
- 2" A-Frame Coupler
- Straight Deck With Board Slides
- (4) U-Hooks
- Smooth Plate Fenders (weld-on)
- Weld-On 2" x 2" Square Tube Side Rails
- Treated Pine Floor
- (2) Safety Chains
- LED Lighting
- 16 Ga. 4-Way Double-Insulated Harness w/4-way RV Plug & Front Polar Cord
- Mechanical and/or Chemical Pretreatment for Maximum Paint Adhesion
- Black Polyester TGIC Gloss Powder Topcoat With PRIMER STANDARD

Standard features shown are based on the SE03 model. Standard features vary by model. Axle options include electric, forward self-adjusting brakes, as well as electric over hydraulic brakes. Length restrictions apply on dove tail options. Rub Rail available with weld-on side rails only.



**LOAD TRAIL**  
Stock photo. May be shown with additional options.



### AXLE OPTIONS

3,500 Lb Dexter Electric/Spring (FSA)

### COUPLER OPTIONS

- 2" Adjustable Coupler
- 2" Cast A-Frame Coupler

### TAIL, GATES & RAMPS

- 2' Dove Tail
- 3', 4' or 5' Fold-up Gate
- 3', 4', or 5' Split Fold-up Gate
- 3', 4', or 5' HD Fold-up Gate
- 3', 4', or 5' Fold-In Gate
- Front-Mount Fold-Up Gate

### TAIL, GATES & RAMPS

- Spring Assist For Gate
- Side-Mount Gate
- Bi-Fold Gate
- Side Rail Ramps

### POPULAR OPTIONS

- ST225/75 R15 LRD Tires
- Rough Oak Floor
- Douglas Fir Floor
- Blackwood Lumber (classic or PRO)
- Steel Diamond Plate Floor
- 16" On-Center Cross-members
- Steel Diamond Plate Fenders
- Aluminum Fenders

### POPULAR OPTIONS

- 7K Drop-Leg Jack
- 5K Swivel Jack
- 3" D-rings
- Angle Iron Side Rails (weld-on or removable)
- Pipe-top Side Rails (weld-on or removable)
- Square Tube Side Rails (weld-on or removable)
- 16" Solid Metal Sides
- 16" Expanded Metal Sides
- Tongue-Mount Toolbox
- Trimmer Rack
- Rub Rail
- Rear Support Stands (Tube or Jacks)
- Additional Stake Pockets
- Spare Tire & Mount

**G.V.W.R.**  
2,990 lbs

**LENGTHS**  
8 - 14 ft

**WIDTHS**  
48 - 77"

**DECK HEIGHT**  
19"

**BASE WEIGHT**  
674 - 1,254 lbs

**G.A.W.R.**  
3,500 lbs/Axle