



Model	Axle Description	Tire Size	GAWR	GVWR
LOW PROFILE DUMP 14K				
12x83" DX14	2 - 7000# Dexter	ST235/80R/16 LRE	7000#	14000#
14x83" DX14	2 - Electric Brakes Nev-R-Adjust			
16x83" DX14	E-Z Lube - 1/2 Cambered			
LOW PROFILE GOOSENECK DUMP 14K				
	2 - 7000# Dexter	ST235/80R/16 LRE	7000#	14000#
14x83" DX14GN	2 - Electric Brakes Nev-R-Adjust			
16x83" DX14GN	E-Z Lube - 1/2 Cambered			

Standard Equipment

- Coupler: 2 5/16" Forged Adjustable 5/Position
- Coupler: 2 5/16" Round Adjustable on GN
- Jack: 10000# Drop Leg
- Jack: Dual 10000# Drop Leg on GN
- Fenders: HD Diamond Plate Straight
- Floor: 7 GA Sheet Metal
- Width: 83" Inside Box
- Brake: Electric All Wheel
- Break Away Unit w/Charger
- DOT Reflective Tape
- Primed & Painted Underside
- Doors: Double Action
- Ramp Pockets w/6' Ramps
- 5/8" D-Rings in Box
- Spare Rack
- Sealed Flush Mount LED Lights
- Wiring Harness
- Lockable Battery/Pump Box
- Deep Cycle 12V Marine Battery w/110V-5 Amp Charger
- Tarp
- Color: Black

Frame Structure

- Frame & Tongue: 8" I-Beam Integrated
- Neck & Risers: (GN Model) 10" I-Beam
- Sides: 24" Tall 10 GA Sheet Metal w/Toprail
- Toprail: Rigid 3x2x7 GA Rectangular Tubing
- Uprights: 24" OC
- Crossmembers: 3" Channel 16" OC
- Tarp Bracket & Tie Downs
- Loading Height 4" Lower than DP Model

Dump Components

- Hoist: Scissor Lift
- Power Up/Power Down
- Control: Pistol Grip w/10' Cord
- Safety Prop
- Caulked Seams on Dump Body

Options

- **DX14 Options**
- Deduct 6' Ramps
- 3' High Sides
- 4' High Sides
- Gas Engine Powered Pump in Lieu of Electric Pump
- Spare ST235/80R/16 LRE on 8-Hole
- Hydraulic Jack
- Solar Battery Charger