



Model	Axle Description	Tire Size	GAWR	GVWR
GOOSENECK 159 LO PROFILE				
20x102" GN 159	2 - 7000# Dexter	ST235/16R LRE	7000#	15900#
24x102" GN 159	2 - Electric Brakes Nev-R-Adjust			
28x102" GN 159	E-Z Lube - 1/2 Cambered			
32x102" GN 159				
36x102" GN 159				
20+5x102" GN 159				
24+5x102" GN 159				
25+5x102" GN 159				
27+5x102" GN 159				
30+5x102" GN 159				

Standard Equipment

- Coupler: 2 5/16" Round Adjustable
- Jack: Dual 10000# Drop Leg
- Floor: 2" Treated Pine
- Brake: Electric All Wheel
- Break Away Unit w/Charger
- Spare Tire Rack Inside Neck
- Lockable Toolbox Between Risers
- Winch Plate Between Risers
- Wiring Harness w/Sealed LED Lights
- Driver & Curb Side Steps w/Grab Handles
- DOT Reflective Tape
- Color: Black

Frame Structure

- Frame: 12"x14# I-Beam, 16# on 32' & Longer
- Neck: 12"x14# I-Beam
- Crossmembers: 3" Channel 16" OC
- Side Rails: 5" Channel
- 3/8x2 Flat Rubrail
- Stake Pockets 24" OC
- Pipe Spools Between Each Stake Pocket
- Frame to Crossmember Gussets
- Anti Flex Torx Tube on 32' & Longer
- Low Profile
- Dovetail w/Fold Over Spring Assist Ramps on +5 Models
- Deck Height: 33"

Options

- Spare ST235/80R/16 LRE on 8-Hole
- Upgrade to ST235/85R/16 LRG on 8-Hole
- Upgrade to 215/75R/17.5 LRH on 8-Hole w/Pressure Plate
- Spare 215/75R/17.5 LRH on 8-Hole
- Jumbo Ramps
- 3rd Ramp on Dovetail
- 7 1/2' Slide-N-Ramps
- Deck Over Neck
- 1" D-Rings

- Underbody Toolbox
- 2-7K Electric/Hydraulic Brakes w/Drum
- 2-7K Electric/Hydraulic Brakes w/Disc
- **Other Options Available**