



SPECIFICATIONS -MIDSOTA DECKOVER
MIDSOTA FBHB 22K

	102 x 30	102 x 32
Model #	N-FBHB30-220	N-FBHB32-220
CAPACITIES		
GVWR (lbs)	22000	
GAWR (lbs/axle)	10000	
Curb Weight	6800	7050
Payload	15200	14950
CHASSIS		
Coupler	Adjustable Pintle Ring, 30 Ton	
Tongue	High Strength Manufactured I-Beam	
Tongue Jack	12K Drop Leg, Set-Back	
Frame	High Strength Manufactured I-Beam, Square Torque Tube	
Crossmembers	3" Steel Channel, 16" On-Center	
Beavertail	10' Hydraulic Tail	
Axle	(2) 10000 lb. Slipper Spring Brake	
Hubs	Oil Bath	
Exterior Finish	Industrial Grade Polymer Finish	
Tires	ST235/80R16E 10-PLY	
Wheels	16" Dual, 8-Lug Steel	
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail	
Wiring	No Exposed Wiring	
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant	
Bulkhead	Custom Formed	
Mud Flaps	Yes	
Decking	2" Pressure Treated Pine	
Exterior Storage	A-Frame Tool Box with Lid Prop	
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)	
Coupler Height	0	
DIMENSIONS		
Coupler Height	0	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA DECKOVER
MIDSOTA FBHB 25.9K

	102 x 30	102 x 32	102 x 34	102 x 36
Model #	N-FBHB30-259	N-FBHB32-259	N-FBHB34-259	N-FBHB36-259
CAPACITIES				
GVWR (lbs)			25900	
GAWR (lbs/axle)			12000	
Curb Weight	6950	8130		7830
Payload	18950	17770		18070
CHASSIS				
Coupler	Adjustable Pintle Ring, 30 Ton			
Tongue	High Strength Manufactured I-Beam			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	High Strength Manufactured I-Beam, Square Torque Tube			
Crossmembers	3" Steel Channel, 16" On-Center			
Beavertail	10' Hydraulic Tail			
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension			
Hubs	Oil Bath			
Exterior Finish	Industrial Grade Polymer Finish			
Tires	ST235/80R16E 10-PLY			
Wheels	16" Dual, 8-Lug Steel			
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail			
Wiring	No Exposed Wiring			
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant			
Bulkhead	Custom Formed			
Mud Flaps	Yes			
Decking	2" Pressure Treated Pine			
Exterior Storage	A-Frame Tool Box with Lid Prop			
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)			
Coupler Height	0			
DIMENSIONS				
Coupler Height	0			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA DECKOVER
MIDSOTA FBHB GN 23K

	102 x	102 x	102 x	102 x	102 x 32
Model #	N-FBHB34-230G	N-FBHB40-230G	N-FBHB30-230G	N-FBHB36-230G	N-FBHB32-230G
CAPACITIES					
GVWR (lbs)	23000				
GAWR (lbs/axle)	10000				
Curb Weight	8130	8880	7630	8380	7880
Payload	14870	14120	15370	14620	15120
CHASSIS					
Coupler	2-5/16" Adjustable Gooseneck				
Tongue	Gooseneck, High Strength Manufactured I-Beam				
Tongue Jack	Dual 12K, 2-Speed Landing Gear				
Frame	High Strength Manufactured I-Beam, Square Torque Tube				
Crossmembers	3" Steel Channel, 16" On-Center				
Beavertail	10' Hydraulic Tail				
Integrated Step(s)	Side Steps				
Axle	(2) 10000 lb. Slipper Spring Brake, Hutch Spring Suspension				
Hubs	Oil Bath				
Exterior Finish	Industrial Grade Polymer Finish				
Tires	ST235/80R16E 10-PLY				
Wheels	16" Dual, 8-Lug Steel				
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail				
Wiring	No Exposed Wiring				
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant				
Bulkhead	Custom Formed				
Mud Flaps	Yes				
Decking	2" Pressure Treated Pine				
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier, Underbody Side Mount Control Box				
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)				
Coupler Height	0	32.25 - 40.25	0	0	32.25 - 40.25
Deck Height		34			34
DIMENSIONS					
Overall Length		594			498
Deck Height		34			34
Coupler Height	0	32.25 - 40.25	0	0	32.25 - 40.25

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	102 x	102 x 30	102 x 32	102 x 34	102 x 36	102 x 44
Model #	N-FBHB40-259G	N-FBHB30-259G	N-FBHB32-259G	N-FBHB34-259G	N-FBHB36-259G	N-FBHB44-259G
CAPACITIES						
GVWR (lbs)	25900					
GAWR (lbs/axle)	12000					
Curb Weight	8880	7630	7880	8130	8380	9336
Payload	17020	18270	18020	17770	17520	16564
CHASSIS						
Coupler	2-5/16" Adjustable Gooseneck					
Tongue	Gooseneck, High Strength Manufactured I-Beam					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Frame	High Strength Manufactured I-Beam, Square Torque Tube					
Crossmembers	3" Steel Channel, 16" On-Center					
Beavertail	10' Hydraulic Tail					
Integrated Step(s)	Side Steps					
Axle	(2) 12000 lb. Slipper Spring Brake, Hutch Spring Suspension					
Hubs	Oil Bath					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST235/80R16E 10-PLY					
Wheels	16" Dual, 8-Lug Steel					
Tie Downs	Stake Pockets, Chain Spools, and Rub Rail					
Wiring	No Exposed Wiring					
Exterior Lights	Dual Taillights and Mid Ship Turn Signals, Full LED, DOT Compliant					
Bulkhead	Custom Formed					
Mud Flaps	Yes					
Decking	2" Pressure Treated Pine					
Exterior Storage	Integrated Gooseneck Toolbox, Receiver Tube Winch Mount, Spare Tire Carrier, Underbody Side Mount Control Box					
Hydraulic Components	12 Volt Hydraulic Pump, Power-Up, Power-Down (Dual Ram)					
Coupler Height	0					
DIMENSIONS						
Coupler Height	0					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.