



WIDE DRIVE OVER GOOSENECK 14K



MODEL	AXLE DESCRIPTION	TIRE SIZE	GAWR
GOOSENECK WIDE DRIVE OVER 14K			
16x102" WD14GN	2 - 7000# Dexter	ST235/80R/16 LRE	7000#
18x102" WD14GN	2 - Electric Brakes Nev-R-Adjust		
20x102" WD14GN	E-Z Lube - 1/2 Cambered		
22x102" WD14GN			
24x102" WD14GN			
26x102" WD14GN			
28x102" WD14GN			
30x102" WD14GN			
32x102" WD14GN			

Standard Equipment

- ST235/80R/16 LRE Tires on 8-Hole
- 2-7000# Dexter Axles w/Electric Brakes
- Axles 1/2 Cambered w/EZ Lube Hubs
- 2 5/16" Round Adjustable Coupler
- Dual 10000# Drop Leg Jacks
- HD Diamond Plate Drive Over Fenders
- Treated Pine Floor
- Break Away Unit w/Charger
- Sealed Flush Mount LED Lights w/Wiring Harness
- Stake Pockets & Rubrail

- Spare Rack
- Color: Stock

Frame Structure

- Frame: 6" Channel on 16-24'
- Frame: 8" Channel on 26-32'
- Neck & Risers: 10"x12# I-Beam
- 4" Channel Truss from Fender to Front
- Crossmembers: 3" Channel 16" OC
- Flush Floor w/Side Extensions to 102"
- 83" Between Drive Over Fenders
- Stake Pockets w/3/8x2 Rubrail
- 2' Treadplate Dovetail
- 5/8" D-Rings (6)

Options

- **Ramps & Dovetail (Length of trailer may limit certain options)**
- Spare ST235/80R/16 LRE on 8-Hole
- Toolbox Between Risers
- Tread Plate Steel Floor
- Weld-on D-Rings 5/8" (Each)
- *5' Rear Slide Channel Ramps (Must Purchase 2 Rear Stabilizer Jacks)
- Rear Stabilizer Jack (5K Top Wind Pipe Mount)
- 5' Fold-up Channel Ramp w/Adjustable Knees & Spring Assist
- 5' XM Fold Up Channel Ramp w/Adjustable Knees & Spring Assist
- **Above Ramp is 24" Wide Covered w/Expanded Metal**
- **3' Self Cleaning Cleated Dovetail & 3' Mini Jumbo Spring Assist Ramps (Must be 20' or longer)
- 3-4' Dovetail ILO 2' Dovetail
- 2' Self Cleaning Cleated Dovetail ILO 2' Treadplate Dovetail
- *Rear Slide-N Ramps on 16' will be 4 1/2'. Rear Slides NA on 12-14'.
- **Jumbo Ramps NA on lengths less than 20'